ADC 14.1 Syslog Message Reference

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
TCP	CONN_DELINK	INFO	When a server side and a client side TCP connection is delinked.These are the connections which are being tracked by netscaler like HTTP	"Source%s:%d-Vserver%s:%d-NatIP%s:%d-""Destination%s:%d-DelinkTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu"	
TCP	CONN_TERMINATE	INFO	When a TCP connection termin	"Source%s:%d-Destination%	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			ates.The logged data indicates the number of bytes transmitted and received over the connection and lso the connection start and end time	s: %d-"" StartTime%s - EndTime%s - Total_bytes_send%llu-""Total_bytes_recv%llu"	
TCP	OTHERCONN_DELINK	INFO	When a server side and a client side TCP connection is delink	"Source%s: %d- Vserver%s: %d- NatIP %s: %d-"" Destination%s:%d-	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			ed.These are the connections which are not being tracked by netscaler like FTP,telnet etc	DelinkTime%s""Total_bytes_send%u-Total_bytes_recv%u"	
TCP	NAT_CONN_DELINK	INFO	When a server side and a client side TCP connection for RNAT are delinked we need to log the connection	"Source%s:%d-Destination%s:%d-NatIP%s:%d-"" Destination%s:%d-StartTime%s-DelinkTime%s-Total_bytes_send%	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			information	llu-""Total_bytes_recv%llu-ClosureReason%s"	
TCP	NAT_OTHERCONN_DELINK	INFO	When a server side and a client side TCP connection for RNAT are delinked we need to log the connection information	"Source%s:%d-Destination%s:%d-NatIP%s:%d-""Destination%s:%d-StartTime%s-DelinkTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu-ClosureReason%s"	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
ACL	ACL_PKT_LOG	INFO	ACL Packet Log	"Source%s-->Destination%s-""ProtocolICMP-""Type%d-Code%d-""TimeStamp%d(ms)-Hitcount%d-HitRule%s-Action%s-Data"	
ACL	ACL6_PKT_LOG	INFO	ACL6 Packet Log	"Source%s-->Destination%s-""ProtocolICMP-""Type%d-Code%d-""TimeStamp%d(ms)-Hitcou	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT				
				nt%d-HitRule%s-Action%s-Data"				
LSN	LSN_SESSION	INFO	Info of LSN session created	"S%s%s	C-%s:%d:%d	N-%s:%d	D-%s:%d:%d	%s"
LSN	LSN_EIM_MAPPING	INFO	Info of LSN Endpoint independent mapping created	"EIM%s%s	C-%s:%d:%d	N-%s:%d	%s"	
LSN	LSN_ADDR_MAPPING	INFO	Info of LSN Address dependent mapping created	"ADM%s%s	C-%s:%d:%d	N-%s:%d	D-%s:%d	%s"
LSN	LSN_ADDRPORT	INFO	Info of LSN Address and	"A&PDM%s%s	C-%s:%d:%d	N-%s:%d	D-%s:%d:%d	%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT				
	_MAPPING		Port dependent mapping created					
LSN	PPTP_LOG	INFO	Info of PPTP connection	"PPTP:%sid:%dfrom:%sto:%sNatIP:%sext-id:%d\n"				
LSN	LSN_PORTBLOCK	INFO	Info of LSN Portblock mappings	"PB%s%s	C-%s	N-%s:%d-%d	%s"	
LSN	LSN_DETERMINISTIC	INFO	Info of LSN Portblock mappings	"DTR%s%s	C-%s	N-%s:%d-%d"		
ALG	ALG_SIP_PARSE_PACKET_	ERROR	Error of SIP packet parsing	maxprintsize)				

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	EVENT				
ALG	ALG_SDP_PARSE_PACKET_EVENT	ERROR	Error of SDP packet parsing	"Errmsg: \"%s\"-""Group: %s-"" Call_ID: %s-""Transport: %s-"" Source_IP: %s-"" Source_port: %u-"" Destination_IP: %s-"" Destination_port: %u-"" Natted_IP: %s-"" Natted_port: %u-"" Method: %s-""	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				Sequence_Number: %u-"" Register: %s-"" Content_Type: %s-"" Error: \"%s\"-""Error_line: \"%s\"-""Caller_user_name: %s-"" Callee_user_name: %s-"" Caller_domain_name: %s-"" Callee_domain_name: %s-"	
ALG	ALG_SIP_ERROR	Error of SIP		maxprintsize)	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	RROR_PACKET_EVENT		protocol		
ALG	ALG_DHT_ERROR_PACKET_EVENT	ERROR	Error of SIP ALG DHT	"Errmsg: \"ErrorinDHT HandlingforSIPrequest\"-"" Group: %s-"" Call_ID: %s-""Transport: %s-"" Source_IP: %s-"" Source_port: %u-"" Destination_IP: %s-"" Destination_port: %u-"" Natted_IP:	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				%s-"" Natted_port: %u-"" Method: %s-"" Sequence_Number: %u-"" Register: %s-"" Content_Type: %s-"" Caller_user_name: %s-"" Callee_user_name: %s-"" Caller_domain_name: %s-"" Callee_domain_name: %s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
ALG	ALG_SIP_GENERATE_ERROR_PACKET_EVENT	ERROR	Error of SIP generate	"Errmsg: \"SIPALGgenetateerror\"-""Error_Code: %u-""Group: %s"	
ALG	ALG_SIP_INFO_PACKET_EVENT	INFO	Info of SIP packet	"Infomsg: \"SIPrequest\"-""Group: %s-""Call_ID: %s-""Transport: %s-""Source_IP: %s-""Source_port: %u-""Destination_IP: %s-""Destination_	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				port: %u-"" Natted_IP: %s-"" Natted_port: %u-"" Method: %s-"" Sequence_Number: %u-"" Register: %s-"" Content_Type: %s-"" Caller_user_name: %s-"" Callee_user_name: %s-"" Caller_domain_name: %s-"" Callee_domain_na	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				me: %s-"	
ALG	ALG_SIP_INFO_DELETE_CALL_PACKET_EVENT	INFO	Info of SIP call deletion	maxprintsize)	
ALG	ALG_RTSP_INFO_PACKET_EVENT	INFO	Info of RTSP packet	maxprintsize)	
ALG	ALG_RTSP_INFO_DELETE_CALL_PACKET_EVENT	INFO	Info of RTSP call deletion	"Infomsg: \"LoginfoRTSPALG calldeletion\"-""Group: %s-"" Session_ID: %s-"	
ALG	ALG_RTSP_PARSE_PACKE	ERROR	Error of RTSP packet	maxprintsize)	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	T_EVENT		parsing		
ALG	ALG_RTSP_ALG_PACKET_EVENT	ERROR	Error of RTSP ALG	maxprintsize)	
ALG	ALG_RTSP_DHT_PACKET_EVENT	ERROR	Error of RTSP DHT	maxprintsize)	
DNS	DNS_QUERY	INFO	Information of DNS queries recieved by the DNS endpoints on NetScaler	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
DNS	DNS_RESPONSE	INFO	Information of DNS responses served by the DNS endpoints on NetScaler to clients	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"	
DNS	DNS_ERROR	INFO	Information of errors encountered during DNS packet processing on NetScaler	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
SUBSCRIBER	SESSION_EVENT	INFO	Subscriber Session Event Info	"Session%s	
SUBSCRIBER	SESSION_FAILURE	ERROR	Subscriber Session Failure Info	"FailureReason:%s	
SSLI	INTERCEPT_LOG	INFO	SSL Interception Success Log	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"	
SSLI	BYPASS_LOG	INFO	SSL Interception Bypass Log	"Source%s:%d-Destination%s:	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"	
SSLI	DROPPED_LOG	INFO	SSL Interception Dropped Log	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"	
URLFILT	URLFILT_LOG	INFO	URL filtering Log	"Source%s-Destination%s""URL%s-""Categ	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				ory%s-Categorygroup%s-Reputation%d-""Policyaction%s"	
CI	ICAP_LOG	INFO	ICAP transaction Log.	"Source%s:%d-"" Destination%s:%d-"" Domain%s-"" Content-Type%s-""ICAPServer%s:%d-"" Mode%s-"" Service%s-"" Response%d-""Action%s"	
CI	ICAPC_LOG	INFO	ICAP custom log.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
CI	INLINE_INSPECTION_LOG	INFO	Inline Inspection transaction Log.	"ID%lld-""Source%s: %d-"" Destination%s: %d-"" Protocol%s-"" "URL %s-"" Domain%s-"" Service%s-"" %s%s-""Action%s-""BytesSent %lld-"" Bytes Received%lld-""OriginServer%s: %d"	
CI	TRAFFIC_MIRROR_LOG	INFO	Traffic Mirror transaction Log.	"ID%lld-""Source%s: %d-"" Destination%s:	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				%d-""Protocol%s-""URL%s-""Domain%s-""Service%s-""%s%s-""Action%s-""RequestBytesSent%lld-""ResponseBytesSent%lld-""OriginServer%s:%d"	
AAA	LOGIN_FAILED	WARNING	When the aaa module failed to login the user.The reason for failure	"User%s-Client_ip%s-Failure_reason\"%s\"-Browser%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			is indicated in the message		
AAA	EXTRACTED_GROUPS	INFO	After a user logs in the group for the user has been extracted	"Extracted_groups\"%s\""	
UI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-ADM_User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""	
SSLVPN	LOGIN	INFO	SSLVPN login succeeds	"User%s-Client_ip%s-""Nat_ip%s-Vserv	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				er%s:%d-Browser_type\"%s\"-SSLVPN_client_type%s-Group(s)\"%s\""	
SSLVPN	LOGOUT	INFO	SSLVPN session logout.Logout method is captured in the message	"User%s-""Client_ip%s-Nat_ip%s-""Vserver%s:%d-""Start_time\"%s\"-End_time\"%s\"-Duration%s-""Http_resources_accessed%s-NonHttp_services_	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				accessed%s-""Total_TCP_connections%d-Total_UDP_flows%d-""Total_policies_allowed%d-Total_policies_denied%d-""Total_bytes_send%s-Total_bytes_recv%s-""Total_compressedbytes_send%s-Total_compressedbytes_recv%s-""Compres	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				sion_ratio_send%d.%02u%%-""Compression_ratio_recv%d.%02u%%-""LogoutMethod\"%s\"-Group(s)\"%s\""	
SSLVPN	ICASTART	INFO	ICA application launch has started	"[TECHSUPPORT][LAUNCH][%s][%s][ICAUUID=%s]""Source%s:%d-Destination%s:%d-""	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				SSLRelayAddress %s: %d-""customername%s-""username:domainname%s-""applicationName%s-startTime\"%s\"-""connectionId%x"	
SSLVPN	ICAEND_CONNSTAT	INFO	ICA application has terminated	"[TECHSUPPORT] [LAUNCH] [%s] [%s] [ICAUUID=%s]""Source %s: %d-Destination%	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				s: %d-"" SSLRelayAddress %s: %d-""customernamе%s-"" username:domainname%s-""startTime\"%s\"-endTime\"%s\"-""Duration%s-Total_bytes_send%u-Total_bytes_recv%u-""Total_compressedbytes_send%u-Total_compressed bytes_	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				recv%u-""Compression_ratio_send%d.%02u%%-Compression_ratio_recv%d.%02u%%-""connectionId%x"	
SSLVPN	TCPCONNSTAT	INFO	Logs the TCP connection related information for a connection belonging to a SSLVPN session	"User%s-Client_ip%s-Nat_ip%s-Vserver%s:%d-"" Source%s:%d-Destination%s:%d-Start_time\"%s\"-	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				End_time\"%s\"-""Duration%s-Total_bytes_send%d-Total_bytes_recv%d-""Total_compressedbytes_send%d-Total_compressedbytes_recv%d-""Compression_ratio_send%d.%02u%%-Compression_ratio_recv%d.%02u%%-Acces	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				s%s-Group(s) \"%s\""	
SSLVPN	TCPCONN_TIMEDOUT	INFO	An SSLVPN connection timed out.The information about the connection start and end time the amount of data transferred and received are present in the message date	"User %s-Client_ip%s-""Nat_ip%s-Vserver%s:%d-Last_contact\"%s\"-Group(s) \"%s\""	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
SSLVPN	UDPFLOWSTAT	INFO	When a UDP flow , within a SSLVPN session, terminates	"[TECHSUPPORT] User%s- Client_ip%s- ""Nat_ip%s- Vserver%s: %d- Source%s: %d-"" Destination%s:%d- Start_time\" %s\"- End_time\"%s\"-""Duration %s- Total_bytes_send%d-""Total_bytes_recv%d- Access%s- Group(s) \"%s\""	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
SSLVPN	HTTPREQUEST	INFO	A SSLVPN session receives a HTTP request	"[TECHSUPPORT][ENUMERATION]%sUser%s: Group(s) %s:Vserver %s: %d-%s:"" Message=SSOis%s: %s%s%s"	
SSLVPN	NONHTTP_RESOURCEACCESS_DENIED	NOTICE	A non-http resource access is denied by policy engine. The denied policy name is captured in	"-Denied_by_policy\"%s\""	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			the log message.		
SSLVPN	HTTP_RESOURCEACCESS_DENIED	NOTICE	A http resource access is denied by policy engine. The denied policy name is captured in the log message.	"-Denied_by_policy\"%s\""	
SSLVPN	LICLMT_REACHED	INFO	SSLVPN license limit reached	"Vserver%s:%d-License_limit%d"	
SSLVPN	CLISEC_CHECK	ERROR	Logs with severity ERROR when client securit	"%s:%s-ClientIP%s-Vserver%s:%d-Client_secur	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			y check for a SSLVPN session fails, otherwise logs with severity DEBUG	ity_expression\"%s\"-"	
SSLVPN	CLISEC_EXP_EVAL	ERROR	Logs with severity ERROR when client security expression evaluates to False, otherwise logs with severity DEBUG	"User %s:-ClientIP%s-Vserver%s:%d-"" Clientsecurity check %s%s(%d)onthecli entmachine"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
SSLVPN	STA_VALIDATE_RESP	INFO	After a user logs into SSLVPN and the group for the user has been extracted	"Xdatalen%d-Xdata%s"	
SSLVPN	REMOVE_SESSION_DEBUG	DEBUG	Gives debug information of session before removing session intentionally	"Sessionid%u-""User%s-""Client_ip%s-Nat_ip%s-""Vserver_ip%s-""Errmsg\"%s\"""	
EVENT	ALERTSTARTED	ALERT	When SNMP module starts an alarm (usuall	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			y when the value of a monitored attribute crosses the threshold value		
EVENT	ALERTENDED	ALERT	When SNMP module stops an alarm (usually when the value of a monitored attribute returns to normal state)	"%s"	
EVENT	STARTSYS	INFO	When NetSc	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			aler starts		
EVENT	STARTCPU	INFO	When a particular CPU starts	"%s"	
EVENT	DEVICEDOWN	NOTICE	When ever a device is down	"%s"	
EVENT	DEVICEOFS	NOTICE	When ever a device is out of service	"%s"	
EVENT	DEVICEUP	NOTICE	When ever a device is up	"%s"	
EVENT	NICSTART	NOTICE	When the network interface is started	"%s"	
EVENT	NICSTOP	NOTICE	When the networ	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			k interface is stopped		
EVENT	NICHANG	NOTICE	When the network interface is in hung state	"%s"	
EVENT	NICRESET	NOTICE	When the network interface is reset	"%s"	
EVENT	NICMIGRATE	NOTICE	When an interface is bound or unbound from a channel	"%s"	
EVENT	STOPSYS	INFO	When the NetScaler	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			system is stopped		
EVENT	FREEBADMEM	EMERGENCY	When bad memory is freed (internal error)	"%s"	
EVENT	FREEDUPMEM	EMERGENCY	When duplicate memory free occurs (internal error)	"%s"	
EVENT	FREEEXTMEM	EMERGENCY	When memory is freed from a wrong pool (internal error)	"%s"	
EVENT	PROPSUCCESS	INFO	When HA propagation is	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			successful		
EVENT	PROPFAIL	ALERT	When HA propagation fails	"%s"	
EVENT	STATECHANGE	0	HA State has changed.The string along with the message gives more information	"%s"	
EVENT	CLSTATECHANGE	0	Cluster State has changed.The string along with the message gives more	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			information		
EVENT	CACHESTARTFLUSH	INFO	When cache flush starts	"%s"	
EVENT	CACHESTOPFLUSH	INFO	When cache flush is complete	"%s"	
EVENT	MONITORTH	INFO	The monitor bound to the service has hit threshold limit	"%s"	
EVENT	MONITORDOWN	INFO	The monitor bound to the service is down.	"%s"	
EVENT	MONITORUP	INFO	The monitor bound	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			to the service is up.		
EVENT	ROUTEDOWN	INFO	When the route is down	"%s"	
EVENT	ROUTEUP	INFO	When the route is up	"%s"	
EVENT	VRID6DOWN	INFO	When the vrid changes state to backup	"%s"	
EVENT	VRIDDOWN	INFO	When the vrid changes state to backup	"%s"	
EVENT	VRIDUP	INFO	When the vrid chang	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			es state to master		
EVENT	VRIDINIT	INFO	When the vrid changes state to init	"%s"	
EVENT	VIPRHIUP	INFO	When the rhi state of vip changes to up	"%s"	
EVENT	VIPRHIDOWN	INFO	When the rhi state of vip changes to down	"%s"	
EVENT	STARTSAVECONFIG	INFO	When save configuration started	"%s"	
EVENT	STOPSAVECONFIG	INFO	When save configuration has	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			stopped		
EVENT	CONFIGSTART	INFO	When NetScaler starts to read the configuration from ns.conf file (during boot-up)	"%s"	
EVENT	CONFIGEND	INFO	When NetScaler has completed reading the configuration from ns.conf file (during boot-up)	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
EVENT	NICLACPSC	NOTICE		"%s"	
EVENT	NICLOW_THROUGHPUT	NOTICE	When an interface's throughput is less than the min required	"%s"	
EVENT	NICNORMAL_THROUGHPUT	NOTICE	When an interface's throughput is equal or greater than the min required	"%s"	
EVENT	NICPOWERON	NOTICE	When an interface is powered on	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
EVENT	NICPOWEROFF	NOTICE	When an interface is powered off	"%s"	
EVENT	DHCPSVRERR	INFO	When the DHCP server sends an invalid setting	"%s"	
EVENT	DHCPCAQUIRE	INFO	When the DHCP client aquires a lease	"%s"	
EVENT	DHCPCRELEASE	INFO	When the DHCP client releases a lease	"%s"	
EVENT	DHCPCDEPENDPBR	INFO	When the DHCP lease is released and	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			a PBR is dependent on the lease ip		
EVENT	ROUTE6DOWN	INFO	When the route6 is down	"%s"	
EVENT	ROUTE6UP	INFO	When the route6 is up	"%s"	
EVENT	MEPDOWN	NOTICE	Mep is down.	"%s"	
EVENT	MEPUP	NOTICE	Mep is up.	"%s"	
EVENT	BACKUPMEPDOWN	NOTICE	Backup Mep is down.	"%s"	
EVENT	BACKUPMEPUP	NOTICE	Backup Mep is up.	"%s"	
EVENT	NWMEPDOWN	NOTICE	Network metric Mep is down.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
EVENT	NWMEPUP	NOTICE	Network metric Mep is up.	"%s"	
EVENT	BACKUPMEP6DOWN	NOTICE	Backup ipv6 Mep is down.	"%s"	
EVENT	BACKUPMEP6UP	NOTICE	Backup ipv6 Mep is up.	"%s"	
EVENT	UNKNOWN	DEBUG		"%s"	
SSLLOG	SSL_HANDSHAKE_FAILURE	DEBUG	SSL HandShake Failure	"BackendSPCBId %d-ServerIP%s-ServerPort%d-""Protocol Version%s-CipherSuite\"%s\"-""Session%s"	
SSLLOG	SSL_HAND	DEBUG	SSL HandS	"BackendSP	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	SHAKE_SUCCESS		hake Success	CBId %d- Server IP%s- Server Port% d-""Protocol Version%s- Cipher Suite\" %s\"-"" Session%s"	
SSLLOG	SSL_CERT_EXPIRY_IMMINENT	NOTICE	SSL Certificate Expiry Imminent	"CertificateKeyPair %s- DaysToExpire%u"	
SSLLOG	SSL_HANDSHAKE_ISSUERNAME	DEBUG	SSL Client Certificate Issue Name	"SPCBId%d- IssuerName\ "%s\""	
SSLLOG	SSL_HANDSHAKE_SUBJECTNAME	DEBUG	SSL Client Certificate SubjectName	"SPCBId%d- SubjectName \"%s\""	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
SSLLOG	SSL_CRL_UPDATE_SUCCESS	NOTICE	SSL CRL Update Success	"crl_name%s-server_ip%s-server_port%d-""methodLDAP-ldapscope%s-"	
SSLLOG	SSL_CRL_UPDATE_FAILURE	NOTICE	SSL CRL Update Failure	"crl_name%s-server_ip%s-server_port%d-""methodLDAP-ldapscope%s-"	
SSLLOG	SSL_OCSPURL_RESOLVE_SUCCESS	DEBUG	SSL OCSP URL Resolve Success	"Domainname%sIpaddress%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
SSLLOG	SSL_OCSPURL_RESOLVE_FAILURE	DEBUG	SSL OCSP URL Resolve Failure	"Domainname%sIpaddress%s"	
SSLLOG	SSL_OCSPRESPONSE_SUCCESS	DEBUG	SSL OCSP Response Success	"%02x "	
SSLLOG	SSL_OCSPRESPONSE_FAILURE	DEBUG	SSL OCSP Response Failure	"%02x "	
SSLLOG	SSL_HANDSHAKE_FAILURE_INFO	INFO	SSL HandShake Failure	"BackendSPCBId%d-ServerIP%s-ServerPort%d-""Protocol Version%s-CipherSuite\"%s\"-""Session%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
SSLLOG	SSL_HANDSHAKE_SUCCESS_INFO	INFO	SSL HandShake Success	"BackendSPCBId %d-Server IP%s-Server Port%d-""Protocol Version%s-Cipher Suite\"%s\"-""Session%s"	
SSLLOG	SSL_HANDSHAKE_ISSUERNAME_INFO	INFO	SSL Client Certificate Issue Name	"SPCBId%d-Issuer Name\"%s\""	
SSLLOG	SSL_HANDSHAKE_SUBJECTNAME_INFO	INFO	SSL Client Certificate SubjectName	"SPCBId%d-SubjectName\"%s\""	
APPFW	APPFW_STARTURL	INFO	AppFw StartURL	"DisallowIllegalUR	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			violation	L.");} else{	
APPFW	APPFW_MULTIPLE_HEADER	INFO	AppFw Multiple Header violation	"Multiplehead ersoftype%sinrequest."	
APPFW	APPFW_XMLPAYLOAD_CONTENT_TYPE_MISMATCH	INFO	AppFw Infer Content-Type Payload violation	"XML Mismatchedcontent-typein HTTP headerdetected=\"%s\"."	
APPFW	APPFW_LOGEXPRESSION	INFO	AppFw Log Expression details	"%.*s"	
APPFW	APPFW_DENYURL	INFO	AppFw DenyURL violation	"DisallowDenyURL forrulepattern=\"%s\"."	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_CONTENT_TYPE	INFO	AppFw Content-type violation	"Unknowncontent-typeheadervalue=\"%s\"."	
APPFW	APPFW_REFERER_HEADER	INFO	AppFw Referer header violation	"parsingrefererheader'%s'failed"	
APPFW	APPFW_CSRF_TAG	INFO	AppFw CSRF tag violation	"CSRFTagvalidationfailed");}else{	
APPFW	APPFW_XSS	INFO	AppFw XSS violation	"%s"	
APPFW	APPFW_XML_XSS	WARNING	AppFw XSS violation in XML	"%s"	
APPFW	APPFW_SQL	INFO	AppFw SQL Injection	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			violation		
APPFW	APPFW_SQL_GRAM	INFO	AppFw SQL Injection violation reported by SQL Grammar	"%sGrammar-based SQLidetectedfor%s%s=\"%s\""	
APPFW	APPFW_XML_SQL	WARNING	AppFw SQL Injection violation in XML	"%s"	
APPFW	APPFW_CMD	INFO	AppFw CMD Injection violation	"%s"	
APPFW	APPFW_CMD_GRAM	INFO	AppFw CMD Injection violation reported by	"%sGrammar-based CMDidetectedfor%	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			CMD Grammar	s%s=\"%s\""	
APPFW	APPFW_COOKIE	INFO	AppFw Cookie Consistency violation	"%s"	
APPFW	APPFW_FIELDCONSISTENCY	INFO	AppFw Field Consistency violation	"%s"	
APPFW	APPFW_FILE_UPLOAD_TYPE	INFO	AppFw File Upload Type violation	"%s"	
APPFW	APPFW_BUFFEROVERFLOW_URL	INFO	AppFw Buffer Overflow violation in URL	"URLlength(%d)isgreaterthanmaximumallowed(%d)."	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_BUFFEROVERFLOW_COOKIE	INFO	AppFw Buffer Overflow violation in Cookie	"Cookieheaderlength(%d)isgreaterthanmaximumallowed(%d)."	
APPFW	APPFW_BUFFEROVERFLOW_HDR	INFO	AppFw Buffer Overflow violation in HTTP Headers	"Header(%s)length(%d)isgreaterthanmaximumallowed(%d)."	
APPFW	APPFW_BUFFEROVERFLOW_QUERY	INFO	AppFw Buffer Overflow violation in Query string	"Querystringlength(%d)isgreaterthanmaximumallowed(%d)."	
APPFW	APPFW_BUFFEROVERFLOW_TOT	INFO	AppFw Buffer Overflow violati	"Total HTTP headerlength(%d)isgreate	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	AL_HDR		on in total HTTP header length	rthan maximumallowed(%d)."	
APPFW	APPFW_FIELDFORMAT	INFO	AppFw Field Format violation	"%s"	
APPFW	APPFW_SAFECOMMERCE	INFO	AppFw Safe Commerce violation	"%s"	
APPFW	APPFW_SAFECOMMERCE_XFORM	INFO	AppFw Safe Commerce violation detected and transformed	"%s"	
APPFW	APPFW_SAFEOBJECT	INFO	AppFw Safe Object violation	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_POLICY_HIT	INFO	AppFw profile invoked	"%s%u-PPE%u%s%s%s<%s>"	
APPFW	APPFW_POLICY_HIT_BUILTIN	INFO	AppFw built-in profile invoked	"%s"	
APPFW	APPFW_MAX_UPLOADS	INFO	File uploads exceed the allowed number	"%s"	
APPFW	APPFW_SIGNATURE_MATCH	INFO	AppFw signature violation	"%s"	
APPFW	AF_BIND_TO_PROFILE	INFO	AppFw rule bound to HTML profile	"Profile:%s	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	AF_BIND_XML_TO_PROFILE	INFO	AppFw rule bound to XML profile	"Profile:%s	
APPFW	AF_ADD_FIELDTYPE	INFO	Add an AppFw Field Type	"Field Type: %s	
APPFW	AF_ADD_PROFILE	INFO	Add an AppFw profile	"Profile: %s\n"	
APPFW	AF_RM_FIELDTYPE	INFO	Remove an Appfw Field Type	"Field Type: %s	
APPFW	AF_RM_PROFILE	INFO	Remove an AppFw profile	"Profile: %s\n"	
APPFW	AF_ADD_CFFIELD	INFO	Add a confidential field	"Field Name: %s	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	AF_RM_CFFIELD	INFO	Remove a confidential field	"Field Name: %s	
APPFW	AF_400_RESP	INFO	AppFw Request error. Generated 400 Response	"%s"	
APPFW	AF_5XX_RESP	INFO	Server Error. Generated 5XX Response	"%s"	
APPFW	AF_RESPONSE_PARSE_ERR	INFO	Response parse error	"Badresponseeachehead er"');	
APPFW	AF_MEMORY_ERR	WARNING	Memory allocation request for %lu	"Contentlengthistoolarge(%lluBytes).Memory	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			bytes failed	Allocationfailed."	
APPFW	AF_ORIGIN_SERVER_RESP_MISMATCH_ERR	WARNING	Origin server sent a response but AppFw needed something different	"Partial(range)requestsenttobackendserverincorrectly");	
APPFW	AF_MALFORMED_REQ_ERR	INFO	Malformed request	"Malformed multi-partrequest-connectionreset");break;	
APPFW	AF_UTHREAD_STACK_ERR	ERROR	Appsecure uthread at 0x%x had a stack error	"Uthreadstackpointerover flowed:");	
APPFW	AF_SIGNAT	INFO	Signature error	"Signatureid %ucon	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	URE_ERR			tainsnofastmatchpattern"	
APPFW	AF_STREAM_MSG_ERR	WARNING	Stream message error	"Lookupofprofilename");	
APPFW	AF_GENERIC_ERR_WITH_URL	WARNING	Generic error with URL	"Internalerror:additionaldatagenerateddafterpartialresponsefor");	
APPFW	APPFW_XML_ATTACHMENT_FOUND	WARNING	Attachment Found in the XML Message.	"%s"	
APPFW	APPFW_XML_ATTACHMENT_ERR_CALLBACK	WARNING	XML Attachment CallBack is NULL but HTTP message is	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT			
	_NULL		MIME Attachment message.				
APPFW	APPFW_XML_ATTACHMENT_ERR_INVALIDHEADER	WARNING	String %s is supposed to be MIME Header. But it is not according to the format of Mime Header HeaderName:HeaderValue	"%s"			
APPFW	APPFW_XML_ATTACHMENT_ERR_INVALID_HEADER	WARNING	HTTP Content type should be 'application/xop+x	application)/([a-zA-Z]*\+xml	xml)' but we got %s.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT			
			ml' or '\^(text				
APPFW	APPFW_XML_ATTACHMENT_ERR_BOUNDARY_MISMATCH	WARNING	Boundary mismatch in mime message.	"%s"			
APPFW	APPFW_XML_ERR_NO_ATTACHMENT_BOUNDARY	WARNING	The message having content-type as 'Multipart/Related' and not having a boundary is invalid.	"%s"			
APPFW	APPFW_XML_ATTACHMENT_ERR_	WARNING	XML Message has an Attachment	"%s"			

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	MAX_SIZE		with size greater than the Configured Max Attachment Size.		
APPFW	APPFW_XML_ATTACHMENT_ERR_CONTENT_TYPE	WARNING	XML Message has an Attachment with Illegal Content-Type	"%s"	
APPFW	APPFW_XML_DDOS_ERR_MSG_SEND_FAIL	WARNING	AppFw XML DDoS Send Fail Error.	"%s"	
APPFW	APPFW_XML_DOS_ERR_CHAR_DATA_L	WARNING	Exceeds max character	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	ENGTH		data length.		
APPFW	APPFW_XML_DOS_ERR_DTD	WARNING	DTD present in the XML message.	"%s"	
APPFW	APPFW_XML_DOS_ERR_EXT_ENTITY	WARNING	External entities present in the XML message.	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX	WARNING	AppFw XML DoS Maximum Error	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTES	WARNING	Element '%s' exceeds maximum attributes per element.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_NAME_LENGTH	WARNING	In element '%s' an attribute exceeds maximum name length.	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_VALUE_LENGTH	WARNING	In element '%s' attribute '%s' exceeds maximum attribute value length.	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENTS	WARNING	Element '%s' exceeds maximum elements per message.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_CHILDREN	WARNING	Parent of element '%s' exceeds maximum children at element '%s'.	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_DEPTH	WARNING	Element '%s' exceeds maximum element depth.	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_NAME_LENGTH	WARNING	Element '%s' exceeds maximum element name length.	"%s"	
APPFW	APPFW_XML_DO	WARNING	Message size	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	S_ERR_MAX_FILE_SIZE		exceeds max size.		
APPFW	APPFW_XML_DOS_ERR_MAX_NODES	WARNING	Node '%s' exceeds maximum nodes per message.	"%s"	
APPFW	APPFW_XML_DOS_ERR_MIN_FILE_SIZE	WARNING	Message size less than min size.	"%s"	
APPFW	APPFW_XML_ERR_NOT_WELLFORMED	WARNING	Message is not a well-formed XML.	"%s"	
APPFW	APPFW_XML_DOS_ERR_PI	WARNING	Processing instructions present in the	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			XML message.		
APPFW	APPFW_XML_DOS_ERR_MAX_NAMESPACES	WARNING	Element '%s' exceeds maximum active namespaces.	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX_NAMESPACEURI_LENGTH	WARNING	In element '%s' a namespace exceeds maximum uri length.	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSION_DEPTH	WARNING	Exceeds max entity expansion depth	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSIONS	WARNING	Exceeds max number of entity expansions	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_SIZE	WARNING	Exceeds max total SOAP array size	"%s"	
APPFW	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_RANK	WARNING	Exceeds max SOAP array rank	"%s"	
APPFW	APPFW_XML_ERR_CUSTOM	WARNING	AppFw XML internal error	"%s"	
APPFW	APPFW_XM	WARNING	AppFw XML	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	L_ERR_DDOS_CONNECT_TO_SERVER_FAILED		DDoS Connect to Server Failed.		
APPFW	APPFW_XML_ERR_DDOS_INTERATION_SOCKET_OPEN_FAIL	WARNING	AppFw XML DDoS Interaction socket open Failed.	"%s"	
APPFW	APPFW_XML_ERR_DDOS_INVALID_CONFIG_FILE	WARNING	AppFw XML DDoS Invalid Config File.	"%s"	
APPFW	APPFW_XML_ERR_DDOS_NO_FOLDER_INST	WARNING	AppFw XML DDoS No Folder Install	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	ALLATION_PATH		ation Path.		
APPFW	APPFW_XML_ERR_DDOS_OPEN_CONFIG_FILE_FAIL	WARNING	AppFw XML DDoS Failure to Open Config File.	"%s"	
APPFW	APPFW_XML_ERR_DOS_TRIGGERED	WARNING	Denial of Service Error.	"%s"	
APPFW	APPFW_XML_ERR_ENV_NOT_SET	WARNING	Environment variable QTHOME not set.	"%s"	
APPFW	APPFW_XML_ERR_HASH_INSERT	WARNING	Problems inserting a namespace into the	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			hash table.		
APPFW	APPFW_XML_ERR_HASH_LOOKUP	WARNING	Problems getting the key of a namespace from the hash table.	"%s"	
APPFW	APPFW_XML_ERR_INITIALIZING_TOKENIZER	WARNING	Unable to initialize XML tokenizer.	"%s"	
APPFW	APPFW_XML_ERR_INVALID_FILE	WARNING	Unable to open the file.	"%s"	
APPFW	APPFW_XML_ERR_INVALID_STATE	WARNING	AppFw XML Internal State Invalid.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_ERR_INVALID_XPATH	WARNING	Invalid XPath.	"%s"	
APPFW	APPFW_XML_ERR_LOW_MEMORY	WARNING	AppFw XML Low memory.	"%s"	
APPFW	APPFW_XML_ERR_CHARDATA_LIMIT_EXCEEDED	WARNING	AppFw XML character data size exceeds the limit of 30MB	"%s"	
APPFW	APPFW_XML_ERR_MALFORMED_ADDRESS	WARNING	Malformed address	"%s"	
APPFW	APPFW_XML_ER	WARNING	NS-XML APPFW	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	R_NO_DIME		supports SwA and MTOM SOAP attachments, but attachment with this message is DIME.		
APPFW	APPFW_XML_ERR_OPERATION_CALLBACK	WARNING	Problems registering callbacks for operations.	"%s"	
APPFW	APPFW_XML_ERR_PREFIX_LENGTH_EXCEEDED	WARNING	Prefix length %d exceeded, encountered length is %d.	"%s"	
APPFW	APPFW_XML_ERR_RE	WARNING	AppFw XML Read Failure	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	AD_FAILED				
APPFW	APPFW_XML_ERR_STREAM_POP	WARNING	Problems during pop of the node out of the XML stream.	"%s"	
APPFW	APPFW_XML_ERR_STREAM_PUSH	WARNING	Problems during push of the node into the XML stream.	"%s"	
APPFW	APPFW_XML_ERR_UNSUPPORTED_PORT	WARNING	Port in address %s is greater than 65535.	"%s"	
APPFW	APPFW_XML_ERR_UN	WARNING	Unsupported	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	SUPPORTED_PROTOCOL		protocol		
APPFW	APPFW_XML_ERR_VALIDATION_FAILED	WARNING	AppFw XML Validation Failed	"%s"	
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_NULL	WARNING	AppFw XML Context is NULL.	"%s"	
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_STATE_NULL	WARNING	Context user state is NULL; internal error.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_MESSAGE_CONFIG_NULL	WARNING	Message config struct is NULL.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_ABSTRACT_ELEMENT	WARNING	Cannot instantiate abstract element	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_ABSTRACT_TYPE	WARNING	Cannot instantiate abstract type '%s', for element '%s'.	"%s"	
APPFW	APPFW_XM	WARNING	Additional	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	L_VALIDATION_ERR_ADDHEADERS		soap header %s present in soap message.		
APPFW	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MAX_OCCURS	WARNING	Attribute '%s' appears more than once in element '%s'.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MIN_OCCURS	WARNING	Required attribute missing in element	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_COMPI	WARNING	Compiled WSDL file is corrupt.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	LED_WSDL				
APPFW	APPFW_XML_VALIDATION_ERR_CONTENT_MODEL_VIOLATED	WARNING	Content model of element '%s' not satisfied.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_CORRUPT_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_CORRUPT_SCHEMA	WARNING	Error compiling the schema	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_VALIDATION_ERR_DATATYPE_ENGINE_INIT	WARNING	Initialization of the datatype engine failed.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_INTERNAL	WARNING	Internal corruption of WSDL in-memory structure.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_ATTRIBUTE	WARNING	Attribute '%s' is invalid.	"%s"	
APPFW	APPFW_XML_VALIDATION_E	WARNING	Invalid configuration for soap	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	RR_INVALID_COMBINATION		validation.		
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_COMPILED_WSDL	WARNING	Not able to open compiled WSDL.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_CONTENT_MODEL	WARNING	Element '%s' has invalid content model.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_DATATYPE	WARNING	Data type is invalid.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_ELEMENT	WARNING	Invalid element.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_FILE	WARNING	Not able to open the file.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_TYPE_SUBSTITUTION	WARNING	Did not get expected type for element '%s', got '%s'.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_L	WARNING	Unable to load validation engine.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	OADING				
APPFW	APPFW_XML_VALIDATION_ERR_MAX	WARNING	AppFw XML Validation Max Error.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_NOSERVICEURL	WARNING	Service Url is not present or NULL.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_NOT_SUPPORTED	WARNING	Feature not supported.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_BODY	WARNING	Soap Body structure check failed.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_ENVELOPE	WARNING	Soap Envelope structure check failed.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_HEADER	WARNING	Soap Header structure check failed.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_UNBOUNDED_PREFIX	WARNING	Prefix '%s' is unbounded.	"%s"	
APPFW	APPFW_XML_VALIDATION_LOAD_ERR_CONT	WARNING	Element '%s' cannot be nil.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	ENTS_CANNOT_BE_NIL				
APPFW	APPFW_XML_VALIDATION_LOAD_ERR_NIL_WITH_CONTENTS	WARNING	Element '%s' is nil, cannot have contents.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_REX_STACK_OVERFLOW	WARNING	Level of recursion more than maximum allowed depth.	"%s"	
APPFW	APPFW_XML_VALIDATION_ERR_REX_STACK	WARNING	Trying to pop from an empty stack.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_EMPTY				
APPFW	APPFW_XML_VALIDATION_ERR_SOAPBODY_EMPTY	WARNING	Both SOAP Body and SOAP Header are empty in the SOAP request.	"%s"	
APPFW	APPFW_XML_GENERIC_ERR_EMPTYBODY_REQ	WARNING	Request body is empty in the XML request.	"%s"	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_DATATYPE	WARNING	Value should be of type '%s'.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_VALUE				
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_LOCATION	WARNING	Element '%s' cannot appears at this location.	"%s"	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_FACET_MISMATCH	WARNING	Facet mismatch.	"%s"	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_FAILED	WARNING	AppFw XML Validator Load Failed.	"%s"	
APPFW	APPFW_XML_VAL	WARNING	Attribute '%s' has	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	IDATOR_LOAD_ERR_INVALID_ATTRIBUTE_VALUE		invalid value '%s'.		
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_DATATYPE	WARNING	Invalid schema datatype.	"%s"	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_SCHEMA_NODE_TYPE	WARNING	Invalid schema node type.	"%s"	
APPFW	APPFW_XML_VALIDATOR_LO	WARNING	Value '%s' does not match	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	AD_ERR_INVALID_VALUE_FOR_FIXED		FIXED constraint '%s'.		
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_GT_MAX	WARNING	List length is greater than max allowed.	"%s"	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_INVALID	WARNING	List length is invalid.	"%s"	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LE	WARNING	List length is lesser than min	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	NGTH_LT_MIN		allowed.		
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_MAX	WARNING	AppFw XML Validation Maximum Load Error.	"%s"	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_REQUIRED_ATTRIBUTE	WARNING	Missing require attribute '%s' in element '%s'.	"%s"	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_SCHEMA_COMPILATION	WARNING	Error code in the compiled Schema is being ignored.	"%s"	
APPFW	APPFW_XML_VAL	WARNING	Error code in the	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	IDATOR_LOAD_ERR_WSDL_COMPILATION		compiled WSDL is being ignored.		
APPFW	APPFW_XML_WSI_ERR_ACCELEMENTNAMESPACED	WARNING	R2735: A MESSAGE described with an rpc-literal binding MUST place the part accessor elements for parameters and return value in no namespace. Element '%s'	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			must be unqualified.		
APPFW	APPFW_XML_WSI_ERR_ARRAYTYPE	WARNING	R2113: A MESSAGE containing serialized arrays MUST NOT include the soapenc:arrayType attribute. Element '%s' must not include the soapenc:arrayType attribute.	"%s"	
APPFW	APPFW_XM	WARNING	R1015: A	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	L_WSI_ERR_BAD_ENV_NAMESPACE		RECEIVER MUST generate a fault if they encounter a message whose document element has a local name of "Envelope" but a namespace name that is not "http://schemas.xmlsoap.org/soap/envelope/" or "http://www.w3.org/		

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			2003/05/soap-envelope". We got namespace '%s' in SOAP Request.		
APPFW	APPFW_XML_WSI_ERR_BINDINGFAULTRESP	WARNING	R2740: The response envelope contained soap:Fault element(s), but they were not defined in the WSDL description. Element '%s' should	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			be defined as soap:fault in WSDL description.		
APPFW	APPFW_XML_WSI_ERR_BODY_CHILD_NAMESPACE	WARNING	R1014: The children of the soap:Body element in a MESSAGE MUST be namespace qualified. Unqualified children of soap:Body is '%s'.	"%s"	
APPFW	APPFW_XML_WSI_ERR_BOD	WARNING	BP1201: The envelope does	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	Y_ENV_NAMESPACE		not use SOAP 1.1 or SOAP 1.2, i.e. does not have a document element named "Envelope" or a namespace value of http://schemas.xmlsoap.org/soap/envelope/ or http://www.w3.org/2003/05/soap-envelope.		

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			We got namespace '%s'.		
APPFW	APPFW_XML_WSI_ERR_CHILDAFTERBODY	WARNING	R1011: A MESSAGE MUST NOT have any element children of soap:Envelope following the soap:Body element. Element '%s' should not appear after 'soap:Body' element.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_WSI_ERR_CLAIM_MUSTUNDERSTAND	WARNING	R0007: A SENDER MUST NOT use the soap:mustUnderstand attribute when sending a SOAP header block containing a conformance claim. soap:mustUnderstand attribute is present on element '%s'.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_WSI_ERR_CTXT_NULL	WARNING	AppFw XML WSI Internal Context NULL	"%s"	
APPFW	APPFW_XML_WSI_ERR_DOCTYPE ALLOWED	WARNING	R1008: A MESSAGE MUST NOT contain a Document Type Declaration. DOCTYPE name is '%s'.	"%s"	
APPFW	APPFW_XML_WSI_ERR_DOT_NOTATION	WARNING	R1031: When a MESSAGE contains a faultcode element the	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			content of that element SHOULD NOT use of the SOAP 1.1 "dot" notation to refine the meaning of the Fault. Data '%s' should not contain 'DOT'(.) in it.		
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLE	WARNING	R1005: A MESSAGE MUST NOT contain soap:e	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			ncodingStyle attribute on any of the elements whose namespace is the same as the namespace of the qualified document element 'Envelope'. 'soap:encodingStyle' attribute should not be present on element '%s'.		

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLECHILD	WARNING	R1006: A MESSAGE MUST NOT contain soap:encodingStyle attributes on any element that is a child of soap:Body. 'soap:encodingStyle' attribute should not be present on immidiate child '%s' of soap:Body.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLEGRANDCHILD	WARNING	R1007: A MESSAGE described in an rpc-literal binding MUST NOT contain soap:encodingStyle attribute on any elements are grandchildren of soap: Body. 'soap: encodingStyle' attribute should not be present on grandc	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			hild '%s' of soap: Body.		
APPFW	APPFW_XML_WSI_ERR_ENV ELEMENTS NOATTRIBUTES	WARNING	R1032: The soap: Envelope, soap: Header, and soap: Body elements in an ENVELOPE MUST NOT have attributes in the same namespace as that of the qualified document element 'Envelope'.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			Attribute '%s' should not be in the same namespace as that of the qualified document element 'Envelope'.		
APPFW	APPFW_XML_WSI_ERR_ENVNONAMESPACE	WARNING	R1033: An ENVELOPE SHOULD NOT contain the namespace declaration xmlns:xml="http://www.w3.org/XML/1998/	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			namespace".		
APPFW	APPFW_XML_WSI_ERR_GOODRESPONSE200	WARNING	R1111: An INSTANCE SHOULD use a "200 OK" HTTP status code for responses that contain a SOAP message that is not a SOAP fault. We should not get 'soap: Fault' element when HTTP response	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			code is '200 OK'.		
APPFW	APPFW_XML_WSI_ERR_HEADER_HAS_WSICLAIM	WARNING	R0005: A MESSAGE's conformance claims MUST be carried as SOAP header blocks. Element '%s' should be immidiate children of soap: Header.	"%s"	
APPFW	APPFW_XML_WSI_ERR_HTTP	WARNING	AppFw XML WSI HTTP Error	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_WSI_ERR_ISHTTPPOST	WARNING	R1132: A HTTP request MESSAGE MUST use the HTTP POST method. We got '%s' HTTP method.	"%s"	
APPFW	APPFW_XML_WSI_ERR_ISUTF8OR16	WARNING	R1012: A MESSAGE MUST be serialized as either UTF-8 or UTF-16. We got encoding '%s'.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_WSI_ERR_MSG HASALLHEADERS	WARNING	R2738: A MESSAGE MUST include all soapbind:headers specified on a wsdl:input or wsdl:output of a wsdl:operation of a wsdl:binding that describes it.Wsdl header %s is not present in soap message.	"%s"	
APPFW	APPFW_XML_WSI	WARNING	R1013: A MESS	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_ERR_MUSTUNDERSTAND		AGE containing a soap:mustUnderstand attribute MUST only use the lexical forms "0" and "1". Value of 'soap:mustUnderstand' attribute is '%s'.		
APPFW	APPFW_XML_WSI_ERR_NODEPLOYED	WARNING	Resource id of deployment is NULL.	"%s"	
APPFW	APPFW_XML_WSI	WARNING	BP1701: The envelo	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_ERR_NOENVELOPEWSDLMATCH		pe does not conform to the SOAP schema located at 'http://schemas.xmlsoap.org/soap/envelope/' or 'http://www.w3.org/2003/05/soap-envelope'.		
APPFW	APPFW_XML_WSI_ERR_NONPOSTREQUEST	WARNING	R1114: An INSTANCE SHOULD use a "405 Method not	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			Allowed" HTTP status code if the request method was not "POST". We got '%d' HTTP status code.		
APPFW	APPFW_XML_WSI_ERR_NONXMLREQUEST	WARNING	R1115: An INSTANCE SHOULD use a "415 Unsupported Media Type" HTTP status code if a HTTP request messa	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			ge's Content-Type header field-value is not permitted by its WSDL description. we got '%d' HTTP status code.		
APPFW	APPFW_XML_WSI_ERR_NOPORTURL	WARNING	Port URL is NULL.	"%s"	
APPFW	APPFW_XML_WSI_ERR_NOREQWSDLMATCH	WARNING	BP1011: The content of the request envelope does not match	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			the wsdl: message definition.		
APPFW	APPFW_XML_WSI_ERR_NORESPWSDLMATCH	WARNING	BP1013 The content of the response envelope does not match the wsdl: message definition.	"%s"	
APPFW	APPFW_XML_WSI_ERR_NOWSDLDEPLOYED	WARNING	Deployed resource is not WSDL.	"%s"	
APPFW	APPFW_XML_WSI_ERR_ONEWAYR	WARNING	R2714: For one-way operations,	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	ESPONSE		an INSTANCE MUST NOT return a HTTP response that contains a SOAP envelope. Specifically, the HTTP response entity-body must be empty. we got the element soap:Envelope.		
APPFW	APPFW_XML_WSI_ERR_RES	WARNING	R1112: An INSTANCE SHOU	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	PONSESTATUS200OR202		LD use either a "200 OK" or "202 Accepted" HTTP status code for a response that does do not contain a SOAP message but indicates successful HTTP outcome of a request. We got '%d' HTTP response code.		

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_WSI_ERR_RESPONSEWRAPPED	WARNING	R2729: A MESSAGE described with an rpc-literal binding that is a response message MUST have a wrapper element whose name is the corresponding wsdl:operation name suffixed with the string "Response".	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			Element name should be '%sResponse' but got '%s'.		
APPFW	APPFW_XML_WSI_ERR_SOAPACTIONHEADERMATCH	WARNING	R2744: A HTTP request MESSAGE MUST contain a SOAP Action HTTP header field with a quoted value equal to the value of the soapAction attribute of soapbind:ope	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			ration, if present in the corresponding WSDL description. Expected '%s' soapAction but got '%s' soapAction in HTTP header.		
APPFW	APPFW_XML_WSI_ERR_SOAPACTIONQUOTED	WARNING	R1109: The value of the SOAP Action HTTP header field in a HTTP request MESSAGE	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			MUST be a quoted string. We got '%s' SOAP Action HTTP header.		
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTALLOWEDCHILD	WARNING	R1000: When a MESSAGE contains a soap:Fault element, that element MUST NOT have element children other than faultcode, faultstr	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			ing, faultactor and detail. Element '%s' is not a allowed child of 'soap: Fault'.		
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTCHILDQ	WARNING	R1001: When a MESSAGE contains a soap:Fault element its element children MUST be unqualified. 'soap: Fault' child '%s'	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			should be unqualified.		
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTINHTTP	WARNING	R1126: An INSTANCE MUST use a "500 Internal Server Error" HTTP status code if the response message is a SOAP Fault. We got '%s' HTTP response code.	"%s"	
APPFW	APPFW_XML_WSI_ERR_SOA	WARNING	R1003: A RECEIVER MUST	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	PFAULTNONENV		acceptfault messages that have any number of qualified or unqualified attributes, including zero, appearing on the detail element. The namespace of qualified attributes can be anything other than the names		

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			pace of the qualified document element 'Envelope'. Namespace of attribute '%s' should not be the same as that of the qualified document element 'Envelope'.		
APPFW	APPFW_XML_WSI_ERR_SOAPGOODXML10	WARNING	BP1601: The soap:Envelope or soap:Body does not	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			conform to XML 1.0. Error is '%s'.		
APPFW	APPFW_XML_WSI_ERR_STDFAULTCODE	WARNING	R1004: When a MESSAGE contains a faultcode element the content of that element SHOULD be one of the fault codes defined in SOAP 1.1 or a namespace qualified	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			fault code. 'faultcode' '%s' is not defined in SOAP 1.1 or it is not namespace qualified.		
APPFW	APPFW_XML_WSI_ERR_USE HTTP 10OR 11	WARNING	R1141: A MESSAGE MUST be sent using either HTTP/1.1 or HTTP/1.0. We got HTTP version '%s'.	"%s"	
APPFW	APPFW_XML_WSI	WARNING	R1140: A MESS	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_ERR_USE HTTP 11		AGE SHOULD be sent using HTTP/ 1.1. We got HTTP versio n '%s'.		
APPFW	APPFW_XML_WSI_ERR_WSI CLAIMSWEL LFORMED	WARNING	R0004: A MESSAGE MAY contain conformance claims, as specified in the conformance claim schema. Either 'conformsTo' attribute is absent or	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			'soap: mustUnderstand' attribute is present on element '%s'.		
APPFW	APPFW_XML_WSI_ERR_WSI_LIST_NULL	WARNING	AppFw XML WSI List Null.	"%s"	
APPFW	APPFW_XML_WSI_ERR_XML_PI	WARNING	R1009: A MESSAGE MUST NOT contain Processing Instructions. Name of Processing Instruction is '%s'.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_WSI_ERR_XSINIL	WARNING	R2211: A MESSAGE described with an rpc-literal binding MUST NOT have the xsi:nil attribute with a value of "1" or "true" on the part accessors. Element '%s' must not have the xsi:nil attribute.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_XML_XSD_COMPILE_INIT_ERR	WARNING	Error during initialization	"%s"	
APPFW	APPFW_XML_XSD_COMPILE_LOADXSD_ERR	WARNING	AppFw XML XSDLOAD Failed during Compile	"%s"	
APPFW	APPFW_XML_XSD_COMPILE_NOMODEL_ERR	WARNING	No XSModel to print	"%s"	
APPFW	APPFW_XML_XSD_COMPILE_PARSE_ERR	INFO	Error during parsing	"%s"	
APPFW	APPFW_XML_XSD_CO	WARNING	Unexpected exception	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	MPILE_UNEXPECTED_ERR		during parsing		
APPFW	APPFW_XML_ERR_SOAP_FAULT	WARNING	Message contains SOAP Fault.	"%s"	
APPFW	APPFW_XML_SOAP_FAULT_CONTENTS	WARNING	Dumps the SOAP Fault contents to Audit log.	"%s"	
APPFW	AF_INVALID_HTTP_HEADER	WARNING	Error while parsing HTTP headers.	"Error whileparsing HTTP headers.");returnns_printlogmsg_appsec(buf	
APPFW	APPFW_CCARD_MATCH_IN_SIGN	INFO	Credit card violation in	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	ATURES		signatures		
APPFW	APPFW_SESSIONLIMIT	INFO	AppFw Session Limit reached	"Appfwmaximumssession Limitreachedf orPEID%d"	
APPFW	AF_ADD_RFCPROFILE	INFO	Add an AppFw rfc profile	"APPFWRFC Profile :%s\n"	
APPFW	AF_RM_RFCPROFILE	INFO	Remove an AppFw rfc profile	"APPFWRFC Profile :%s\n"	
APPFW	APPFW_INV_RFC	INFO	RFC syntax violation. Generated 302 Response	"%s"	
APPFW	APPFW_NEW_SIGNATURE_	INFO	AppFw New Signature Added	"Newsignatureavailable:R	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	ADDED			uleID=%d	
APPFW	APPFW_JSON_DOS_MAX_DOCUMENT_LENGTH	INFO	AppFw JSON document length exceeded	"%s"	
APPFW	APPFW_JSON_DOS_MAX_CONTAINER_DEPTH	INFO	AppFw JSON document exceeds maximum container depth	"%s"	
APPFW	APPFW_JSON_DOS_MAX_OBJECT_KEY_COUNT	INFO	AppFw JSON document has object that exceeds maximum	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			key count		
APPFW	APPFW_JSON_DOS_MAX_OBJECT_KEY_LENGTH	INFO	AppFw JSON document has key in object that exceeds maximum key length	"%s"	
APPFW	APPFW_JSON_DOS_MAX_ARRAY_LENGTH	INFO	AppFw JSON document has array exceeds maximum array length	"%s"	
APPFW	APPFW_JSON_DOS_MAX_STRIN	INFO	AppFw JSON document has string	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	G_LENGTH		that exceeds maximum string length		
APPFW	APPFW_JSON_SQL	INFO	AppFw JSON document has sql violation	"%s"	
APPFW	APPFW_JSON_XSS	INFO	AppFw JSON document has Cross-site script violation	"%s"	
APPFW	APPFW_DEPLOY_RELAXATION_DP	INFO	AppFw relaxation about to be deployed through	"Learnedrule willbeauto-deployedafter%dmins.ViolType: %s.Pr	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			Dynamic Learning	ofile: %s	
APPFW	APPFW_COOKIE_HIJACK	INFO	AppFw Cookie Hijacking violation	"%s"	
APPFW	APPFW_POSTBODYLIMIT	INFO	AppFw Post Body Limit violation	"%s"	
APPFW	APPFW_JSON_CMD	INFO	AppFw JSON document has command injection violation	"%s"	
APPFW	APPFW_JSON_SQL_GRAM	INFO	AppFw JSON document has	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			SQL Injection violation reported by SQL Grammar		
APPFW	APPFW_GRPC	INFO	AppFw gRPC detected an invalid request.	"APIvalidationerror(%s)Req(%s:%s)"	
APPFW	APPFW_GRPC_WEB_TEXT	INFO	AppFw grpc_web_text detected an invalid request.	"Appsecgrpc_web_textrejectsinvalidrequest.");returnns_printlogmsg_appsec(buf	
APPFW	APPFW_GRPC_WEB_JSON	INFO	AppFw grpc_web_json detect	"Appsecgrpc_web_jsonrejectsinvalidre	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			ed an invalid request.	quest.");returnns_printlogmsg_appsec(buf	
APPFW	APPFW_JSON_CMD_GRAM	INFO	AppFw JSON document has CMD Injection violation reported by CMD Grammar	"%s"	
APPFW	APPFW_BLOCK_KEYWORD	INFO	AppFw Block Keyword Violation	"%s"	
APPFW	APPFW_JSON_BLOCKKEYWORD	INFO	AppFw JSON Block Keyword	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			Violation		
APPFW	APPFW_BYPASS_LIST	INFO	AppFw Bypass List Match	"%s"	
APPFW	APPFW_DENY_LIST	INFO	AppFw Deny List Match	"%s"	
APPFW	APPFW_SCHEMA_ENDPOINT_NOTFOUND	INFO	AppFw Schema violation endpoint not found	"Endpoint: (%s%s)notfoundinAPISpec: (%s)"	
APPFW	APPFW_SCHEMA_METHOD_UNSUPPORTED	INFO	AppFw Schema violation method un-supported	"HTTPmethodunsupportedasperAPISpec: (%s)forEndpoint: (%s%s)"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_SCHEMA_PARAMETER_MISSING	INFO	AppFw Schema violation parameter missing	"Requiredparameterm issingasperAPISpec: (%s)forEndpoint: (%s%s)"	
APPFW	APPFW_SCHEMA_VALUE_INCORRECT	INFO	AppFw Schema violation value incorrect	"Parametervaluein correctasperAPISpec: (%s)forEndpoint: (%s%s)"	
APPFW	APPFW_SCHEMA_CONTENTTYPE_UNSUPPORTED	INFO	AppFw Schema violation content un-supported	"Contenttypeunsupportedasper APISpec: (%s)forEndpoint: (%s%s)"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW	APPFW_SCHEMA_PARAMETER_INVALID	INFO	AppFw Schema violation parameter invalid	"Parameterisinvalidasper APISpec: (%s)forEndpoint: (%s%s)"	
APPFW	APPFW_SCHEMA_OTHER	INFO	AppFw Schema violation other	"Schemavalidationfailedasper APISpec: (%s)forEndpoint: (%s%s)"	
APPFW	APPFW_SCHEMA_RELAXATION_RULE	INFO	AppFw Schema Relaxation Rule Hit	"REST Validationrelaxationrule: %shitaturl: %s"	
ROUTING	ZEBOS_CMD_EXECUTED	INFO	The ZebOS command	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			executed.		
SNMP	TRAP_SENT	INFO	Trap Sent Information	"%s"	
SNMP	TRAP_DROPPED	INFO	Trap Dropped information. Traps are dropped due to rate-limiting	"%s"	
TRANSFORM	FILE_REQUEST	DEBUG	URL Transformation profile invoked	"Client %s- Profile %s- %sinto %s"	
TRANSFORM	REQ_PARSE_ERROR	WARNING	URL Transformation parsing error	"Client %s- Profile %s- Failedtoparse requestURL %stransform	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				ation-URL%s"	
TRANSFORM	REQ_HEADER	DEBUG	URL Transformation in a request header	"Client%s-Profile%s-Header%s-%sinto%s"	
TRANSFORM	RESP_HEADER	DEBUG	URL Transformation in a response header	"Client%s-Profile%s-Header%s-%sinto%s"	
TRANSFORM	BODY_FRAG	DEBUG	URL Transformation in a response body	"Client%s-Profile%s-Type%s-%sinto%s"	
TRANSFORM	ACTION_MATCH	DEBUG	URL Transformation action matched URL	"Client%s-Profile%s-Action%s-%sinto%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
TRANSFORM	ACTION_MISMATCH	DEBUG	URL Transformation action didn't match URL	"Client %s- Profile %s- Action %s- Value %s"	
TRANSFORM	PCRE_ERROR	WARNING	URL Transformation regex error	"Client %s- Profile %s- Action %s- PCRE errorcode%d"	
TRANSFORM	REQ_WRITE_ERROR	WARNING	URL Transformation error in a request header	"Client %s- Profile %s- Failedtowrite %srequestheader"	
APPFW_RESP	APPFW_XML_XSS	WARNING	AppFw XSS violation in XML	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_SQL	WARNING	AppFw SQL Injection violation in XML	"%s"	
APPFW_RESP	APPFW_XML_ATTACHMENT_FOUND	WARNING	Attachment Found in the XML Message.	"%s"	
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_CALLBACK_NULL	WARNING	XML Attachment CallBack is NULL but HTTP message is MIME Attachment message.	"%s"	
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_INVALI	WARNING	String %s is supposed to be MIME Heade	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT			
	DHEADER		r. But it is not according to the format of Mime Header HeaderName:HeaderValue				
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_INVALID_HEADER	WARNING	HTTP Content type should be 'application/xop+xml' or '\^(text	application)/([a-zA-Z]*\+xml	xml)' but we got %s.	"%s"	
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_BOUNDARY_MISMATCH	WARNING	Boundary mismatch in mime message.	"%s"			

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_ERR_NO_ATTACHMENT_BOUNDARY	WARNING	The message having content-type as 'Multipart/Related' and not having a boundary is invalid.	"%s"	
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_MAX_SIZE	WARNING	XML Message has an Attachment with size greater than the Configured Max Attachment Size.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_CONTENT_TYPE	WARNING	XML Message has an Attachment with Illegal Content-Type	"%s"	
APPFW_RESP	APPFW_XML_DDOS_ERR_MSG_SEND_FAIL	WARNING	AppFw XML DDoS Send Fail Error.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_CHAR_DATA_LENGTH	WARNING	Exceeds max character data length.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_DTD	WARNING	DTD present in the XML message.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_DOS_ERR_EXT_ENTITY	WARNING	External entities present in the XML message.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX	WARNING	AppFw XML DoS Maximum Error	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTES	WARNING	Element '%s' exceeds maximum attributes per element.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_NAME_LENGTH	WARNING	In element '%s' an attribute exceeds maximum	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			name length.		
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_VALUE_LENGTH	WARNING	In element '%s' attribute '%s' exceeds maximum attribute value length.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENTS	WARNING	Element '%s' exceeds maximum elements per message.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_CHILDREN	WARNING	Parent of element '%s' exceeds maximum children at eleme	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			nt '%s'.		
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_DEPTH	WARNING	Element '%s' exceeds maximum element depth.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_NAME_LENGTH	WARNING	Element '%s' exceeds maximum element name length.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_FILE_SIZE	WARNING	Message size exceeds max size.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MA	WARNING	Node '%s' exceeds maximum	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	X_NODES		nodes per message.		
APPFW_RESP	APPFW_XML_DOS_ERR_MIN_FILE_SIZE	WARNING	Message size less than min size.	"%s"	
APPFW_RESP	APPFW_XML_ERR_NOT_WELLFORMED	WARNING	Message is not a well-formed XML.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_PI	WARNING	Processing instructions present in the XML message.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NA	WARNING	Element '%s' exceeds maximum active	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	MESPACES		namespaces.		
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NAMESPACEURI_LENGTH	WARNING	In element '%s' a namespace exceeds maximum uri length.	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSION_DEPTH	WARNING	Exceeds max entity expansion depth	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSIONS	WARNING	Exceeds max number of entity expansions	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_SIZE	WARNING	Exceeds max total SOAP array size	"%s"	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_RANK	WARNING	Exceeds max SOAP array rank	"%s"	
APPFW_RESP	APPFW_XML_ERR_CUSTOM	WARNING	AppFw XML internal error	"%s"	
APPFW_RESP	APPFW_XML_ERR_DDOS_CONNECT_TO_SERVER_FAILED	WARNING	AppFw XML DDoS Connect to Server Failed.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_ERR_DDOS_INTERATION_SOCKET_OPEN_FAIL	WARNING	AppFw XML DDoS Interaction socket open Failed.	"%s"	
APPFW_RESP	APPFW_XML_ERR_DDOS_INVALID_CONFIG_FILE	WARNING	AppFw XML DDoS Invalid Config File.	"%s"	
APPFW_RESP	APPFW_XML_ERR_DDOS_NO_FOLDER_INSTALLATION_PATH	WARNING	AppFw XML DDoS No Folder Installation Path.	"%s"	
APPFW_RESP	APPFW_XML_ERR_DDOS_O	WARNING	AppFw XML DDoS Failure to	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	PEN_CONFIG_FILE_FAIL		Open Config File.		
APPFW_RESP	APPFW_XML_ERR_DOS_TRIGGERED	WARNING	Denial of Service Error.	"%s"	
APPFW_RESP	APPFW_XML_ERR_ENV_NOT_SET	WARNING	Environment variable QTHOME not set.	"%s"	
APPFW_RESP	APPFW_XML_ERR_HASH_INSERT	WARNING	Problems inserting a namespace into the hash table.	"%s"	
APPFW_RESP	APPFW_XML_ERR_HASH_L	WARNING	Problems getting the key of a	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	OOKUP		namespace from the hash table.		
APPFW_RESP	APPFW_XML_ERR_INITIALIZING_TOKENIZER	WARNING	Unable to initialize XML tokenizer.	"%s"	
APPFW_RESP	APPFW_XML_ERR_INVALID_FILE	WARNING	Unable to open the file.	"%s"	
APPFW_RESP	APPFW_XML_ERR_INVALID_STATE	WARNING	AppFw XML Internal State Invalid.	"%s"	
APPFW_RESP	APPFW_XML_ERR_INVALID_XPATH	WARNING	Invalid XPath.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_ERR_LOW_MEMORY	WARNING	AppFw XML Low memory.	"%s"	
APPFW_RESP	APPFW_XML_ERR_CHARDATA_LIMIT_EXCEEDED	WARNING	AppFw XML character data size exceeds the limit of 30MB	"%s"	
APPFW_RESP	APPFW_XML_ERR_MALFORMED_ADDRESS	WARNING	Malformed address	"%s"	
APPFW_RESP	APPFW_XML_ERR_NO_DIME	WARNING	NS-XML APPFW supports SwA and MTOM SOAP attachments, but	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			attachment with this message is DIME.		
APPFW_RESP	APPFW_XML_ERR_OPERATION_CALLBACK	WARNING	Problems registering callbacks for operations.	"%s"	
APPFW_RESP	APPFW_XML_ERR_PREFIX_LENGTH_EXCEEDED	WARNING	Prefix length %d exceeded, encountered length is %d.	"%s"	
APPFW_RESP	APPFW_XML_ERR_READ_FAILED	WARNING	AppFw XML Read Failure	"%s"	
APPFW_RESP	APPFW_XML_ERR_ST	WARNING	Problems during pop of the node	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	REAM_POP		out of the XML stream.		
APPFW_RESP	APPFW_XML_ERR_STREAM_PUSH	WARNING	Problems during push of the node into the XML stream.	"%s"	
APPFW_RESP	APPFW_XML_ERR_UNSUPPORTED_PORT	WARNING	Port in address %s is greater than 65535.	"%s"	
APPFW_RESP	APPFW_XML_ERR_UNSUPPORTED_PROTOCOL	WARNING	Unsupported protocol	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_ERR_VALIDATION_FAILED	WARNING	AppFw XML Validation Failed	"%s"	
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_NULL	WARNING	AppFw XML Context is NULL.	"%s"	
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_STATE_NULL	WARNING	Context user state is NULL; internal error.	"%s"	
APPFW_RESP	APPFW_XML_PACKET_PROCESSI	WARNING	Message config struct is NULL.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	NG_ERR_MESSAGE_CONFIG_NULL				
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ABSTRACT_ELEMENT	WARNING	Cannot instantiate abstract element	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ABSTRACT_TYPE	WARNING	Cannot instantiate abstract type '%s', for element '%s'.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ADDHE	WARNING	Additional soap header %s present in soap	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	ADERS		message.		
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MAX_OCCURS	WARNING	Attribute '%s' appears more than once in element '%s'.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MIN_OCCURS	WARNING	Required attribute missing in element	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CONTENT_MODEL_VIOLATED	WARNING	Content model of element '%s' not satisfied.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CORRUPT_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CORRUPT_SCHEMA	WARNING	Error compiling the schema	"%s"	
APPFW_RESP	APPFW_XML_VALIDATI	WARNING	Initialization of the dataty	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	ON_ERR_DATATYPE_ENGINE_INIT		pe engine failed.		
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INTERNAL	WARNING	Internal corruption of WSDL in-memory structure.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_ATTRIBUTE	WARNING	Attribute '%s' is invalid.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_COM	WARNING	Invalid configuration for soap validation.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	BINATION				
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_COMPILED_WSDL	WARNING	Not able to open compiled WSDL.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_CONTENT_MODEL	WARNING	Element '%s' has invalid content model.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_DATATYPE	WARNING	Data type is invalid.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_ELEMENT	WARNING	Invalid element.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_FILE	WARNING	Not able to open the file.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_TYPE_SUBSTITUTION	WARNING	Did not get expected type for element '%s', got '%s'.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_L	WARNING	Unable to load validation engine.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	OADING				
APPFW_RESP	APPFW_XML_VALIDATION_ERR_MAX	WARNING	AppFw XML Validation Max Error.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_NOSERVICEURL	WARNING	Service Url is not present or NULL.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_NOT_SUPPORTED	WARNING	Feature not supported.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_BODY	WARNING	Soap Body structure check failed.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_ENVELOPE	WARNING	Soap Envelope structure check failed.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_HEADER	WARNING	Soap Header structure check failed.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_UNBOUNDED_PREFIX	WARNING	Prefix '%s' is unbounded.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_LOAD_ERR_CONT	WARNING	Element '%s' cannot be nil.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	ENTS_CANNOT_BE_NIL				
APPFW_RESP	APPFW_XML_VALIDATION_LOAD_ERR_NIL_WITH_CONTENTS	WARNING	Element '%s' is nil, cannot have contents.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_REX_STACK_OVERFLOW	WARNING	Level of recursion more than maximum allowed depth.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_REX_STACK	WARNING	Trying to pop from an empty stack.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_EMPTY				
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAPBODY_EMPTY	WARNING	Both SOAP Body and SOAP Header are empty in the SOAP request.	"%s"	
APPFW_RESP	APPFW_XML_GENERIC_ERR_EMPTYBODY_REQ	WARNING	Request body is empty in the XML request.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_DATATYPE	WARNING	Value should be of type '%s'.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_VALUE				
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_LOCATION	WARNING	Element '%s' cannot appears at this location.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_FACET_MISMATCH	WARNING	Facet mismatch.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_FAILED	WARNING	AppFw XML Validator Load Failed.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_ATTRIBUTE_VALUE	WARNING	Attribute '%s' has invalid value '%s'.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_DATATYPE	WARNING	Invalid schema datatype.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_SCHEMA_NODE_TYPE	WARNING	Invalid schema node type.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_VALUE_FOR_FIXED	WARNING	Value '%s' does not match FIXED constraint '%s'.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_GT_MAX	WARNING	List length is greater than max allowed.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_INVALID	WARNING	List length is invalid.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_LT_MIN	WARNING	List length is lesser than min allowed.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_MAX	WARNING	AppFw XML Validation Maximum Load Error.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_REQUIRED_ATTRIBUTE	WARNING	Missing require attribute '%s' in element '%s'.	"%s"	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_E	WARNING	Error code in the compiled Sche	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	RR_SCHEMA_COMPILATION		ma is being ignored.		
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_WSDL_COMPILATION	WARNING	Error code in the compiled WSDL is being ignored.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_ACCELEMENTNAMESPACED	WARNING	R2735: A MESSAGE described with an rpc-literal binding MUST place the part accessor elements for param	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			eters and return value in no namespace. Element '%s' must be unqualified.		
APPFW_RESP	APPFW_XML_WSI_ERR_ARRAYTYPE	WARNING	R2113: A MESSAGE containing serialized arrays MUST NOT include the soapenc:arrayType attribute. Element '%s' must not include the	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			soapenc:arrayType attribute.		
APPFW_RESP	APPFW_XML_WSI_ERR_BAD_ENV_NAMESPACE	WARNING	R1015: A RECEIVER MUST generate a fault if they encounter a message whose document element has a local name of "Envelope" but a namespace name that is not "http://schemas.xml	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			soap.org/soap/envelope/" or "http://www.w3.org/2003/05/soap-envelope". We got namespace '%s' in SOAP Request.		
APPFW_RESP	APPFW_XML_WSI_ERR_BINDINGFAULTRESP	WARNING	R2740: The response envelope contained soap:Fault element(s), but they were not	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			defined in the WSDL description. Element '%s' should be defined as soap:fault in WSDL description.		
APPFW_RESP	APPFW_XML_WSI_ERR_BODY_CHILD_NAMESPACE	WARNING	R1014: The children of the soap:Body element in a MESSAGE MUST be namespace qualified. Unqualified children of	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			soap: Body is '%s'.		
APPFW_RESP	APPFW_XML_WSI_ERR_BODY_ENV_NAMESPACE	WARNING	BP1201: The envelope does not use SOAP 1.1 or SOAP 1.2, i.e. does not have a document element named "Envelope" or a namespace value of http://schemas.xmlsoap.org/soap/envelope/ or	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			http://www.w3.org/2003/05/soap-envelope. We got namespace '%s'.		
APPFW_RESP	APPFW_XML_WSI_ERR_CHILDAFTERBODY	WARNING	R1011: A MESSAGE MUST NOT have any element children of soap:Envelope following the soap:Body element. Element '%s' should	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			not appear after 'soap: Body' element.		
APPFW_RESP	APPFW_XML_WSI_ERR_CLAIM_MUSTUNDERSTAND	WARNING	R0007: A SENDER MUST NOT use the soap: mustUnderstand attribute when sending a SOAP header block containing a conformance claim. soap: mustUnderstand attribute is	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			present on element '%s'.		
APPFW_RESP	APPFW_XML_WSI_ERR_CTXT_NULL	WARNING	AppFw XML WSI Internal Context NULL	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_DOCTYPE ALLOWED	WARNING	R1008: A MESSAGE MUST NOT contain a Document Type Declaration. DOCTYPE name is '%s'.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_DOT	WARNING	R1031: When a MESSAGE contai	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_NOTATION		ns a faultcode element the content of that element SHOULD NOT use of the SOAP 1.1 "dot" notation to refine the meaning of the Fault. Data '%s' should not contain 'DOT'(.) in it.		
APPFW_RESP	APPFW_XML_WSI_ERR	WARNING	R1005: A MESSAGE	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_ENCODINGSTYLE		MUST NOT contain soap:encodingStyle attribute on any of the elements whose namespace is the same as the namespace of the qualified document element 'Envelope'. 'soap:encodingStyle' attribute should not be presen		

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			t on element '%s'.		
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLECHILD	WARNING	R1006: A MESSAGE MUST NOT contain soap:encodingStyle attributes on any element that is a child of soap: Body. 'soap: encodingStyle' attribute should not be present on immidiate child	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			'%s' of soap: Body.		
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLEGRANDCHILD	WARNING	R1007: A MESSAGE described in an rpc-literal binding MUST NOT contain soap:encodingStyle attribute on any elements are grandchildren of soap: Body. 'soap: encodingStyle' attribute should	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			not be present on grandchild '%s' of soap: Body.		
APPFW_RESP	APPFW_XML_WSI_ERR_ENVELEMENTSNOATTRIBUTES	WARNING	R1032: The soap: Envelope, soap: Header, and soap: Body elements in an ENVELOPE MUST NOT have attributes in the same namespace as that of the qualified document	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			element 'Envelope'. Attribute '%s' should not be in the same namespace as that of the qualified document element 'Envelope'.		
APPFW_RESP	APPFW_XML_WSI_ERR_ENVNONAMESPACE	WARNING	R1033: An ENVELOPE SHOULD NOT contain the namespace declaration xmlns:xml="http://	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			www.w3.org/XML/1998/namespace".		
APPFW_RESP	APPFW_XML_WSI_ERR_GOODRESPONSE200	WARNING	R1111: An INSTANCE SHOULD use a "200 OK" HTTP status code for responses that contain a SOAP message that is not a SOAP fault. We should not get 'soap: Fault' element	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			when HTTP response code is '200 OK'.		
APPFW_RESP	APPFW_XML_WSI_ERR_HEADER_HAS_WSICLAIM	WARNING	R0005: A MESSAGE's conformance claims MUST be carried as SOAP header blocks. Element '%s' should be immidiate childrен of soap: Header.	"%s"	
APPFW_RESP	APPFW_XML_WSI	WARNING	AppFw XML WSI	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_ERR_HTTP		HTTP Error		
APPFW_RESP	APPFW_XML_WSI_ERR_ISHTTPPOST	WARNING	R1132: A HTTP request MESSAGE MUST use the HTTP POST method. We got '%s' HTTP method.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_ISUTF8OR16	WARNING	R1012: A MESSAGE MUST be serialized as either UTF-8 or UTF-16. We got encodi	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			ng '%s'.		
APPFW_RESP	APPFW_XML_WSI_ERR_MSG HASALLHEADERS	WARNING	R2738: A MESSAGE MUST include all soapbind:headers specified on a wsdl:input or wsdl:output of a wsdl:operation of a wsdl:binding that describes it.Wsdl header %s is not present in soap message.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_WSI_ERR_MUSTUNDERSTAND	WARNING	R1013: A MESSAGE containing a soap:mustUnderstand attribute MUST only use the lexical forms "0" and "1". Value of 'soap:mustUnderstand' attribute is '%s'.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_NODEPLOYED	WARNING	Resource id of deployment is NULL.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_WSI_ERR_NOENVELOPEWSDLMATCH	WARNING	BP1701: The envelope does not conform to the SOAP schema located at 'http://schemas.xmlsoap.org/soap/envelope/' or 'http://www.w3.org/2003/05/soap-envelope'.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_NONPOST	WARNING	R1114: An INSTANCE SHOULD use a	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	REQUEST		"405 Method not Allowed" HTTP status code if the request method was not "POST". We got '%d' HTTP status code.		
APPFW_RESP	APPFW_XML_WSI_ERR_NONXMLREQUEST	WARNING	R1115: An INSTANCE SHOULD use a "415 Unsupported Media Type" HTTP status code if a HTTP	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			request message's Content-Type header field-value is not permitted by its WSDL description. we got '%d' HTTP status code.		
APPFW_RESP	APPFW_XML_WSI_ERR_NOPORTURL	WARNING	Port URL is NULL.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_NOREQWSDLMATCH	WARNING	BP1011: The content of the request envelope	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			does not match the wsdl: message definition.		
APPFW_RESP	APPFW_XML_WSI_ERR_NORESPWSDLMATCH	WARNING	BP1013 The content of the response envelope does not match the wsdl: message definition.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_NOWSDLDEPLOYED	WARNING	Deployed resource is not WSDL.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_WSI_ERR_ONEWAYRESPONSE	WARNING	R2714: For one-way operations, an INSTANCE MUST NOT return a HTTP response that contains a SOAP envelope. Specifically, the HTTP response entity-body must be empty. we got the element soap:	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			Envelope.		
APPFW_RESP	APPFW_XML_WSI_ERR_RESPONSESTATUS200OR202	WARNING	R1112: An INSTANCE SHOULD use either a "200 OK" or "202 Accepted" HTTP status code for a response that does do not contain a SOAP message but indicates successful HTTP outcome of a request. We	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			got '%d' HTTP response code.		
APPFW_RESP	APPFW_XML_WSI_ERR_RESPONSEWRAPPED	WARNING	R2729: A MESSAGE described with an rpc-literal binding that is a response message MUST have a wrapper element whose name is the corresponding wsdl:operation	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			name suffixed with the string "Response". Element name should be '%sResponse' but got '%s'.		
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPACTIONHEADERMATCH	WARNING	R2744: A HTTP request MESSAGE MUST contain a SOAP Action HTTP header field with a quoted value equal to the value	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			of the soapAction attribute of soapbind:operation, if present in the corresponding WSDL description. Expected '%s' soapAction but got '%s' soapAction in HTTP header.		
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPACTIONQUOTED	WARNING	R1109: The value of the SOAP Action HTTP heade	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			r field in a HTTP request MESSAGE MUST be a quoted string. We got '%s' SOAP Action HTTP header.		
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTALLOWEDCHILD	WARNING	R1000: When a MESSAGE contains a soap:Fault element, that element MUST NOT have element	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			children other than faultcode, faultstring, faultactor and detail. Element '%s' is not a allowed child of 'soap: Fault'.		
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTCHILDQ	WARNING	R1001: When a MESSAGE contains a soap:Fault element its element children MUST	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			be unqualified. 'soap: Fault' child '%s' should be unqualified.		
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTINHTTP	WARNING	R1126: An INSTANCE MUST use a "500 Internal Server Error" HTTP status code if the response message is a SOAP Fault. We got '%s' HTTP respon	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			se code.		
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTNONENV	WARNING	R1003: A RECEIVER MUST accept fault messages that have any number of qualified or unqualified attributes, including zero, appearing on the detail element. The namespace of qualified attribut	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			es can be anything other than the namespace of the qualified document element 'Envelope'. Namespace of attribute '%s' should not be the same as that of the qualified document element 'Envelope'.		

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPGOODXML10	WARNING	BP1601: The soap:Envelope or soap:Body does not conform to XML 1.0. Error is '%s'.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_STDFAULTCODE	WARNING	R1004: When a MESSAGE contains a faultcode element the content of that element SHOULD be one of the fault codes	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			defined in SOAP 1.1 or a namespace qualified fault code. 'faultcode' '%s' is not defined in SOAP 1.1 or it is not namespace qualified.		
APPFW_RESP	APPFW_XML_WSI_ERR_USE HTTP 10OR 11	WARNING	R1141: A MESSAGE MUST be sent using either HTTP/1.1 or HTTP/1.0.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			We got HTTP version '%s'.		
APPFW_RESP	APPFW_XML_WSI_ERR_USE HTTP 11	WARNING	R1140: A MESSAGE SHOULD be sent using HTTP/1.1. We got HTTP version '%s'.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_WSI CLAIMSWELLFORMED	WARNING	R0004: A MESSAGE MAY contain conformance claims, as specified in the conformance claim	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			schema. Either 'conformsTo' attribute is absent or 'soap:mustUnderstand' attribute is present on element '%s'.		
APPFW_RESP	APPFW_XML_WSI_ERR_WSI_LIST_NULL	WARNING	AppFw XML WSI List Null.	"%s"	
APPFW_RESP	APPFW_XML_WSI_ERR_XML_PI	WARNING	R1009: A MESSAGE MUST NOT contain Processing	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			Instructions. Name of Processing Instruction is '%s'.		
APPFW_RESP	APPFW_XML_WSI_ERR_XSINIL	WARNING	R2211: A MESSAGE described with an rpc-literal binding MUST NOT have the xsi:nil attribute with a value of "1" or "true" on the part accessors. Eleme	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			nt '%s' must not have the xsi:nil attribute.		
APPFW_RESP	APPFW_XML_XSD_COMPILE_INIT_ERR	WARNING	Error during initialization	"%s"	
APPFW_RESP	APPFW_XML_XSD_COMPILE_LOADXSD_ERR	WARNING	AppFw XML XSDLOAD Failed during Compile	"%s"	
APPFW_RESP	APPFW_XML_XSD_COMPILE_NOMODEL_ERR	WARNING	No XSModel to print	"%s"	
APPFW_RESP	APPFW_XML_XSD_COMPILE	INFO	Error during parsing	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	_PARSE_ERR				
APPFW_RESP	APPFW_XML_XSD_COMPILE_UNEXPECTED_ERR	WARNING	Unexpected exception during parsing	"%s"	
APPFW_RESP	APPFW_XML_ERR_SOAP_FAULT	WARNING	Message contains SOAP Fault.	"%s"	
APPFW_RESP	APPFW_XML_SOAP_FAULT_CONTENTS	WARNING	Dumps the SOAP Fault contents to Audit log.	"%s"	
APPFW_RESP	AF_INVALID_HTTP_HEADER	WARNING	Error while parsing HTTP headers.	"Error whileparsing HTTP headers.");returnns_printlogmsg	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				_appsec(buf	
APPFW_RESP	APPFW_CCARD_MATCH_IN_SIGNATURES	INFO	Credit card violation in signatures	"%s"	
AAATM	LOGIN	INFO	Login to AAATM vserver succeeds	"User %s- Client_ip%s- ""Nat_ip%s- Vserver%s: %d- Browser_type\"%s\"- Group(s) \"%s\""	
AAATM	LOGOUT	INFO	AAATM session logged out	"User %s-"" Client_ip%s- Nat_ip%s-"" Vserver%s: %d-"" Start_time\"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				%s\"-End_time\"%s\"-Duration%s-""Http_resources_accessed%s-""Total_TCP_connections%d-""Total_policies_allowed%d-Total_policies_denied%d-""Total_bytes_send%s-Total_bytes_recv%s-""Total_compressedbytes_send%s-Total_	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				compressed bytes_recv%s-""Compression_ratio_send%d.%02u%%-""Compression_ratio_recv%d.%02u%%-""LogoutMethod\"%s\"-Group(s)\"%s\""	
AAATM	HTTP REQUEST	DEBUG	A AAATM session receives a HTTP request	"[TECHSUPPORT][ENUMERATION]%sUser%s:Group(s)%s:Vs	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				erver %s: %d- %s:"" Message=SSOis%s: %s%s %s"	
AAATM	HTTP_RESOURCEACCESS_DENIED	NOTICE	A http resource access is denied by policy engine. The denied policy name is captured in the log message.	"-Denied_by_policy\"%s\""	
NSIP6	IPV6_DUPLICATED	INFO	IPv6 address got duplicated.	"%s"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
ICA	SESSION_SETUP	DEBUG	ICA session setup	"[HDXINSIGHT]session_guid%s-device_serial_number%u-client_cookie:%s-""flags%llu-session_setup_time%s-client_ip%s-client_type%d-""client_launcher%d-client_version%s-client_hostname%s-""domain_name%s-server	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				_name %s-connection_priority %u-""access_type %d-status %d-username%s"	
ICA	CHANNEL_UPDATE	DEBUG	ICA channel update	"[HDXINSIGHT]session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-channel_update_begin%s-channel_update_end%s-""chann	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				el_id_1%d-channel_id_1_val%d-channel_id_2%d-channel_id_2_val%d-""channel_id_3%d-channel_id_3_val%d-channel_id_4%d-channel_id_4_val%d-""channel_id_5%d-channel_id_5_val%d"	
ICA	SESSION_UPDATE	DEBUG	ICA session update	"[HDXINSIGHT]session_	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				guid%s-device_serial_number%u-""client_cookie%s-flags%llu-""nsica_session_status%d-""nsica_session_client_ip%s-""nsica_session_client_port%d-""nsica_session_server_ip%s-""nsica_session_server_port%d-""nsica_session_reconnect_count	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				%d-""nsica_session_acr_count%d-""connection_priority%u-""timestamp%s-"	
ICA	L7_LATENCY_UPDATE	DEBUG	ICA L7 latency update	"[HDXINSIGHT]session_guid%s-device_serial_number%u-""client_cookie%s-flags%llu-""nsica_status%d-""L7LatencyThresholdFactor%d-""L7LatencyWaittime%d	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				-""L7Latency NotifyInterval %d-""L7LatencyMax Notify Count %d-""L7ThresholdBreach AvgClientsideLatency%d-""L7ThresholdBreachMax ClientsideLatency%d-""L7ThresholdBreachAvgServersideLatency%d-""L7ThresholdBreachMax ServersideLatency	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				%d-""MinL7 Latency%d-"	
ICA	SESSION_TERMINATE	DEBUG	ICA session terminate	"[HDXINSIGHT]session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-session_end_time%s"	
ICA	NETWORK_UPDATE	DEBUG	ICA network update	"[HDXINSIGHT]session_guid%s-device_serial_number%u-client_cookie%s-""flags%ll	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				u-ica_rtt%u-clientside_rxbytes%u-""clientside_txbytes%u-clientside_packet_retransmits%u-""serverside_packet_retransmits%u-clientside_rtt%u-serverside_rtt%u-""clientside_jitter%u-serverside_jitter%u"	
ICA	APPLICATIO	DEBUG	ICA applic	"[HDXINSIGHT]se	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	N_LAUNCH		ation launch	ssion_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-startup_duration%u-launch_mechanism%u-""app_launch_time%s-app_process_id%u-""app_name%s-module_path%s"	
ICA	APPLICATION_TERMINATE	DEBUG	ICA application terminate	"[HDXINSIGHT]session_guid%s-	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
				device_serial_number%u-client_cookie%s-""flags%llu-app_termination_type%d-app_process_id%u-""app_termination_time%s"	
RDP	RDP_EVENT	DEBUG	RDP event	"User Name: %s	
RDP	RDP_CONNECTION_EVENT	DEBUG	RDP connection event	"User Name: %s	
CLI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in	"User %s-ADM_User%s-Remote_ip%s-	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			NetScaler	Command\"%s\"-""Status\"%s\""	
GUI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-ADM_User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""	
API	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-ADM_User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""	
CONSOLE	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command	"User%s-ADM_User%s-Remot	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
			executed in NetScaler	e_ip%s-Command\"%s\"-""Status\"%s\""	
BOT	BOT_WHITELIST	INFO	Bot whitelist	"Allow whitelist.URL: %.*sLogMsg:%.*s"	
BOT	BOT_BLACKLIST	INFO	Bot blacklist	"Disallowblacklist.URL: %.*sLogMsg: %.*s<%s>"	
BOT	BOT_IPREP	INFO	Bot iprep	"DisallowmaliciousIP.Category: %.*sURL: %.*sLogMsg: %.*s<%s>"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
BOT	BOT_DEVICE_FINGERPRINT	INFO	Bot Device Finger Print	"DeviceFingerPrintvalidationfailed.URL: %.*s<%s>"	
BOT	BOT_RATE_LIMIT	INFO	Bot Rate Limit	"ConnectionRateLimithit.URL: %.*sLogMsg: %.*s<%s>"	
BOT	BOT_STATIC_SIGNATURE	INFO	Bot static signature log.	"Botsignaturematched.User-Agent: %s(%u)Type: %sURL: %.*s<%s>"	
BOT	BOT_SIG_AUTO_	INFO	Bot signature auto	"BotNewSignatureAvaila	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	UPDATE		update log.	ble.NewlyaddedRules: %uDeletedRules: %u\n"	
BOT	BOT_TRAP_URL	INFO	Bot Trap URL.	"Trap URLSession.URL: %.*s< %s>"	
BOT	BOT_CAPTCHA	INFO	Bot Captcha	"Captchamax attempts(%u) exceeded.URL: %.*sLogMsg: %.*s< %s>"	
BOT	BOT_TPS	INFO	Bot TPS.	"TPSIPlimithitforIP: %sURL: %.*sLogMsg: %.*s< %s>"	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
BOT	BOT_LOGEXPRESSION	INFO	Bot Log Expression.	"%s%u-PPE%u%s%s%.*s%.*s"	
ROUTING	PAL	VARIABLE			
PITBOSS	PITBOSS	INFO	Pitboss watch is added on a process with the process id pid	Adding pitboss watch on (%d)	
PITBOSS	PITBOSS	INFO	Pitboss watch is deleted on a process with the process id pid	Deleting watch on (%d)	
PITBOSS	PB_SYSTEM_RE	ALERT	Process with pid	proc (%d) (%s)	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
	START		has reached maximum number of restarts.Therefore the system is being restarted	has had its maximum number of restarts (%d), rebooting the system	
PITBOSS	PB_PROCESS_RESTART	ALERT	Process with pid is being restarted.The message indicates the number of times the process has been restarted	Restarting process old pid (%d) action (%s)	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
ROUTING	ROUTE_ADVERTISED	INFO	Route Advertised	ROUTE (%s %s %s) - ADVERTISED	
ROUTING	ROUTE_WITHDRAWN	INFO	Route Withdrawn	ROUTE (%s %s %s) - WITHDRAWN	
ROUTING	ROUTE_RELEARN		Route Relearnt	RELEARN (0x%x)	
ROUTING	ROUTE_HASTATE	INFO	HA state change	HASTATE (0x%x)	
CVPN	CVPN_INPUT_URL	DEBUG	The input URL before rewriting	HTML_URL %s	
CVPN	CVPN_REWRITTEN_URL	DEBUG	The rewritten url	REWRITTEN_URL %.*s	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT	
CVPN	CVPN_PCRE_ERROR	DEBUG	PCRE Error	Regex %.*s : PCRE_ERROR %d	
CVPN	CVPN_MATCHED_URL	DEBUG	The matched url	MATCHED_URL %.*s	

ADC 13.1 Syslog Message Reference

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
TCP	CONN_DELINK	INFO	When a server side and a client side TCP connection is delinked.These are the connections which are being tracked by netscaler like HTTP	"Source%s:%d-Vserver%s:%d-NatIP%s:%d-""Destination%s:%d-DelinkTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu"
TCP	CONN_TERMINATE	INFO	When a TCP connection terminates.The logged data indicates the number of bytes transmitted and received over the connection and lso the connection start and end time	"Source%s:%d-Destination%s:%d-""StartTime%s-EndTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu"
TCP	OTHERCONN_DELINK	INFO	When a server side and a client side TCP connection is delinked.These are the connections which are not	"Source%s:%d-Vserver%s:%d-NatIP%s:%d-""Destination%s:%d-DelinkTime%s""Total_bytes_send%u-

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			being tracked by netscaler like FTP,telnet etc	Total_bytes_recv%u"
TCP	NAT_CONN_DELINK	INFO	When a server side and a client side TCP connection for RNAT are delinked we need to log the connection information	"Source%s:%d-Destination%s:%d-NatIP%s:%d-""Destination%s:%d-StartTime%s-DelinkTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu-ClosureReason%s"
TCP	NAT_OTHERCONN_DELINK	INFO	When a server side and a client side TCP connection for RNAT are delinked we need to log the connection information	"Source%s:%d-Destination%s:%d-NatIP%s:%d-""Destination%s:%d-StartTime%s-DelinkTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu-ClosureReason%s"
ACL	ACL_PKT_LOG	INFO	ACL Packet Log	"Source%s-->Destination%s-""ProtocolICMP-""Type%d-Code%d-""TimeStamp%d(ms)-Hitcount%d-HitRule%s-Action%s-Data"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ACL	ACL6_PKT_LOG	INFO	ACL6 Packet Log	"Source%s-->Destination%s-""ProtocolICMP-""Type%d-Code%d-""TimeStamp%d(ms)-Hitcount%d-HitRule%s-Action%s-Data"
LSN	LSN_SESSION	INFO	Info of LSN session created	"S%s%s C-%s:%d:%d N-%s:%d D-%s:%d:%d %s"
LSN	LSN_EIM_MAPPING	INFO	Info of LSN Endpoint independent mapping created	"EIM%s%s C-%s:%d:%d N-%s:%d %s"
LSN	LSN_ADDR_MAPPING	INFO	Info of LSN Address dependent mapping created	"ADM%s%s C-%s:%d:%d N-%s:%d D-%s:%d %s"
LSN	LSN_ADDRPORT_MAPPING	INFO	Info of LSN Address and Port dependent mapping created	"A&PDM%s%s C-%s:%d:%d N-%s:%d D-%s:%d:%d %s"
LSN	PPTP_LOG	INFO	Info of PPTP connection	"CALLREQUEST");break;
LSN	LSN_PORTBLOCK	INFO	Info of LSN Portblock mappings	"PB%s%s C-%s N-%s:%d-%d %s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
LSN	LSN_DETERMINISTIC	INFO	Info of LSN Portblock mappings	"DTR%s%s C-%s N-%s:%d-%d"
ALG	ALG_SIP_PARSE_PACKET_EVENT	ERROR	Error of SIP packet parsing	maxprintsize)
ALG	ALG_SDP_PARSE_PACKET_EVENT	ERROR	Error of SDP packet parsing	"Errmsg: \"%s\"-""Group: %s-""Call_ID: %s-""Transport: %s-""Source_IP: %s-""Source_port: %u-""Destination_IP: %s-""Destination_port: %u-""Natted_IP: %s-""Natted_port:%u-""Method: %s-""Sequence_Number: %u-""Register: %s-""Content_Type:%s-""Error: \"%s\"-""Error_line: \"%s\"-""Caller_user_name: %s-""Callee_user_name: %s-""Caller_domain_name: %s-""Callee_domain_name: %s-"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ALG	ALG_SIP_ERROR_PACKET_EVENT	ERROR	Error of SIP protocol	maxprintsize)
ALG	ALG_DHT_ERROR_PACKET_EVENT	ERROR	Error of SIP ALG DHT	"Errmsg: \"ErrorinDHTHandlingforSIPrequest\"-""Group: %s-""Call_ID: %s-""Transport: %s-""Source_IP: %s-""Source_port: %u-""Destination_IP: %s-""Destination_port: %u-""Natted_IP: %s-""Natted_port:%u-""Method: %s-""Sequence_Number: %u-""Register: %s-""Content_Type: %s-""Caller_user_name: %s-""Callee_user_name: %s-""Caller_domain_name: %s-""Callee_domain_name: %s"
ALG	ALG_SIP_GENERATE_ERRO	ERROR	Error of SIP generate	"Errmsg: \"SIPALGgenetateerror\"-""Error_Code:

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	R_PACKET_EVENT			%u-""Group: %s"
ALG	ALG_SIP_INFO_PACKET_EVENT	INFO	Info of SIP packet	"Infomsg: \"SIPrequest\"-" "Group: %s-""Call_ID: %s-""Transport: %s-""Source_IP: %s-""Source_port: %u-""Destination_IP: %s-""Destination_port: %u-""Natted_IP: %s-""Natted_port:%u-""Method: %s-""Sequence_Number: %u-""Register: %s-""Content_Type: %s-""Caller_user_name: %s-""Callee_user_name: %s-""Caller_domain_name: %s-""Callee_domain_name: %s-"
ALG	ALG_SIP_INFO_DELETE_CALL_PACKET_EVENT	INFO	Info of SIP call deletion	maxprintsize)

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ALG	ALG_RTSP_INFO_PACKET_EVENT	INFO	Info of RTSP packet	maxprintsize)
ALG	ALG_RTSP_INFO_DELETE_CALL_PACKET_EVENT	INFO	Info of RTSP call deletion	"Infomsg: \"LoginfoRTSPALGcalldeletion\"-""Group: %s-""Session_ID:%s-"
ALG	ALG_RTSP_PARSE_PACKET_EVENT	ERROR	Error of RTSP packet parsing	maxprintsize)
ALG	ALG_RTSP_ALG_PACKET_EVENT	ERROR	Error of RTSP ALG	maxprintsize)
ALG	ALG_RTSP_DHT_PACKET_EVENT	ERROR	Error of RTSP DHT	maxprintsize)
DNS	DNS_QUERY	INFO	Information of DNS queries recieved by the DNS endpoints on NetScaler	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
DNS	DNS_RESPONSE	INFO	Information of DNS responses served by the DNS endpoints on NetScaler to clients	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
DNS	DNS_ERROR	INFO	Information of errors	"Source%s:%d-Destination%s:

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			encountered during DNS packet processing on NetScaler	%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
SUBSCRIBER	SESSION_EVENT	INFO	Subscriber Session Event Info	"Session%s
SUBSCRIBER	SESSION_FAILURE	ERROR	Subscriber Session Failure Info	"FailureReason:%s
SSLI	INTERCEPT_LOG	INFO	SSL Interception Success Log	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
SSLI	BYPASS_LOG	INFO	SSL Interception Bypass Log	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
SSLI	DROPPED_LOG	INFO	SSL Interception Dropped Log	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
URLFILT	URLFILT_LOG	INFO	URL filtering Log	"Source%s-Destination%s""URL%s-""Category%s-

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
				Categorygroup %s- Reputation%d-" "Policyaction%s "
CI	ICAP_LOG	INFO	ICAP transaction Log.	"Source%s: %d-""Destination%s: %d-""Domain%s-""Content-Type%s-""ICAP Server%s: %d-""Mode%s-" "Service%s-""Response%d-""Action%s"
CI	ICAPC_LOG	INFO	ICAP custom log.	"%s"
CI	INLINE_INSPECTION_LOG	INFO	Inline Inspection transaction Log.	"ID%lld-""Source%s: %d-""Destination%s: %d-""Protocol%s-""URL%s-""Domain%s-""Service%s-""%s%s-""Action%s-""BytesSent%lld-"" BytesReceived %lld-""OriginServer%s:%d"
CI	TRAFFIC_MIRROR_LOG	INFO	Traffic Mirror transaction Log.	"ID%lld-""Source%s: %d-""Destination%s: %d-""Protocol%s-""URL%s-""D

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
				omain%s-""Service%s-""%s%s-""Action%s-""RequestBytesSent%lld-""ResponseBytesSent%lld-""OriginServer%s:%d"
AAA	LOGIN_FAILED	WARNING	When the aaa module failed to login the user.The reason for failure is indicated in the message	"User%s-Client_ip%s-Failure_reason\"%s\"-Browser%s"
AAA	EXTRACTED_GROUPS	INFO	After a user logs in the group for the user has been extracted	"Extracted_groups\"%s\""
UI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""
SSLVPN	LOGIN	INFO	SSLVPN login succeeds	"User%s-Client_ip%s-""Nat_ip%s-Vserver%s:%d-Browser_type\"%s\"-SSLVPN_client_type%s-Group(s)\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
SSLVPN	LOGOUT	INFO	SSLVPN session logs out.Logout method is captured in the message	"User%s-""Client_ip%s-Nat_ip%s-""Vserver%s:%d-""Start_time\"%s\"-End_time\"%s\"-Duration%s-""Http_resources_accessed%s-NonHttp_services_accessed%s-""Total_TCP_connections%d-Total_UDP_flows%d-""Total_policies_allowed%d-Total_policies_denied%d-""Total_bytes_send%s-Total_bytes_recv%s-""Total_compressedbytes_send%s-Total_compressedbytes_recv%s-""Compression_ratio_send%d.%02u%%-""Compression_ratio_recv%d.%02u%%-""LogoutMethod\"%s\"-Group(s)\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
SSLVPN	ICASTART	INFO	ICA application launch has started	"Source%s:%d-Destination%s:%d-""SSLRelayAddress%s:%d-""customername%s-""username:domainname%s-""applicationName%s-startTime\"%s\"-""connectionId%x"
SSLVPN	ICAEND_CONNSTAT	INFO	ICA application has terminated	"Source%s:%d-Destination%s:%d-""SSLRelayAddress%s:%d-""customername%s-""username:domainname%s-""startTime\"%s\"-endTime\"%s\"-""Duration%s-Total_bytes_send%u-Total_bytes_recv%u-""Total_compressedbytes_send%u-Total_compressedbytes_recv%u-""Compression_ratio_send%d.%02u%%-Compression_ratio_recv%d.%02u%%-""connectionId%x"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
SSLVPN	TCPCONNSTAT	INFO	Logs the TCP connection related information for a connection belonging to a SSLVPN session	"User%s-Client_ip%s-Nat_ip%s-Vserver%s:%d-""Source%s:%d-Destination%s:%d-Start_time\"%s\"-End_time\"%s\"-""Duration%s-Total_bytes_send%d-Total_bytes_recv%d-""Total_compressedbytes_send%d-Total_compressedbytes_recv%d-""Compression_ratio_send%d.%02u%%-Compression_ratio_recv%d.%02u%%-Access%s-Group(s)\"%s\""
SSLVPN	TCPCONN_TIMEDOUT	INFO	An SSLVPN connection timed out.The information about the connection start and end time the amount of data transferred and received are present in	"User%s-Client_ip%s-""Nat_ip%s-Vserver%s:%d-Last_contact\"%s\"-Group(s)\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			the message date	
SSLVPN	UDPFLOWSTAT	INFO	When a UDP flow , within a SSLVPN session, terminates	"User%s-Client_ip%s-""Nat_ip%s-Vserver%s:%d-Source%s:%d-""Destination%s:%d-Start_time\"%s\"-End_time\"%s\"-""Duration%s-Total_bytes_send%d-""Total_bytes_recv%d-Access%s-Group(s)\"%s\""
SSLVPN	HTTPREQUEST	INFO	A SSLVPN session receives a HTTP request	"%sUser%s:Group(s) %s:Vserver%s:%d-%s:SSOis%s:%s%s%s"
SSLVPN	NONHTTP_RESOURCEACCESS_DENIED	NOTICE	A non-http resource access is denied by policy engine. The denied policy name is captured in the log message.	"-Denied_by_policy\"%s\""
SSLVPN	HTTP_RESOURCEACCESS_DENIED	NOTICE	A http resource access is denied by policy engine.	"-Denied_by_policy\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			The denied policy name is captured in the log message.	
SSLVPN	LICLMT_REACHED	INFO	SSLVPN license limit reached	"Vserver%s:%d-License_limit%d"
SSLVPN	CLISEC_CHECK	ERROR	Logs with severity ERROR when client security check for a SSLVPN session fails, otherwise logs with severity DEBUG	"%s:%s-ClientIP%s-Vserver%s:%d-Client_security_expression\"%s\"-"
SSLVPN	CLISEC_EXP_EVAL	ERROR	Logs with severity ERROR when client security expression evaluates to False, otherwise logs with severity DEBUG	"User%s:-ClientIP%s-Vserver%s:%d-""Clientsecuritycheck%s%s(%d)ontheclient machine"
SSLVPN	STA_VALIDATE_RESP	INFO	After a user logs into SSLVPN and the group for the user has been extracted	"Xdatalen%d-Xdata%s"
SSLVPN	REMOVE_SESSION_DEBUG	DEBUG	Gives debug information of session before	"Sessionid%u-""User%s-""Client_ip%s-

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			removing session intentionally	Nat_ip%s-""Vserver_ip%s-""Errmsg\"%s\""
EVENT	ALERTSTARTED	ALERT	When SNMP module starts an alarm (usually when the value of a monitored attribute crosses the threshold value	"%s"
EVENT	ALERTENDED	ALERT	When SNMP module stops an alarm (usually when the value of a monitored attribute returns to normal state)	"%s"
EVENT	STARTSYS	INFO	When NetScaler starts	"%s"
EVENT	STARTCPU	INFO	When a particular CPU starts	"%s"
EVENT	DEVICEDOWN	NOTICE	Whenever a device is down	"%s"
EVENT	DEVICEOFS	NOTICE	Whenever a device is out of service	"%s"
EVENT	DEVICEUP	NOTICE	Whenever a device is up	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	NICSTART	NOTICE	When the network interface is started	"%s"
EVENT	NICSTOP	NOTICE	When the network interface is stopped	"%s"
EVENT	NICHANG	NOTICE	When the network interface is in hung state	"%s"
EVENT	NICRESET	NOTICE	When the network interface is reset	"%s"
EVENT	NICMIGRATE	NOTICE	When an interface is bound or unbound from a channel	"%s"
EVENT	STOPSYS	INFO	When the NetScaler system is stopped	"%s"
EVENT	FREEBADMEM	EMERGENCY	When bad memory is freed (internal error)	"%s"
EVENT	FREEDUPMEM	EMERGENCY	When duplicate memory free occurs (internal error)	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	FREEEXTMEM	EMERGENCY	When memory is freed from a wrong pool (internal error)	"%s"
EVENT	PROPSUCCESS	INFO	When HA propagation is successful	"%s"
EVENT	PROPFAIL	ALERT	When HA propagation fails	"%s"
EVENT	STATECHANGE	0	HA State has changed.The string along with the message gives more information	"%s"
EVENT	CLSTATECHANGE	0	Cluster State has changed.The string along with the message gives more information	"%s"
EVENT	CACHESTARTFLUSH	INFO	When cache flush starts	"%s"
EVENT	CACHESTOPFLUSH	INFO	When cache flush is complete	"%s"
EVENT	MONITORTH	INFO	The monitor bound to the service has hit threshold limit	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	MONITORDOWN	INFO	The monitor bound to the service is down.	"%s"
EVENT	MONITORUP	INFO	The monitor bound to the service is up.	"%s"
EVENT	ROUTEDOWN	INFO	When the route is down	"%s"
EVENT	ROUTEUP	INFO	When the route is up	"%s"
EVENT	VRID6DOWN	INFO	When the vrid changes state to backup	"%s"
EVENT	VRIDDOWN	INFO	When the vrid changes state to backup	"%s"
EVENT	VRIDUP	INFO	When the vrid changes state to master	"%s"
EVENT	VRIDINIT	INFO	When the vrid changes state to init	"%s"
EVENT	VIPRHIUP	INFO	When the rhi state of vip changes to up	"%s"
EVENT	VIPRHIDOWN	INFO	When the rhi state of vip changes to down	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	STARTSAVECONFIG	INFO	When save configuration started	"%s"
EVENT	STOPSAVECONFIG	INFO	When save configuration has stopped	"%s"
EVENT	CONFIGSTART	INFO	When NetScaler starts to read the configuration from ns.conf file (during boot-up)	"%s"
EVENT	CONFIGEND	INFO	When NetScaler has completed reading the configuration from ns.conf file (during boot-up)	"%s"
EVENT	NICLACPSC	NOTICE		"%s"
EVENT	NICLOW_THROUGHPUT	NOTICE	When an interface's throughput is less than the min required	"%s"
EVENT	NICNORMAL_THROUGHPUT	NOTICE	When an interface's throughput is equal or greater than the min required	"%s"
EVENT	NICPOWERON	NOTICE	When an interface is powered on	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	NICPOWEROFF	NOTICE	When an interface is powered off	"%s"
EVENT	DHCPSVRERR	INFO	When the DHCP server sends an invalid setting	"%s"
EVENT	DHCPCAQUIRE	INFO	When the DHCP client aquires a lease	"%s"
EVENT	DHCPCRELEASE	INFO	When the DHCP client releases a lease	"%s"
EVENT	DHCPCDEPENDPBR	INFO	When the DHCP lease is released and a PBR is dependent on the lease ip	"%s"
EVENT	ROUTE6DOWN	INFO	When the route6 is down	"%s"
EVENT	ROUTE6UP	INFO	When the route6 is up	"%s"
EVENT	MEPDOWN	NOTICE	Mep is down.	"%s"
EVENT	MEPUP	NOTICE	Mep is up.	"%s"
EVENT	BACKUPMEPDOWN	NOTICE	Backup Mep is down.	"%s"
EVENT	BACKUPMEPUP	NOTICE	Backup Mep is up.	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	NWMEPDOWN	NOTICE	Network metric Mep is down.	"%s"
EVENT	NWMEPUP	NOTICE	Network metric Mep is up.	"%s"
EVENT	BACKUPMEP6 DOWN	NOTICE	Backup ipv6 Mep is down.	"%s"
EVENT	BACKUPMEP6 UP	NOTICE	Backup ipv6 Mep is up.	"%s"
EVENT	UNKNOWN	DEBUG		"%s"
SSLLOG	SSL_HANDSH AKE_FAILURE	DEBUG	SSL HandShake Failure	"BackendSPCB Id%d-ServerIP%s-ServerPort%d-"\"ProtocolVersion%s-CipherSuite\"%s\"-"\"Session%s"
SSLLOG	SSL_HANDSH AKE_SUCCES S	DEBUG	SSL HandShake Success	"BackendSPCB Id%d-ServerIP%s-ServerPort%d-"\"ProtocolVersion%s-CipherSuite\"%s\"-"\"Session%s"
SSLLOG	SSL_CERT_EX PIRY_IMMINE NT	NOTICE	SSL Certificate Expiry Imminent	"CertificateKey Pair%s-DaysToExpire%u"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
SSLLOG	SSL_HANDSHAKE_ISSUERNAME	DEBUG	SSL Client Certificate IssueName	"SPCBId%d-IssuerName\"%s\""
SSLLOG	SSL_HANDSHAKE_SUBJECTNAME	DEBUG	SSL Client Certificate SubjectName	"SPCBId%d-SubjectName\"%s\""
SSLLOG	SSL_CRL_UPDATE_SUCCESS	NOTICE	SSL CRL Update Success	"crl_name%s-server_ip%s-server_port%d-"\"methodLDAP-ldapscope%s-"
SSLLOG	SSL_CRL_UPDATE_FAILURE	NOTICE	SSL CRL Update Failure	"crl_name%s-server_ip%s-server_port%d-"\"methodLDAP-ldapscope%s-"
SSLLOG	SSL_OCSPURL_RESOLVE_SUCCESS	DEBUG	SSL OCSPURL Resolve Success	"Domainname%sIpaddress%s"
SSLLOG	SSL_OCSPURL_RESOLVE_FAILURE	DEBUG	SSL OCSPURL Resolve Failure	"Domainname%sIpaddress%s"
SSLLOG	SSL_OCSPRESPONSE_SUCCESS	DEBUG	SSL OCSPResponse Success	"%02x"
SSLLOG	SSL_OCSPRESPONSE_FAILURE	DEBUG	SSL OCSPResponse Failure	"%02x"
APPFW	APPFW_STARTURL	INFO	AppFw StartURL violation	"DisallowIllegalURL.");}else{

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_MULTIPLE_HEADER	INFO	AppFw Multiple Header violation	"Multipleheadersinrequest");}
APPFW	APPFW_XMLPAYLOAD_CONTENT_TYPE_MISMATCH	INFO	AppFw Infer Content-Type Payload violation	"XMLMismatchedcontent-typeinHTTPheaderdetected=\"%s\"."
APPFW	APPFW_LOGEXPRESSION	INFO	AppFw Log Expression details	"%.*s"
APPFW	APPFW_DENYURL	INFO	AppFw DenyURL violation	"DisallowDenyURLforrulepattern=\"%s\"."
APPFW	APPFW_CONTENT_TYPE	INFO	AppFw Content-type violation	"Unknowncontent-typeheadervalue=\"%s\"."
APPFW	APPFW_REFERER_HEADER	INFO	AppFw Referer header violation	"parsingrefererheader'%s'failed"
APPFW	APPFW_CSRF_TAG	INFO	AppFw CSRF tag violation	"CSRFTagvalidationfailed");}
APPFW	APPFW_XSS	INFO	AppFw XSS violation	"%s"
APPFW	APPFW_XML_XSS	WARNING	AppFw XSS violation in XML	"%s"
APPFW	APPFW_SQL	INFO	AppFw SQL Injection violation	"%s"
APPFW	APPFW_SQL_GRAM	INFO	AppFw SQL Injection violation	"%sGrammar-basedSQLidete

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			reported by SQL Grammar	ctedfor%s%s=\" %s\""
APPFW	APPFW_XML_SQL	WARNING	AppFw SQL Injection violation in XML	"%s"
APPFW	APPFW_CMD	INFO	AppFw CMD Injection violation	"%s"
APPFW	APPFW_COOKIE	INFO	AppFw Cookie Consistency violation	"%s"
APPFW	APPFW_FIELDCONSISTENCY	INFO	AppFw Field Consistency violation	"%s"
APPFW	APPFW_FILE_UPLOAD_TYPE	INFO	AppFw File Upload Type violation	"%s"
APPFW	APPFW_BUFFEROVERFLOW_URL	INFO	AppFw Buffer Overflow violation in URL	"URLlength(%d)isgreaterthanmaximumallowed(%d)."
APPFW	APPFW_BUFFEROVERFLOW_COOKIE	INFO	AppFw Buffer Overflow violation in Cookie	"Cookieheaderlength(%d)isgreaterthanmaximumallowed(%d)."
APPFW	APPFW_BUFFEROVERFLOW_HDR	INFO	AppFw Buffer Overflow violation in HTTP Headers	"Header(%s)length(%d)isgreaterthanmaximumallowed(%d)."
APPFW	APPFW_BUFFEROVERFLOW_QUERY	INFO	AppFw Buffer Overflow	"Querystringlength(%d)isgreate

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			violation in Query string	rthanmaximum allowed(%d)."
APPFW	APPFW_BUFFEROVERFLOW_TOTAL_HDR	INFO	AppFw Buffer Overflow violation in total HTTP header length	"TotalHTTPheaderlength(%d)isgreaterthanmaximumallowed(%d)."
APPFW	APPFW_FIELDFORMAT	INFO	AppFw Field Format violation	"%s"
APPFW	APPFW_SAFECOMMERCE	INFO	AppFw Safe Commerce violation	"%s"
APPFW	APPFW_SAFECOMMERCE_XFORM	INFO	AppFw Safe Commerce violation detected and transformed	"%s"
APPFW	APPFW_SAFEOBJECT	INFO	AppFw Safe Object violation	"%s"
APPFW	APPFW_POLICY_HIT	INFO	AppFw profile invoked	"%s%u-PPE%u%s%s%s<%s>"
APPFW	APPFW_POLICY_HIT_BUILTIN	INFO	AppFw built-in profile invoked	"%s"
APPFW	APPFW_MAX_UPLOADS	INFO	File uploads exceed the allowed number	"%s"
APPFW	APPFW_SIGNATURE_MATCH	INFO	AppFw signature violation	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	AF_BIND_TO_PROFILE	INFO	AppFw rule bound to HTML profile	"Profile:%s
APPFW	AF_BIND_XML_TO_PROFILE	INFO	AppFw rule bound to XML profile	"Profile:%s
APPFW	AF_ADD_FIELDTYPE	INFO	Add an AppFw Field Type	"FieldType:%s
APPFW	AF_ADD_PROFILE	INFO	Add an AppFw profile	"Profile:%s\n"
APPFW	AF_RM_FIELDTYPE	INFO	Remove an Appfw Field Type	"FieldType:%s
APPFW	AF_RM_PROFILE	INFO	Remove an AppFw profile	"Profile:%s\n"
APPFW	AF_ADD_CFFIELD	INFO	Add a confidential field	"FieldName:%s
APPFW	AF_RM_CFFIELD	INFO	Remove a confidential field	"FieldName:%s
APPFW	AF_400_RESP	INFO	AppFw Request error. Generated 400 Response	"%s"
APPFW	AF_5XX_RESP	INFO	Server Error. Generated 5XX Response	"%s"
APPFW	AF_RESPONSE_PARSE_ERR	INFO	Response parse error	"Badresponsecacheheader"');

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	AF_MEMORY_ERR	WARNING	Memory allocation request for %lu bytes failed	"Contentlengthistoolarge(%lluBytes).MemoryAllocationfailed."
APPFW	AF_ORIGIN_SERVER_RESP_MISMATCH_ERR	WARNING	Origin server sent a response but AppFw needed something different	"Partial(range)requestsenttobackendserverincorrectly");
APPFW	AF_MALFORMED_REQ_ERR	INFO	Malformed request	"Malformedmulti-partrequest-connectionreset");break;
APPFW	AF_UTHREAD_STACK_ERR	ERROR	Appsecure uthread at 0x%x had a stack error	"Uthreadstackpointeroverflowed:");
APPFW	AF_SIGNATURE_ERR	INFO	Signature error	"Signatureid%ucontainsnofastmatchpattern"
APPFW	AF_STREAM_MSG_ERR	WARNING	Stream message error	"Lookupofprofilename'");
APPFW	AF_GENERIC_ERR_WITH_URL	WARNING	Generic error with URL	"Internalerror:additionaldatageneratedafterpartialresponsefor'");
APPFW	APPFW_XML_ATTACHMENT_FOUND	WARNING	Attachment Found in the XML Message.	"%s"
APPFW	APPFW_XML_ATTACHMENT	WARNING	XML Attachment	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	_ERR_CALLBACK_NULL		CallBack is NULL but HTTP message is MIME Attachment message.	
APPFW	APPFW_XML_ATTACHMENT_ERR_INVALID HEADER	WARNING	String %s is supposed to be MIME Header. But it is not according to the format of Mime Header HeaderName:HeaderValue	"%s"
APPFW	APPFW_XML_ATTACHMENT_ERR_INVALID_HEADER	WARNING	HTTP Content type should be 'application/xop+xml' or '\^(text	application)/([a-zA-Z]*\+xml xml)' but we got %s. "%s"
APPFW	APPFW_XML_ATTACHMENT_ERR_BOUNDARY_MISMATCH	WARNING	Boundary mismatch in mime message.	"%s"
APPFW	APPFW_XML_ERR_NO_ATTACHMENT_BOUNDARY	WARNING	The message having content-type as 'Multipart/Related' and not having a boundary is invalid.	"%s"
APPFW	APPFW_XML_ATTACHMENT	WARNING	XML Message has an Attachment with size greater	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	_ERR_MAX_SIZE		than the Configured Max Attachment Size.	
APPFW	APPFW_XML_ATTACHMENT_ERR_CONTENT_TYPE	WARNING	XML Message has an Attachment with Illegal Content-Type	"%s"
APPFW	APPFW_XML_DDOS_ERR_MSG_SEND_FAIL	WARNING	AppFw XML DDoS Send Fail Error.	"%s"
APPFW	APPFW_XML_DOS_ERR_CHAR_DATA_LENGTH	WARNING	Exceeds max character data length.	"%s"
APPFW	APPFW_XML_DOS_ERR_DTD	WARNING	DTD present in the XML message.	"%s"
APPFW	APPFW_XML_DOS_ERR_EXT_ENTITY	WARNING	External entities present in the XML message.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX	WARNING	AppFw XML DoS Maximum Error	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTES	WARNING	Element '%s' exceeds maximum attributes per element.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE	WARNING	In element '%s' an attribute exceeds	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	_NAME_LENGTH		maximum name length.	
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_VALUE_LENGTH	WARNING	In element '%s' attribute '%s' exceeds maximum attribute value length.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENTS	WARNING	Element '%s' exceeds maximum elements per message.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_CHILDREN	WARNING	Parent of element '%s' exceeds maximum children at element '%s'.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_DEPTH	WARNING	Element '%s' exceeds maximum element depth.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_NAME_LENGTH	WARNING	Element '%s' exceeds maximum element name length.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_FILE_SIZE	WARNING	Message size exceeds max size.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_NODES	WARNING	Node '%s' exceeds maximum	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			nodes per message.	
APPFW	APPFW_XML_DOS_ERR_MIN_FILE_SIZE	WARNING	Message size less than min size.	"%s"
APPFW	APPFW_XML_ERR_NOT_WELLFORMED	WARNING	Message is not a well-formed XML.	"%s"
APPFW	APPFW_XML_DOS_ERR_PI	WARNING	Processing instructions present in the XML message.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_NAMESPACES	WARNING	Element '%s' exceeds maximum active namespaces.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_NAMESPACEURI_LENGTH	WARNING	In element '%s' a namespace exceeds maximum uri length.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSION_DEPTH	WARNING	Exceeds max entity expansion depth	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSIONS	WARNING	Exceeds max number of entity expansions	"%s"
APPFW	APPFW_XML_DOS_ERR_MA	WARNING	Exceeds max total SOAP array size	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	X_SOAPARRAY_SIZE			
APPFW	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_RANK	WARNING	Exceeds max SOAP array rank	"%s"
APPFW	APPFW_XML_ERR_CUSTOM	WARNING	AppFw XML internal error	"%s"
APPFW	APPFW_XML_ERR_DDOS_CONNECT_TO_SERVER_FAILED	WARNING	AppFw XML DDoS Connect to Server Failed.	"%s"
APPFW	APPFW_XML_ERR_DDOS_INTERATION_SOCKET_OPEN_FAIL	WARNING	AppFw XML DDoS Interaction socket open Failed.	"%s"
APPFW	APPFW_XML_ERR_DDOS_INVALID_CONFIG_FILE	WARNING	AppFw XML DDoS Invalid Config File.	"%s"
APPFW	APPFW_XML_ERR_DDOS_NO_FOLDER_INSTALLATION_PATH	WARNING	AppFw XML DDoS No Folder Installation Path.	"%s"
APPFW	APPFW_XML_ERR_DDOS_OPEN_CONFIG_FILE_FAIL	WARNING	AppFw XML DDoS Failure to Open Config File.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_ERR_DOS_TRIGGERED	WARNING	Denial of Service Error.	"%s"
APPFW	APPFW_XML_ERR_ENV_NOT_SET	WARNING	Environment variable QTHOME not set.	"%s"
APPFW	APPFW_XML_ERR_HASH_INSERT	WARNING	Problems inserting a namespace into the hash table.	"%s"
APPFW	APPFW_XML_ERR_HASH_LOOKUP	WARNING	Problems getting the key of a namespace from the hash table.	"%s"
APPFW	APPFW_XML_ERR_INITIALIZING_TOKENIZER	WARNING	Unable to initialize XML tokenizer.	"%s"
APPFW	APPFW_XML_ERR_INVALID_FILE	WARNING	Unable to open the file.	"%s"
APPFW	APPFW_XML_ERR_INVALID_STATE	WARNING	AppFw XML Internal State Invalid.	"%s"
APPFW	APPFW_XML_ERR_INVALID_XPATH	WARNING	Invalid XPath.	"%s"
APPFW	APPFW_XML_ERR_LOW_MEMORY	WARNING	AppFw XML Low memory.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_ERR_CHARDATA_LIMIT_EXCEEDED	WARNING	AppFw XML character data size exceeds the limit of 30MB	"%s"
APPFW	APPFW_XML_ERR_MALFORMED_ADDRESS	WARNING	Malformed address	"%s"
APPFW	APPFW_XML_ERR_NO_DIME	WARNING	NS-XML APPFW supports SwA and MTOM SOAP attachments, but attachment with this message is DIME.	"%s"
APPFW	APPFW_XML_ERR_OPERATION_CALLBACK	WARNING	Problems registering callbacks for operations.	"%s"
APPFW	APPFW_XML_ERR_PREFIX_LENGTH_EXCEEDED	WARNING	Prefix length %d exceeded, encountered length is %d.	"%s"
APPFW	APPFW_XML_ERR_READ_FAILED	WARNING	AppFw XML Read Failure	"%s"
APPFW	APPFW_XML_ERR_STREAM_POP	WARNING	Problems during pop of the node out of the XML stream.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_ERR_STREAM_PUSH	WARNING	Problems during push of the node into the XML stream.	"%s"
APPFW	APPFW_XML_ERR_UNSUPPORTED_PORT	WARNING	Port in address %s is greater than 65535.	"%s"
APPFW	APPFW_XML_ERR_UNSUPPORTED_PROTOCOL	WARNING	Unsupported protocol	"%s"
APPFW	APPFW_XML_ERR_VALIDATION_FAILED	WARNING	AppFw XML Validation Failed	"%s"
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_NULL	WARNING	AppFw XML Context is NULL.	"%s"
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_STATE_NULL	WARNING	Context user state is NULL; internal error.	"%s"
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_MESSAGE_CONFIG_NULL	WARNING	Message config struct is NULL.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_ABSTRACT_ELEMENT	WARNING	Cannot instantiate abstract element	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_VALIDATION_ERR_ABSTRACT_TYPE	WARNING	Cannot instantiate abstract type '%s', for element '%s'.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_ADDHEADERS	WARNING	Additional soap header %s present in soap message.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MAX_OCCURS	WARNING	Attribute '%s' appears more than once in element '%s'.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MIN_OCCURS	WARNING	Required attribute missing in element	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_CONTENT_MODEL_VIOLATED	WARNING	Content model of element '%s' not satisfied.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_CORRUPT_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_VALIDATION_ERR_CORRUPT_SCHEMA	WARNING	Error compiling the schema	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_DATATYPE_ENGINE_INIT	WARNING	Initialization of the datatype engine failed.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INTERNAL	WARNING	Internal corruption of WSDL in-memory structure.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_ATTRIBUTE	WARNING	Attribute '%s' is invalid.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_COMBINATION	WARNING	Invalid configuration for soap validation.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_COMPILED_WSDL	WARNING	Not able to open compiled WSDL.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_CONTENT_MODEL	WARNING	Element '%s' has invalid content model.	"%s"
APPFW	APPFW_XML_VALIDATION_E	WARNING	Data type is invalid.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	RR_INVALID_DATATYPE			
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_ELEMENT	WARNING	Invalid element.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_FILE	WARNING	Not able to open the file.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_TYPE_SUBSTITUTION	WARNING	Did not get expected type for element '%s', got '%s'.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_LOADING	WARNING	Unable to load validation engine.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_MAX	WARNING	AppFw XML Validation Max Error.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_NOSERVICEURL	WARNING	Service Url is not present or NULL.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_NOT_SUPPORTED	WARNING	Feature not supported.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_BODY	WARNING	Soap Body structure check failed.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_ENVELOPE	WARNING	Soap Envelope structure check failed.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_HEADER	WARNING	Soap Header structure check failed.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_UNBOUNDED_PREFIX	WARNING	Prefix '%s' is unbounded.	"%s"
APPFW	APPFW_XML_VALIDATION_LOAD_ERR_CONTENTS_CANNOT_BE_NIL	WARNING	Element '%s' cannot be nil.	"%s"
APPFW	APPFW_XML_VALIDATION_LOAD_ERR_NIL_WITH_CONTENTS	WARNING	Element '%s' is nil, cannot have contents.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_REX_STACK_OVERFLOW	WARNING	Level of recursion more than maximum allowed depth.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_REX_STACK_EMPTY	WARNING	Trying to pop from an empty stack.	"%s"
APPFW	APPFW_XML_VALIDATION_E	WARNING	Both SOAP Body and SOAP Header	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	RR_SOAPBODY_EMPTY		are empty in the SOAP request.	
APPFW	APPFW_XML_GENERIC_ERR_EMPTYBODY_REQ	WARNING	Request body is empty in the XML request.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_DATATYPE_VALUE	WARNING	Value should be of type '%s'.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_LOCATION	WARNING	Element '%s' cannot appears at this location.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_FACET_MISMATCH	WARNING	Facet mismatch.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_FAILED	WARNING	AppFw XML Validator Load Failed.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_ATTRIBUTE_VALUE	WARNING	Attribute '%s' has invalid value '%s'.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INV	WARNING	Invalid schema datatype.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	ALID_DATATYPE			
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_SCHEMA_NODE_TYPE	WARNING	Invalid schema node type.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_VALUE_FOR_FIXED	WARNING	Value '%s' does not match FIXED constraint '%s'.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_GT_MAX	WARNING	List length is greater than max allowed.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_INVALID	WARNING	List length is invalid.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_LT_MIN	WARNING	List length is lesser than min allowed.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_MAX	WARNING	AppFw XML Validation Maximum Load Error.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_RE	WARNING	Missing require attribute '%s' in element '%s'.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	QUIRED_ATTRIBUTE			
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_SCHEMA_COMPILATION	WARNING	Error code in the compiled Schema is being ignored.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_WSDL_COMPILATION	WARNING	Error code in the compiled WSDL is being ignored.	"%s"
APPFW	APPFW_XML_WSI_ERR_ACCELEMENTNAMESPACED	WARNING	R2735: A MESSAGE described with an rpc-literal binding MUST place the part accessor elements for parameters and return value in no namespace. Element '%s' must be unqualified.	"%s"
APPFW	APPFW_XML_WSI_ERR_ARRAYTYPE	WARNING	R2113: A MESSAGE containing serialized arrays MUST NOT include the soapenc:arrayType attribute. Element '%s' must not	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			include the soapenc:arrayType attribute.	
APPFW	APPFW_XML_WSI_ERR_BAD_ENV_NAMESPACE	WARNING	R1015: A RECEIVER MUST generate a fault if they encounter a message whose document element has a local name of "Envelope" but a namespace name that is not "http://schemas.xmlsoap.org/soap/envelope/" or "http://www.w3.org/2003/05/soap-envelope". We got namespace '%s' in SOAP Request.	"%s"
APPFW	APPFW_XML_WSI_ERR_BINDINGFAULTRESP	WARNING	R2740: The response envelope contained soap:Fault element(s), but they were not defined in the WSDL description. Element '%s' should be	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			defined as soap:fault in WSDL description.	
APPFW	APPFW_XML_WSI_ERR_BODY_CHILD_NAMESPACE	WARNING	R1014: The children of the soap:Body element in a MESSAGE MUST be namespace qualified. Unqualified children of soap:Body is '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_BODY_ENV_NAMESPACE	WARNING	BP1201: The envelope does not use SOAP 1.1 or SOAP 1.2, i.e. does not have a document element named "Envelope" or a namespace value of http://schemas.xmlsoap.org/soap/envelope/ or http://www.w3.org/2003/05/soap-envelope. We got namespace '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_CHI	WARNING	R1011: A MESSAGE	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	LDAFTERBODY		MUST NOT have any element children of soap:Envelope following the soap:Body element. Element '%s' should not appear after 'soap:Body' element.	
APPFW	APPFW_XML_WSI_ERR_CLAIM_MUSTUNDERSTAND	WARNING	R0007: A SENDER MUST NOT use the soap:mustUnderstand attribute when sending a SOAP header block containing a conformance claim. soap:mustUnderstand attribute is present on element '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_CTXT_NULL	WARNING	AppFw XML WSI Internal Context NULL	"%s"
APPFW	APPFW_XML_WSI_ERR_DOCTYPEALLOWED	WARNING	R1008: A MESSAGE MUST NOT contain a Document Type Declaration.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			DOCTYPE name is '%s'.	
APPFW	APPFW_XML_WSI_ERR_DOT_NOTATION	WARNING	R1031: When a MESSAGE contains a faultcode element the content of that element SHOULD NOT use of the SOAP 1.1 "dot" notation to refine the meaning of the Fault. Data '%s' should not contain 'DOT'(.) in it.	"%s"
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLE	WARNING	R1005: A MESSAGE MUST NOT contain soap:encoding Style attribute on any of the elements whose namespace is the same as the namespace of the qualified document element 'Envelope'. 'soap:encoding Style' attribute should not be	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			present on element '%s'.	
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLECHILD	WARNING	R1006: A MESSAGE MUST NOT contain soap:encodingStyle attributes on any element that is a child of soap:Body. 'soap:encodingStyle' attribute should not be present on immidiate child '%s' of soap:Body.	"%s"
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLEGRANDCHILD	WARNING	R1007: A MESSAGE described in an rpc-literal binding MUST NOT contain soap:encodingStyle attribute on any elements are grandchildren of soap:Body. 'soap:encodingStyle' attribute should not be present on grandchild '%s' of soap:Body.	"%s"
APPFW	APPFW_XML_WSI_ERR_EN	WARNING	R1032: The soap:Envelope,	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	VELEMENTSNOATTRIBUTES		soap:Header, and soap:Body elements in an ENVELOPE MUST NOT have attributes in the same namespace as that of the qualified document element 'Envelope'. Attribute '%s' should not be in the same namespace as that of the qualified document element 'Envelope'.	
APPFW	APPFW_XML_WSI_ERR_ENVNONAMESPACE	WARNING	R1033: An ENVELOPE SHOULD NOT contain the namespace declaration xmlns:xml="http://www.w3.org/XML/1998/namespace".	"%s"
APPFW	APPFW_XML_WSI_ERR_GOODRESPONSE200	WARNING	R1111: An INSTANCE SHOULD use a "200 OK" HTTP status code for responses that contain a SOAP	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			message that is not a SOAP fault. We should not get 'soap:Fault' element when HTTP response code is '200 OK'.	
APPFW	APPFW_XML_WSI_ERR_HEADER_HAS_WSICLAIM	WARNING	R0005: A MESSAGE's conformance claims MUST be carried as SOAP header blocks. Element '%s' should be immidiate children of soap:Header.	"%s"
APPFW	APPFW_XML_WSI_ERR_HTTP	WARNING	AppFw XML WSI HTTP Error	"%s"
APPFW	APPFW_XML_WSI_ERR_ISHTTPPOST	WARNING	R1132: A HTTP request MESSAGE MUST use the HTTP POST method. We got '%s' HTTP method.	"%s"
APPFW	APPFW_XML_WSI_ERR_ISUTF8OR16	WARNING	R1012: A MESSAGE MUST be serialized as either UTF-8 or	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			UTF-16. We got encoding '%s'.	
APPFW	APPFW_XML_WSI_ERR_MSGHASALLHEADERS	WARNING	R2738: A MESSAGE MUST include all soapbind:headers specified on a wsdl:input or wsdl:output of a wsdl:operation of a wsdl:binding that describes it.Wsdl header %s is not present in soap message.	"%s"
APPFW	APPFW_XML_WSI_ERR_MUSTUNDERSTAND	WARNING	R1013: A MESSAGE containing a soap:mustUnderstand attribute MUST only use the lexical forms "0" and "1". Value of 'soap:mustUnderstand' attribute is '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_NODEPLOYED	WARNING	Resource id of deployment is NULL.	"%s"
APPFW	APPFW_XML_WSI_ERR_NOENVELOPEWSDLMATCH	WARNING	BP1701: The envelope does not conform to the SOAP	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			schema located at 'http://schemas.xmlsoap.org/soap/envelope/' or 'http://www.w3.org/2003/05/soap-envelope'.	
APPFW	APPFW_XML_WSI_ERR_NONPOSTREQUEST	WARNING	R1114: An INSTANCE SHOULD use a "405 Method not Allowed" HTTP status code if the request method was not "POST". We got '%d' HTTP status code.	"%s"
APPFW	APPFW_XML_WSI_ERR_NONXMLREQUEST	WARNING	R1115: An INSTANCE SHOULD use a "415 Unsupported Media Type" HTTP status code if a HTTP request message's Content-Type header field-value is not permitted by its WSDL description. we got '%d' HTTP status code.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_WSI_ERR_NO PORTURL	WARNING	Port URL is NULL.	"%s"
APPFW	APPFW_XML_WSI_ERR_NO REQWSDLMAT CH	WARNING	BP1011: The content of the request envelope does not match the wsdl:message definition.	"%s"
APPFW	APPFW_XML_WSI_ERR_NO RESPWSDLMA TCH	WARNING	BP1013 The content of the response envelope does not match the wsdl:message definition.	"%s"
APPFW	APPFW_XML_WSI_ERR_NO WSDLDEPLOY ED	WARNING	Deployed resource is not WSDL.	"%s"
APPFW	APPFW_XML_WSI_ERR_ON EWAYRESPON SE	WARNING	R2714: For one-way operations, an INSTANCE MUST NOT return a HTTP response that contains a SOAP envelope. Specifically, the HTTP response entity-body must be empty. we got the	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			element soap:Envelope.	
APPFW	APPFW_XML_WSI_ERR_RESPONSESTATUS200OR202	WARNING	R1112: An INSTANCE SHOULD use either a "200 OK" or "202 Accepted" HTTP status code for a response that does do not contain a SOAP message but indicates successful HTTP outcome of a request. We got '%d' HTTP response code.	"%s"
APPFW	APPFW_XML_WSI_ERR_RESPONSEWRAPPED	WARNING	R2729: A MESSAGE described with an rpc-literal binding that is a response message MUST have a wrapper element whose name is the corresponding wsdl:operation name suffixed with the string "Response". Element name should be	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			'%sResponse' but got '%s'.	
APPFW	APPFW_XML_WSI_ERR_SOAPACTIONHEADERMATCH	WARNING	R2744: A HTTP request MESSAGE MUST contain a SOAPAction HTTP header field with a quoted value equal to the value of the soapAction attribute of soapbind:operation, if present in the corresponding WSDL description. Expected '%s' soapAction but got '%s' soapAction in HTTP header.	"%s"
APPFW	APPFW_XML_WSI_ERR_SOAPACTIONQUOTED	WARNING	R1109: The value of the SOAPAction HTTP header field in a HTTP request MESSAGE MUST be a quoted string. We got '%s' SOAPAction HTTP header.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTALLOWEDCHILD	WARNING	R1000: When a MESSAGE contains a soap:Fault element, that element MUST NOT have element children other than faultcode, faultstring, faultactor and detail. Element '%s' is not a allowed child of 'soap:Fault'.	"%s"
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTCHILDQ	WARNING	R1001: When a MESSAGE contains a soap:Fault element its element children MUST be unqualified. 'soap:Fault' child '%s' should be unqualified.	"%s"
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTINHTTP	WARNING	R1126: An INSTANCE MUST use a "500 Internal Server Error" HTTP status code if the response message is a SOAP Fault. We got '%s'	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			HTTP response code.	
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTNONENV	WARNING	R1003: A RECEIVER MUST accept fault messages that have any number of qualified or unqualified attributes, including zero, appearing on the detail element. The namespace of qualified attributes can be anything other than the namespace of the qualified document element 'Envelope'. Namespace of attribute '%s' should not be the same as that of the qualified document element 'Envelope'.	"%s"
APPFW	APPFW_XML_WSI_ERR_SOAPGOODXML10	WARNING	BP1601: The soap:Envelope or soap:Body does not conform to XML	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			1.0. Error is '%s'.	
APPFW	APPFW_XML_WSI_ERR_STDFAULTCODE	WARNING	R1004: When a MESSAGE contains a faultcode element the content of that element SHOULD be one of the fault codes defined in SOAP 1.1 or a namespace qualified fault code. 'faultcode' '%s' is not defined in SOAP 1.1 or it is not namespace qualified.	"%s"
APPFW	APPFW_XML_WSI_ERR_USEHTTP10OR11	WARNING	R1141: A MESSAGE MUST be sent using either HTTP/1.1 or HTTP/1.0. We got HTTP version '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_USEHTTP11	WARNING	R1140: A MESSAGE SHOULD be sent using HTTP/1.1. We got HTTP version '%s'.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_WSI_ERR_WSICLAIMSWELLFORMED	WARNING	R0004: A MESSAGE MAY contain conformance claims, as specified in the conformance claim schema. Either 'conformsTo' attribute is absent or 'soap:mustUnderstand' attribute is present on element '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_WSI_LIST_NULL	WARNING	AppFw XML WSI List Null.	"%s"
APPFW	APPFW_XML_WSI_ERR_XMLPI	WARNING	R1009: A MESSAGE MUST NOT contain Processing Instructions. Name of Processing Instruction is '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_XSINIL	WARNING	R2211: A MESSAGE described with an rpc-literal binding MUST NOT have the xsi:nil attribute with a value of	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			"1" or "true" on the part accessors. Element '%s' must not have the xsi:nil attribute.	
APPFW	APPFW_XML_XSD_COMPILE_INIT_ERR	WARNING	Error during initialization	"%s"
APPFW	APPFW_XML_XSD_COMPILE_LOADXSD_ERR	WARNING	AppFw XML XSDLOAD Failed during Compile	"%s"
APPFW	APPFW_XML_XSD_COMPILE_NOMODEL_ERR	WARNING	No XSModel to print	"%s"
APPFW	APPFW_XML_XSD_COMPILE_PARSE_ERR	INFO	Error during parsing	"%s"
APPFW	APPFW_XML_XSD_COMPILE_UNEXPECTED_ERR	WARNING	Unexpected exception during parsing	"%s"
APPFW	APPFW_XML_ERR_SOAP_FAULT	WARNING	Message contains SOAP Fault.	"%s"
APPFW	APPFW_XML_SOAP_FAULT_CONTENTS	WARNING	Dumps the SOAP Fault contents to Audit log.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	AF_INVALID_HTTP_HEADER	WARNING	Error while parsing HTTP headers.	"ErrorwhileparsingHTTPheaders.");
APPFW	APPFW_CCARD_MATCH_IN_SIGNATURES	INFO	Credit card violation in signatures	"%s"
APPFW	APPFW_SESSIONLIMIT	INFO	AppFw Session Limit reached	"AppfwmaximumsessionLimitreachedforPEID%d"
APPFW	AF_ADD_RFCPROFILE	INFO	Add an AppFw rfc profile	"APPFWRFCProfile:%s\n"
APPFW	AF_RM_RFCPROFILE	INFO	Remove an AppFw rfc profile	"APPFWRFCProfile:%s\n"
APPFW	APPFW_INV_RFC	INFO	RFC syntax violation. Generated 302 Response	"%s"
APPFW	APPFW_NEW_SIGNATURE_ADDED	INFO	AppFw New Signature Added	"Newsignatureavailable:RuleID=%d
APPFW	APPFW_JSON_DOS_MAX_DOCUMENT_LENGTH	INFO	AppFw JSON document length exceeded	"%s"
APPFW	APPFW_JSON_DOS_MAX_CONTAINER_DEPTH	INFO	AppFw JSON document exceeds maximum container depth	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_JSON_DOS_MAX_OBJECT_KEY_COUNT	INFO	AppFw JSON document has object that exceeds maximum key count	"%s"
APPFW	APPFW_JSON_DOS_MAX_OBJECT_KEY_LENGTH	INFO	AppFw JSON document has key in object that exceeds maximum key length	"%s"
APPFW	APPFW_JSON_DOS_MAX_ARRAY_LENGTH	INFO	AppFw JSON document has array exceeds maximum array length	"%s"
APPFW	APPFW_JSON_DOS_MAX_STRING_LENGTH	INFO	AppFw JSON document has string that exceeds maximum string length	"%s"
APPFW	APPFW_JSON_SQL	INFO	AppFw JSON document has sql violation	"%s"
APPFW	APPFW_JSON_XSS	INFO	AppFw JSON document has Cross-site script violation	"%s"
APPFW	APPFW_DEPLOY_RELAXATION_DP	INFO	AppFw relaxation about to be deployed through	"Learnedrulewill beauto-deployedafter%dmins.ViolType:%s.Profile:%s

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			Dynamic Learning	
APPFW	APPFW_COOKIE_HIJACK	INFO	AppFw Cookie Hijacking violation	"%s"
APPFW	APPFW_POSTBODYLIMIT	INFO	AppFw Post Body Limit violation	"%s"
APPFW	APPFW_JSON_CMD	INFO	AppFw JSON document has command injection violation	"%s"
APPFW	APPFW_JSON_SQL_GRAM	INFO	AppFw JSON document has SQL Injection violation reported by SQL Grammar	"%s"
ROUTING	ZEBOS_CMD_EXECUTED	INFO	The ZebOS command executed.	"%s"
SNMP	TRAP_SENT	INFO	Trap Sent Information	"%s"
SNMP	TRAP_DROPPED	INFO	Trap Dropped information. Traps are dropped due to rate-limiting	"%s"
TRANSFORM	FILE_REQUEST	DEBUG	URL Transformation profile invoked	"Client%s-Profile%s-%sinto%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
TRANSFORM	REQ_PARSE_ERROR	WARNING	URL Transformation parsing error	"Client%s-Profile%s-Failedtoparserequest URL%stransformation-URL%s"
TRANSFORM	REQ_HEADER	DEBUG	URL Transformation in a request header	"Client%s-Profile%s-Header%s-%sinto%s"
TRANSFORM	RESP_HEADER	DEBUG	URL Transformation in a response header	"Client%s-Profile%s-Header%s-%sinto%s"
TRANSFORM	BODY_FRAG	DEBUG	URL Transformation in a response body	"Client%s-Profile%s-Type%s-%sinto%s"
TRANSFORM	ACTION_MATCH	DEBUG	URL Transformation action matched URL	"Client%s-Profile%s-Action%s-%sinto%s"
TRANSFORM	ACTION_MISMATCH	DEBUG	URL Transformation action didn't match URL	"Client%s-Profile%s-Action%s-Value%s"
TRANSFORM	PCRE_ERROR	WARNING	URL Transformation regex error	"Client%s-Profile%s-Action%s-PCREerrorcode%d"
TRANSFORM	REQ_WRITE_ERROR	WARNING	URL Transformation	"Client%s-Profile%s-

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			error in a request header	Failedtowrite%s requestheader"
APPFW_RESP	APPFW_XML_XSS	WARNING	AppFw XSS violation in XML	"%s"
APPFW_RESP	APPFW_XML_SQL	WARNING	AppFw SQL Injection violation in XML	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_FOUND	WARNING	Attachment Found in the XML Message.	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_CALLBACK_NULL	WARNING	XML Attachment CallBack is NULL but HTTP message is MIME Attachment message.	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_INVALID HEADER	WARNING	String %s is supposed to be MIME Header. But it is not according to the format of Mime Header HeaderName:HeaderValue	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_INVALID_HEADER	WARNING	HTTP Content type should be 'application/xop+xml' or '\^(text	application)/([a-zA-Z]*\+xml xml)' but we got %s. "%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_BOUND	WARNING	Boundary mismatch in mime message.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	ARY_MISMATCH			
APPFW_RESP	APPFW_XML_ERR_NO_ATTACHMENT_BOUNDARY	WARNING	The message having content-type as 'Multipart/ Related' and not having a boundary is invalid.	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_MAX_SIZE	WARNING	XML Message has an Attachment with size greater than the Configured Max Attachment Size.	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_CONTENT_TYPE	WARNING	XML Message has an Attachment with Illegal Content-Type	"%s"
APPFW_RESP	APPFW_XML_DDOS_ERR_MSG_SEND_FAIL	WARNING	AppFw XML DDoS Send Fail Error.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_CHAR_DATA_LENGTH	WARNING	Exceeds max character data length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_DTD	WARNING	DTD present in the XML message.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_DOS_ERR_EXT_ENTITY	WARNING	External entities present in the XML message.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX	WARNING	AppFw XML DoS Maximum Error	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTES	WARNING	Element '%s' exceeds maximum attributes per element.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_NAME_LENGTH	WARNING	In element '%s' an attribute exceeds maximum name length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_VALUE_LENGTH	WARNING	In element '%s' attribute '%s' exceeds maximum attribute value length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENTS	WARNING	Element '%s' exceeds maximum elements per message.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_CHILDREN	WARNING	Parent of element '%s' exceeds maximum children at element '%s'.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_DEPTH	WARNING	Element '%s' exceeds maximum element depth.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_NAME_LENGTH	WARNING	Element '%s' exceeds maximum element name length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_FILE_SIZE	WARNING	Message size exceeds max size.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NODES	WARNING	Node '%s' exceeds maximum nodes per message.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MIN_FILE_SIZE	WARNING	Message size less than min size.	"%s"
APPFW_RESP	APPFW_XML_ERR_NOT_WELLFORMED	WARNING	Message is not a well-formed XML.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_PI	WARNING	Processing instructions present in the XML message.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NAMESPACES	WARNING	Element '%s' exceeds maximum active namespaces.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NAMESPACEURI_LENGTH	WARNING	In element '%s' a namespace exceeds maximum uri length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSION_DEPTH	WARNING	Exceeds max entity expansion depth	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSIONS	WARNING	Exceeds max number of entity expansions	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_SIZE	WARNING	Exceeds max total SOAP array size	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_RANK	WARNING	Exceeds max SOAP array rank	"%s"
APPFW_RESP	APPFW_XML_ERR_CUSTOM	WARNING	AppFw XML internal error	"%s"
APPFW_RESP	APPFW_XML_ERR_DDOS_CONNECT_TO_SERVER_FAILED	WARNING	AppFw XML DDoS Connect to Server Failed.	"%s"
APPFW_RESP	APPFW_XML_ERR_DDOS_INTERATION_SOCKET_OPEN_FAIL	WARNING	AppFw XML DDoS Interaction socket open Failed.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_ERR_DDOS_INVALID_CONFIG_FILE	WARNING	AppFw XML DDoS Invalid Config File.	"%s"
APPFW_RESP	APPFW_XML_ERR_DDOS_NO_FOLDER_INSTALLATION_PATH	WARNING	AppFw XML DDoS No Folder Installation Path.	"%s"
APPFW_RESP	APPFW_XML_ERR_DDOS_OPEN_CONFIG_FILE_FAIL	WARNING	AppFw XML DDoS Failure to Open Config File.	"%s"
APPFW_RESP	APPFW_XML_ERR_DOS_TRIGGERED	WARNING	Denial of Service Error.	"%s"
APPFW_RESP	APPFW_XML_ERR_ENV_NOT_SET	WARNING	Environment variable QTHOME not set.	"%s"
APPFW_RESP	APPFW_XML_ERR_HASH_INSERT	WARNING	Problems inserting a namespace into the hash table.	"%s"
APPFW_RESP	APPFW_XML_ERR_HASH_LOOKUP	WARNING	Problems getting the key of a namespace from the hash table.	"%s"
APPFW_RESP	APPFW_XML_ERR_INITIALIZING_TOKENIZER	WARNING	Unable to initialize XML tokenizer.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_ERR_INVALID_FILE	WARNING	Unable to open the file.	"%s"
APPFW_RESP	APPFW_XML_ERR_INVALID_STATE	WARNING	AppFw XML Internal State Invalid.	"%s"
APPFW_RESP	APPFW_XML_ERR_INVALID_XPATH	WARNING	Invalid XPath.	"%s"
APPFW_RESP	APPFW_XML_ERR_LOW_MEMORY	WARNING	AppFw XML Low memory.	"%s"
APPFW_RESP	APPFW_XML_ERR_CHARDATA_LIMIT_EXCEEDED	WARNING	AppFw XML character data size exceeds the limit of 30MB	"%s"
APPFW_RESP	APPFW_XML_ERR_MALFORMED_ADDRESS	WARNING	Malformed address	"%s"
APPFW_RESP	APPFW_XML_ERR_NO_DIME	WARNING	NS-XML APPFW supports SwA and MTOM SOAP attachments, but attachment with this message is DIME.	"%s"
APPFW_RESP	APPFW_XML_ERR_OPERATI	WARNING	Problems registering	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	ON_CALLBACK		callbacks for operations.	
APPFW_RESP	APPFW_XML_ERR_PREFIX_LENGTH_EXCEEDED	WARNING	Prefix length %d exceeded, encountered length is %d.	"%s"
APPFW_RESP	APPFW_XML_ERR_READ_FAILED	WARNING	AppFw XML Read Failure	"%s"
APPFW_RESP	APPFW_XML_ERR_STREAM_POP	WARNING	Problems during pop of the node out of the XML stream.	"%s"
APPFW_RESP	APPFW_XML_ERR_STREAM_PUSH	WARNING	Problems during push of the node into the XML stream.	"%s"
APPFW_RESP	APPFW_XML_ERR_UNSUPPORTED_PORT	WARNING	Port in address %s is greater than 65535.	"%s"
APPFW_RESP	APPFW_XML_ERR_UNSUPPORTED_PROTOCOL	WARNING	Unsupported protocol	"%s"
APPFW_RESP	APPFW_XML_ERR_VALIDATION_FAILED	WARNING	AppFw XML Validation Failed	"%s"
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ER	WARNING	AppFw XML Context is NULL.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	R_CONTEXT_NULL			
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_STATE_NULL	WARNING	Context user state is NULL; internal error.	"%s"
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ERR_MESSAGE_CONFIG_NULL	WARNING	Message config struct is NULL.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ABSTRACT_ELEMENT	WARNING	Cannot instantiate abstract element	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ABSTRACT_TYPE	WARNING	Cannot instantiate abstract type '%s', for element '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ADDHEADERS	WARNING	Additional soap header %s present in soap message.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MAX_OCCURS	WARNING	Attribute '%s' appears more than once in element '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ATTRIBUT	WARNING	Required attribute missing in element	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	E_MIN_OCCURS			
APPFW_RESP	APPFW_XML_VALIDATION_ERR_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CONTENT_MODEL_VIOLATED	WARNING	Content model of element '%s' not satisfied.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CORRUPT_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CORRUPT_SCHEMA	WARNING	Error compiling the schema	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_DATATYPE_ENGINE_INIT	WARNING	Initialization of the datatype engine failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INTERNAL	WARNING	Internal corruption of WSDL in-memory structure.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_ATTRIBUTE	WARNING	Attribute '%s' is invalid.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_COMBINATION	WARNING	Invalid configuration for soap validation.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_COMPILED_WSDL	WARNING	Not able to open compiled WSDL.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_CONTENT_MODEL	WARNING	Element '%s' has invalid content model.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_DATATYPE	WARNING	Data type is invalid.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_ELEMENT	WARNING	Invalid element.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_FILE	WARNING	Not able to open the file.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_TYPE_SUBSTITUTION	WARNING	Did not get expected type for element '%s', got '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_LOADING	WARNING	Unable to load validation engine.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATION_ERR_MAX	WARNING	AppFw XML Validation Max Error.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_NOSERVICEURL	WARNING	Service Url is not present or NULL.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_NOT_SUPPORTED	WARNING	Feature not supported.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_BODY	WARNING	Soap Body structure check failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_ENVELOPE	WARNING	Soap Envelope structure check failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_HEADER	WARNING	Soap Header structure check failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_UNBOUNDED_PREFIX	WARNING	Prefix '%s' is unbounded.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_LOAD_ERR_CONTENTS_CANNOT_BE_NIL	WARNING	Element '%s' cannot be nil.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATION_LOAD_ERR_NIL_WITH_CONTENTS	WARNING	Element '%s' is nil, cannot have contents.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_REX_STACK_OVERFLOW	WARNING	Level of recursion more than maximum allowed depth.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_REX_STACK_EMPTY	WARNING	Trying to pop from an empty stack.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAPBODY_EMPTY	WARNING	Both SOAP Body and SOAP Header are empty in the SOAP request.	"%s"
APPFW_RESP	APPFW_XML_GENERIC_ERR_EMPTYBODY_REQ	WARNING	Request body is empty in the XML request.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_DATATYPE_VALUE	WARNING	Value should be of type '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_LOCATION	WARNING	Element '%s' cannot appears at this location.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_FACET_MISMATCH	WARNING	Facet mismatch.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_FAILED	WARNING	AppFw XML Validator Load Failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_ATTRIBUTE_VALUE	WARNING	Attribute '%s' has invalid value '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_DATATYPE	WARNING	Invalid schema datatype.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_SCHEMA_NODE_TYPE	WARNING	Invalid schema node type.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_VALUE_FOR_FIXED	WARNING	Value '%s' does not match FIXED constraint '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_GT_MAX	WARNING	List length is greater than max allowed.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_INVALID	WARNING	List length is invalid.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_LT_MIN	WARNING	List length is lesser than min allowed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_MAX	WARNING	AppFw XML Validation Maximum Load Error.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_REQUIRED_ATTRIBUTE	WARNING	Missing require attribute '%s' in element '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_SCHEMA_COMPILATION	WARNING	Error code in the compiled Schema is being ignored.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_WSDL_COMPILATION	WARNING	Error code in the compiled WSDL is being ignored.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ACCELEMENTNAMESPACED	WARNING	R2735: A MESSAGE described with an rpc-literal binding MUST place the part	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			accessor elements for parameters and return value in no namespace. Element '%s' must be unqualified.	
APPFW_RESP	APPFW_XML_WSI_ERR_ARRAYTYPE	WARNING	R2113: A MESSAGE containing serialized arrays MUST NOT include the soapenc:arrayType attribute. Element '%s' must not include the soapenc:arrayType attribute.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_BAD_ENV_NAMESPACE	WARNING	R1015: A RECEIVER MUST generate a fault if they encounter a message whose document element has a local name of "Envelope" but a namespace name that is not "http://schemas.xmlsoap.org/soap/envelope/" or	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			"http://www.w3.org/2003/05/soap-envelope". We got namespace '%s' in SOAP Request.	
APPFW_RESP	APPFW_XML_WSI_ERR_BINDINGFAULTRESP	WARNING	R2740: The response envelope contained soap:Fault element(s), but they were not defined in the WSDL description. Element '%s' should be defined as soap:fault in WSDL description.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_BODY_CHILD_NAMESPACE	WARNING	R1014: The children of the soap:Body element in a MESSAGE MUST be namespace qualified. Unqualified children of soap:Body is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_BO	WARNING	BP1201: The envelope does not use SOAP	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	DY_ENV_NAMESPACE		1.1 or SOAP 1.2, i.e. does not have a document element named "Envelope" or a namespace value of http://schemas.xmlsoap.org/soap/envelope/ or http://www.w3.org/2003/05/soap-envelope. We got namespace '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_CHILDAFTERBODY	WARNING	R1011: A MESSAGE MUST NOT have any element children of soap:Envelope following the soap:Body element. Element '%s' should not appear after 'soap:Body' element.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_CLAIM_MUSTUNDERSTAND	WARNING	R0007: A SENDER MUST NOT use the soap:mustUnderstand attribute when sending a	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			SOAP header block containing a conformance claim. soap:mustUnderstand attribute is present on element '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_CTXT_NULL	WARNING	AppFw XML WSI Internal Context NULL	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_DOCTYPEALLOWED	WARNING	R1008: A MESSAGE MUST NOT contain a Document Type Declaration. DOCTYPE name is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_DOT_NOTATION	WARNING	R1031: When a MESSAGE contains a faultcode element the content of that element SHOULD NOT use of the SOAP 1.1 "dot" notation to refine the meaning of the Fault. Data '%s' should not contain 'DOT'(.) in it.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLE	WARNING	R1005: A MESSAGE MUST NOT contain soap:encodingStyle attribute on any of the elements whose namespace is the same as the namespace of the qualified document element 'Envelope'. 'soap:encodingStyle' attribute should not be present on element '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLECHILD	WARNING	R1006: A MESSAGE MUST NOT contain soap:encodingStyle attributes on any element that is a child of soap:Body. 'soap:encodingStyle' attribute should not be present on immidiate child '%s' of soap:Body.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLEGRANDCHILD	WARNING	R1007: A MESSAGE described in an rpc-literal binding MUST NOT contain soap:encodingStyle attribute on any elements are grandchildren of soap:Body. 'soap:encodingStyle' attribute should not be present on grandchild '%s' of soap:Body.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ENVELEMENTSNOATTRIBUTES	WARNING	R1032: The soap:Envelope, soap:Header, and soap:Body elements in an ENVELOPE MUST NOT have attributes in the same namespace as that of the qualified document element 'Envelope'. Attribute '%s' should not be in the same namespace as that of the qualified document	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			element 'Envelope'.	
APPFW_RESP	APPFW_XML_WSI_ERR_ENVNONAMESPACE	WARNING	R1033: An ENVELOPE SHOULD NOT contain the namespace declaration xmlns:xml="http://www.w3.org/XML/1998/namespace".	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_GOODRESPONSE200	WARNING	R1111: An INSTANCE SHOULD use a "200 OK" HTTP status code for responses that contain a SOAP message that is not a SOAP fault. We should not get 'soap:Fault' element when HTTP response code is '200 OK'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_HEADER_HAS_WSICLAIM	WARNING	R0005: A MESSAGE's conformance claims MUST be carried as SOAP header blocks. Element '%s' should be immidiate	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			children of soap:Header.	
APPFW_RESP	APPFW_XML_WSI_ERR_HTTP	WARNING	AppFw XML WSI HTTP Error	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ISHTTPPOST	WARNING	R1132: A HTTP request MESSAGE MUST use the HTTP POST method. We got '%s' HTTP method.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ISUTF8OR16	WARNING	R1012: A MESSAGE MUST be serialized as either UTF-8 or UTF-16. We got encoding '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_MSGHASALLHEADERS	WARNING	R2738: A MESSAGE MUST include all soapbind:headers specified on a wsdl:input or wsdl:output of a wsdl:operation of a wsdl:binding that describes it.Wsdl header %s is not present in soap message.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_MUSTUNDERSTAND	WARNING	R1013: A MESSAGE containing a soap:mustUnderstand attribute MUST only use the lexical forms "0" and "1". Value of 'soap:mustUnderstand' attribute is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NODEPLOYED	WARNING	Resource id of deployment is NULL.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NOENVELOPEWSDLMATCH	WARNING	BP1701: The envelope does not conform to the SOAP schema located at 'http://schemas.xmlsoap.org/soap/envelope/' or 'http://www.w3.org/2003/05/soap-envelope'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NONPOSTREQUEST	WARNING	R1114: An INSTANCE SHOULD use a "405 Method not Allowed" HTTP status code if the request method was not "POST". We got	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			'%d' HTTP status code.	
APPFW_RESP	APPFW_XML_WSI_ERR_NONXMLREQUEST	WARNING	R1115: An INSTANCE SHOULD use a "415 Unsupported Media Type" HTTP status code if a HTTP request message's Content-Type header field-value is not permitted by its WSDL description. we got '%d' HTTP status code.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NOPORTURL	WARNING	Port URL is NULL.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NOREQWSDLMATCH	WARNING	BP1011: The content of the request envelope does not match the wsdl:message definition.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NORESPWSDLMATCH	WARNING	BP1013 The content of the response envelope does not match the wsdl:message definition.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_NOWSDLDEPLOYED	WARNING	Deployed resource is not WSDL.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ONEWAYRESPONSE	WARNING	R2714: For one-way operations, an INSTANCE MUST NOT return a HTTP response that contains a SOAP envelope. Specifically, the HTTP response entity-body must be empty. we got the element soap:Envelope.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_RESPONSESTATUS200OR202	WARNING	R1112: An INSTANCE SHOULD use either a "200 OK" or "202 Accepted" HTTP status code for a response that does do not contain a SOAP message but indicates successful HTTP outcome of a request. We got '%d'	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			HTTP response code.	
APPFW_RESP	APPFW_XML_WSI_ERR_RESPONSEWRAPPED	WARNING	R2729: A MESSAGE described with an rpc-literal binding that is a response message MUST have a wrapper element whose name is the corresponding wsdl:operation name suffixed with the string "Response". Element name should be '%sResponse' but got '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPACTIONHEADERMATCH	WARNING	R2744: A HTTP request MESSAGE MUST contain a SOAPAction HTTP header field with a quoted value equal to the value of the soapAction attribute of soapbind:operation, if present in the corresponding WSDL description.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			Expected '%s' soapAction but got '%s' soapAction in HTTP header.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPACTIONQUOTED	WARNING	R1109: The value of the SOAPAction HTTP header field in a HTTP request MESSAGE MUST be a quoted string. We got '%s' SOAPAction HTTP header.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTALLOWEDCHILD	WARNING	R1000: When a MESSAGE contains a soap:Fault element, that element MUST NOT have element children other than faultcode, faultstring, faultactor and detail. Element '%s' is not a allowed child of 'soap:Fault'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTCHILDQ	WARNING	R1001: When a MESSAGE contains a soap:Fault element its	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			element children MUST be unqualified. 'soap:Fault' child '%s' should be unqualified.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTINHTTP	WARNING	R1126: An INSTANCE MUST use a "500 Internal Server Error" HTTP status code if the response message is a SOAP Fault. We got '%s' HTTP response code.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTNONENV	WARNING	R1003: A RECEIVER MUST accept fault messages that have any number of qualified or unqualified attributes, including zero, appearing on the detail element. The namespace of qualified attributes can be anything other than the namespace of	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			the qualified document element 'Envelope'. Namespace of attribute '%s' should not be the same as that of the qualified document element 'Envelope'.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPGOODXML10	WARNING	BP1601: The soap:Envelope or soap:Body does not conform to XML 1.0. Error is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_STDFAULTCODE	WARNING	R1004: When a MESSAGE contains a faultcode element the content of that element SHOULD be one of the fault codes defined in SOAP 1.1 or a namespace qualified fault code. 'faultcode' '%s' is not defined in SOAP 1.1 or it is not	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			namespace qualified.	
APPFW_RESP	APPFW_XML_WSI_ERR_USEHTTP10OR11	WARNING	R1141: A MESSAGE MUST be sent using either HTTP/1.1 or HTTP/1.0. We got HTTP version '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_USEHTTP11	WARNING	R1140: A MESSAGE SHOULD be sent using HTTP/1.1. We got HTTP version '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_WSICLAIMSWELLFORMED	WARNING	R0004: A MESSAGE MAY contain conformance claims, as specified in the conformance claim schema. Either 'conformsTo' attribute is absent or 'soap:mustUnderstand' attribute is present on element '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_WSI_LIST_NULL	WARNING	AppFw XML WSI List Null.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_XMLPI	WARNING	R1009: A MESSAGE MUST NOT contain Processing Instructions. Name of Processing Instruction is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_XSINIL	WARNING	R2211: A MESSAGE described with an rpc-literal binding MUST NOT have the xsi:nil attribute with a value of "1" or "true" on the part accessors. Element '%s' must not have the xsi:nil attribute.	"%s"
APPFW_RESP	APPFW_XML_XSD_COMPILE_INIT_ERR	WARNING	Error during initialization	"%s"
APPFW_RESP	APPFW_XML_XSD_COMPILE_LOADXSD_ERR	WARNING	AppFw XML XSDLOAD Failed during Compile	"%s"
APPFW_RESP	APPFW_XML_XSD_COMPILE_NOMODEL_ERR	WARNING	No XSModel to print	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_XSD_COMPILE_PARSE_ERR	INFO	Error during parsing	"%s"
APPFW_RESP	APPFW_XML_XSD_COMPILE_UNEXPECTED_ERR	WARNING	Unexpected exception during parsing	"%s"
APPFW_RESP	APPFW_XML_ERR_SOAP_FAULT	WARNING	Message contains SOAP Fault.	"%s"
APPFW_RESP	APPFW_XML_SOAP_FAULT_CONTENTS	WARNING	Dumps the SOAP Fault contents to Audit log.	"%s"
APPFW_RESP	AF_INVALID_HTTP_HEADER	WARNING	Error while parsing HTTP headers.	"Errorwhileparsingheaders.");
APPFW_RESP	APPFW_CCARD_MATCH_IN_SIGNATURES	INFO	Credit card violation in signatures	"%s"
AAATM	LOGIN	INFO	Login to AAA TM vserver succeeds	"User%s-Client_ip%s-""Nat_ip%s-Vserver%s:%d-Browser_type\"%s\"-Group(s)\"%s\""
AAATM	LOGOUT	INFO	AAA TM session logged out	"User%s-""Client_ip%s-Nat_ip%s-""Vserver%s:%d-""Start_time\"%s\"-End_time\"%s\"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
				-Duration%s-"" Http_resources _accessed%s-" "Total_TCP_co nnections%d-"" Total_policies_a llowed%d- Total_policies_d enied%d-""Total _bytes_send%s - Total_bytes_rec v%s-""Total_co mpressedbytes _send%s- Total_compress edbytes_recv% s-""Compressio n_ratio_send% d.%02u% %-""Compressi on_ratio_recv% d.%02u% %-""LogoutMet hod\"%s\"- Group(s)\"%s\""
AAATM	HTTPREQUES T	DEBUG	A AAA TM session receives a HTTP request	"%sUser%s:Gr oup(s) %s:Vserver%s: %d- %s:SSOis%s: %s%s%s"
AAATM	HTTP_RESOU RCEACCESS_ DENIED	NOTICE	A http resource access is denied by policy engine. The denied policy name is	"- Denied_by_poli cy\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			captured in the log message.	
NSIP6	IPV6_DUPLICATED	INFO	IPv6 address got duplicated.	"%s"
ICA	SESSION_SETUP	DEBUG	ICA session setup	"session_guid%s-device_serial_number%u-client_cookie:%s-""flags%llu-session_setup_time%s-client_ip%s-client_type%d-""client_launcher%d-client_version%s-client_hostname%s-""domain_name%s-server_name%s-connection_priority%u-""access_type%d-status%d-username%s"
ICA	CHANNEL_UPDATE	DEBUG	ICA channel update	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-channel_update_begin%s-channel_update_end%s-""chan

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
				nel_id_1%d-channel_id_1_val%d-channel_id_2%d-channel_id_2_val%d-""channel_id_3%d-channel_id_3_val%d-channel_id_4%d-channel_id_4_val%d-""channel_id_5%d-channel_id_5_val%d"
ICA	SESSION_UPDATE	DEBUG	ICA session update	"session_guid%s-device_serial_number%u-""client_cookie%s-flags%llu-""nsica_session_status%d-""nsica_session_client_ip%s-""nsica_session_client_port%d-""nsica_session_server_ip%s-""nsica_session_server_port%d-""nsica_session_reconnect_count%d-""nsica_session_acr_count%d-""connection_priority%u-""timestamp%s-"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ICA	L7_LATENCY_UPDATE	DEBUG	ICA L7 latency update	"session_guid%s-device_serial_number%u-""client_cookie%s-flags%llu-""nsica_status%d-""L7LatencyThresholdFactor%d-""L7LatencyWaittime%d-""L7LatencyNotifyInterval%d-""L7LatencyMaxNotifyCount%d-""L7ThresholdBreachAvgClientsideLatency%d-""L7ThresholdBreachMaxClientsideLatency%d-""L7ThresholdBreachAvgServersideLatency%d-""L7ThresholdBreachMaxServersideLatency%d-""MinL7Latency%d-"
ICA	SESSION_TERMINATE	DEBUG	ICA session terminate	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-session_end_time%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ICA	NETWORK_UPDATE	DEBUG	ICA network update	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-ica_rtt%u-clientside_rxbytes%u-""clientside_txbytes%u-clientside_packet_retransmits%u-""serverside_packet_retransmits%u-clientside_rtt%u-serverside_rtt%u-""clientside_jitter%u-serverside_jitter%u"
ICA	APPLICATION_LAUNCH	DEBUG	ICA application launch	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-startup_duration%u-launch_mechanism%u-""app_launch_time%s-app_process_id%u-""app_name%s-module_path%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ICA	APPLICATION_TERMINATE	DEBUG	ICA application terminate	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-app_termination_type%d-app_process_id%u-""app_termination_time%s"
RDP	RDP_EVENT	DEBUG	RDP event	"UserName:%s
RDP	RDP_CONNECTION_EVENT	DEBUG	RDP connection event	"UserName:%s
CLI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""
GUI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""
API	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""
CONSOLE	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
BOT	BOT_WHITELIST	INFO	Bot whitelist	"Allowwhitelist.URL: %.*sLogMsg: %.*s"
BOT	BOT_BLACKLIST	INFO	Bot blacklist	"Disallowblacklist.URL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_IPREP	INFO	Bot iprep	"DisallowmaliciousIP.Category: %.*sURL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_DEVICE_FINGERPRINT	INFO	Bot Device FingerPrint	"DeviceFingerPrintvalidationfailed.URL: %.*s<%s>"
BOT	BOT_RATE_LIMIT	INFO	Bot Rate Limit	"ConnectionRateLimithit.URL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_STATIC_SIGNATURE	INFO	Bot static signature log.	"Botsignaturematched.User-Agent: %s(%u)Type: %sURL: %.*s<%s>"
BOT	BOT_SIG_AUTO_UPDATE	INFO	Bot signature auto update log.	"BotNewSignatureAvailable.NewlyaddedRules: %uDeletedRules:%u\n"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
BOT	BOT_TRAP_URL	INFO	Bot Trap URL.	"TrapURLSession.URL: %.*s<%s>"
BOT	BOT_CAPTCHA	INFO	Bot Captcha	"Captchamaxattempts(%u)exceeded.URL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_TPS	INFO	Bot TPS.	"TPSIPlimithitforIP:%sURL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_LOGEXPRESSION	INFO	Bot Log Expression.	"%s%u-PPE%u%s%s%.*s%.*s"
ROUTING	PAL	VARIABLE		
PITBOSS	PITBOSS	INFO	Pitboss watch is added on a process with the process id pid	Adding pitboss watch on (%d)
PITBOSS	PITBOSS	INFO	Pitboss watch is deleted on a process with the process id pid	Deleting watch on (%d)
PITBOSS	PB_SYSTEM_RESTART	ALERT	Process with pid has reached maximum number of restarts.Therefore the systemis being restarted	proc (%d) (%s) has had its maximum number of restarts (%d), rebooting the system

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
PITBOSS	PB_PROCESS_RESTART	ALERT	Process with pid is being restarted.The message indicates the number of times the process has been restarted	Restarting process old pid (%d) action (%s)
ROUTING	ROUTE_ADVERTISED	INFO	Route Advertised	ROUTE (%s %s %s) - ADVERTISED
ROUTING	ROUTE_WITHDRAWN	INFO	Route Withdrawn	ROUTE (%s %s %s) - WITHDRAWN
ROUTING	ROUTE_RELEARN		Route Relearnt	RELEARN (0x%x)
ROUTING	ROUTE_HASTATE	INFO	HA state change	HASTATE (0x%x)
CVPN	CVPN_INPUT_URL	DEBUG	The input URL before rewriting	HTML_URL %s
CVPN	CVPN_REWRITTEN_URL	DEBUG	The rewritten url	REWRITTEN_URL %.*s
CVPN	CVPN_PCRE_ERROR	DEBUG	PCRE Error	Regex %.*s : PCRE_ERROR %d
CVPN	CVPN_MATCHED_URL	DEBUG	The matched url	MATCHED_URL %.*s

ADC 13.0 Syslog Message Reference

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
TCP	CONN_DELINK	INFO	When a server side and a client side TCP connection is delinked.These are the connections which are being tracked by netscaler like HTTP	"Source%s:%d-Vserver%s:%d-NatIP%s:%d-""Destination%s:%d-DelinkTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu"
TCP	CONN_TERMINATE	INFO	When a TCP connection terminates.The logged data indicates the number of bytes transmitted and received over the connection and lso the connection start and end time	"Source%s:%d-Destination%s:%d-""StartTime%s-EndTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu"
TCP	OTHERCONN_DELINK	INFO	When a server side and a client side TCP connection is delinked.These are the connections which are not	"Source%s:%d-Vserver%s:%d-NatIP%s:%d-""Destination%s:%d-DelinkTime%s""Total_bytes_send%u-

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			being tracked by netscaler like FTP,telnet etc	Total_bytes_recv%u"
TCP	NAT_CONN_DELINK	INFO	When a server side and a client side TCP connection for RNAT are delinked we need to log the connection information	"Source%s:%d-Destination%s:%d-NatIP%s:%d-""Destination%s:%d-StartTime%s-DelinkTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu-ClosureReason%s"
TCP	NAT_OTHERCONN_DELINK	INFO	When a server side and a client side TCP connection for RNAT are delinked we need to log the connection information	"Source%s:%d-Destination%s:%d-NatIP%s:%d-""Destination%s:%d-StartTime%s-DelinkTime%s-Total_bytes_send%llu-""Total_bytes_recv%llu-ClosureReason%s"
ACL	ACL_PKT_LOG	INFO	ACL Packet Log	"Source%s-->Destination%s-""ProtocolICMP-""Type%d-Code%d-""TimeStamp%d(ms)-Hitcount%d-HitRule%s-Action%s-Data"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ACL	ACL6_PKT_LOG	INFO	ACL6 Packet Log	"Source%s-->Destination%s-""ProtocolICMP-""Type%d-Code%d-""TimeStamp%d(ms)-Hitcount%d-HitRule%s-Action%s-Data"
LSN	LSN_SESSION	INFO	Info of LSN session created	"S%s%s C-%s:%d:%d N-%s:%d D-%s:%d:%d %s"
LSN	LSN_EIM_MAPPING	INFO	Info of LSN Endpoint independent mapping created	"EIM%s%s C-%s:%d:%d N-%s:%d %s"
LSN	LSN_ADDR_MAPPING	INFO	Info of LSN Address dependent mapping created	"ADM%s%s C-%s:%d:%d N-%s:%d D-%s:%d %s"
LSN	LSN_ADDRPORT_MAPPING	INFO	Info of LSN Address and Port dependent mapping created	"A&PDM%s%s C-%s:%d:%d N-%s:%d D-%s:%d:%d %s"
LSN	PPTP_LOG	INFO	Info of PPTP connection	"CALLREQUEST");break;
LSN	LSN_PORTBLOCK	INFO	Info of LSN Portblock mappings	"PB%s%s C-%s N-%s:%d-%d %s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
LSN	LSN_DETERMINISTIC	INFO	Info of LSN Portblock mappings	"DTR%s%s C-%s N-%s:%d-%d"
ALG	ALG_SIP_PARSE_PACKET_EVENT	ERROR	Error of SIP packet parsing	maxprintsize)
ALG	ALG_SDP_PARSE_PACKET_EVENT	ERROR	Error of SDP packet parsing	"Errmsg: \"%s\"-""Group: %s-""Call_ID: %s-""Transport: %s-""Source_IP: %s-""Source_port: %u-""Destination_IP: %s-""Destination_port: %u-""Natted_IP: %s-""Natted_port:%u-""Method: %s-""Sequence_Number: %u-""Register: %s-""Content_Type:%s-""Error: \"%s\"-""Error_line: \"%s\"-""Caller_user_name: %s-""Callee_user_name: %s-""Caller_domain_name: %s-""Callee_domain_name: %s-"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ALG	ALG_SIP_ERROR_PACKET_EVENT	ERROR	Error of SIP protocol	maxprintsize)
ALG	ALG_DHT_ERROR_PACKET_EVENT	ERROR	Error of SIP ALG DHT	"Errmsg: \"ErrorinDHTHandlingforSIPrequest\"-""Group: %s-""Call_ID: %s-""Transport: %s-""Source_IP: %s-""Source_port: %u-""Destination_IP: %s-""Destination_port: %u-""Natted_IP: %s-""Natted_port:%u-""Method: %s-""Sequence_Number: %u-""Register: %s-""Content_Type: %s-""Caller_user_name: %s-""Callee_user_name: %s-""Caller_domain_name: %s-""Callee_domain_name: %s"
ALG	ALG_SIP_GENERATE_ERRO	ERROR	Error of SIP generate	"Errmsg: \"SIPALGgenetateerror\"-""Error_Code:

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	R_PACKET_EVENT			%u-""Group: %s"
ALG	ALG_SIP_INFO_PACKET_EVENT	INFO	Info of SIP packet	"Infomsg: \"SIPrequest\"-" "Group: %s-""Call_ID: %s-""Transport: %s-""Source_IP: %s-""Source_port: %u-""Destination_IP: %s-""Destination_port: %u-""Natted_IP: %s-""Natted_port:%u-""Method: %s-""Sequence_Number: %u-""Register: %s-""Content_Type: %s-""Caller_user_name: %s-""Callee_user_name: %s-""Caller_domain_name: %s-""Callee_domain_name: %s-"
ALG	ALG_SIP_INFO_DELETE_CALL_PACKET_EVENT	INFO	Info of SIP call deletion	maxprintsize)

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ALG	ALG_RTSP_INFO_PACKET_EVENT	INFO	Info of RTSP packet	maxprintsize)
ALG	ALG_RTSP_INFO_DELETE_CALL_PACKET_EVENT	INFO	Info of RTSP call deletion	"Infomsg: \"LoginfoRTSPALGcalldeletion\"-""Group: %s-""Session_ID:%s-"
ALG	ALG_RTSP_PARSE_PACKET_EVENT	ERROR	Error of RTSP packet parsing	maxprintsize)
ALG	ALG_RTSP_ALG_PACKET_EVENT	ERROR	Error of RTSP ALG	maxprintsize)
ALG	ALG_RTSP_DHT_PACKET_EVENT	ERROR	Error of RTSP DHT	maxprintsize)
DNS	DNS_QUERY	INFO	Information of DNS queries recieved by the DNS endpoints on NetScaler	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
DNS	DNS_RESPONSE	INFO	Information of DNS responses served by the DNS endpoints on NetScaler to clients	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
DNS	DNS_ERROR	INFO	Information of errors	"Source%s:%d-Destination%s:

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			encountered during DNS packet processing on NetScaler	%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
SUBSCRIBER	SESSION_EVENT	INFO	Subscriber Session Event Info	"Session%s
SUBSCRIBER	SESSION_FAILURE	ERROR	Subscriber Session Failure Info	"FailureReason:%s
SSLI	INTERCEPT_LOG	INFO	SSL Interception Success Log	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
SSLI	BYPASS_LOG	INFO	SSL Interception Bypass Log	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
SSLI	DROPPED_LOG	INFO	SSL Interception Dropped Log	"Source%s:%d-Destination%s:%d""User:%s-Domain:%s-Category:%d""Action:%s-Reason:%s"
URLFILT	URLFILT_LOG	INFO	URL filtering Log	"Source%s-Destination%s""URL%s-""Category%s-

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
				Categorygroup %s- Reputation%d-" "Policyaction%s "
CI	ICAP_LOG	INFO	ICAP transaction Log.	"Source%s: %d-""Destination%s: %d-""Domain%s-""Content-Type%s-""ICAP Server%s: %d-""Mode%s-" "Service%s-""Response%d-""Action%s"
CI	ICAPC_LOG	INFO	ICAP custom log.	"%s"
CI	INLINE_INSPECTION_LOG	INFO	Inline Inspection transaction Log.	"ID%lld-""Source%s: %d-""Destination%s: %d-""Protocol%s-""URL%s-""Domain%s-""Service%s-""%s%s-""Action%s-""BytesSent%lld-""BytesReceived%lld-""OriginServer%s:%d"
CI	TRAFFIC_MIRROR_LOG	INFO	Traffic Mirror transaction Log.	"ID%lld-""Source%s: %d-""Destination%s: %d-""Protocol%s-""URL%s-""D

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
				omain%s-""Service%s-""%s%s-""Action%s-""RequestBytesSent%lld-""ResponseBytesSent%lld-""OriginServer%s:%d"
AAA	LOGIN_FAILED	WARNING	When the aaa module failed to login the user.The reason for failure is indicated in the message	"User%s-Client_ip%s-Failure_reason\"%s\"-Browser%s"
AAA	EXTRACTED_GROUPS	INFO	After a user logs in the group for the user has been extracted	"Extracted_groups\"%s\""
UI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""
SSLVPN	LOGIN	INFO	SSLVPN login succeeds	"User%s-Client_ip%s-""Nat_ip%s-Vserver%s:%d-Browser_type\"%s\"-SSLVPN_client_type%s-Group(s)\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
SSLVPN	LOGOUT	INFO	SSLVPN session logs out.Logout method is captured in the message	"User%s-""Client_ip%s-Nat_ip%s-""Vserver%s:%d-""Start_time\"%s\"-End_time\"%s\"-Duration%s-""Http_resources_accessed%s-NonHttp_services_accessed%s-""Total_TCP_connections%d-Total_UDP_flows%d-""Total_policies_allowed%d-Total_policies_denied%d-""Total_bytes_send%s-Total_bytes_recv%s-""Total_compressedbytes_send%s-Total_compressedbytes_recv%s-""Compression_ratio_send%d.%02u%%-""Compression_ratio_recv%d.%02u%%-""LogoutMethod\"%s\"-Group(s)\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
SSLVPN	ICASTART	INFO	ICA application launch has started	"Source%s:%d-Destination%s:%d-""SSLRelayAddress%s:%d-""customername%s-""username:domainname%s-""applicationName%s-startTime\"%s\"-""connectionId%x"
SSLVPN	ICAEND_CONNSTAT	INFO	ICA application has terminated	"Source%s:%d-Destination%s:%d-""SSLRelayAddress%s:%d-""customername%s-""username:domainname%s-""startTime\"%s\"-endTime\"%s\"-""Duration%s-Total_bytes_send%u-Total_bytes_recv%u-""Total_compressedbytes_send%u-Total_compressedbytes_recv%u-""Compression_ratio_send%d.%02u%%-Compression_ratio_recv%d.%02u%%-""connectionId%x"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
SSLVPN	TCPCONNSTAT	INFO	Logs the TCP connection related information for a connection belonging to a SSLVPN session	"User%s-Client_ip%s-Nat_ip%s-Vserver%s:%d-""Source%s:%d-Destination%s:%d-Start_time\"%s\"-End_time\"%s\"-""Duration%s-Total_bytes_send%d-Total_bytes_recv%d-""Total_compressedbytes_send%d-Total_compressedbytes_recv%d-""Compression_ratio_send%d.%02u%%-Compression_ratio_recv%d.%02u%%-Access%s-Group(s)\"%s\""
SSLVPN	TCPCONN_TIMEDOUT	INFO	An SSLVPN connection timed out.The information about the connection start and end time the amount of data transferred and received are present in	"User%s-Client_ip%s-""Nat_ip%s-Vserver%s:%d-Last_contact\"%s\"-Group(s)\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			the message date	
SSLVPN	UDPFLOWSTAT	INFO	When a UDP flow , within a SSLVPN session, terminates	"User%s-Client_ip%s-""Nat_ip%s-Vserver%s:%d-Source%s:%d-""Destination%s:%d-Start_time\"%s\"-End_time\"%s\"-""Duration%s-Total_bytes_send%d-""Total_bytes_recv%d-Access%s-Group(s)\"%s\""
SSLVPN	HTTPREQUEST	INFO	A SSLVPN session receives a HTTP request	"%sUser%s:Group(s) %s:Vserver%s:%d-%s:SSOis%s:%s%s%s"
SSLVPN	NONHTTP_RESOURCEACCESS_DENIED	NOTICE	A non-http resource access is denied by policy engine. The denied policy name is captured in the log message.	"-Denied_by_policy\"%s\""
SSLVPN	HTTP_RESOURCEACCESS_DENIED	NOTICE	A http resource access is denied by policy engine.	"-Denied_by_policy\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			The denied policy name is captured in the log message.	
SSLVPN	LICLMT_REACHED	INFO	SSLVPN license limit reached	"Vserver%s:%d-License_limit%d"
SSLVPN	CLISEC_CHECK	ERROR	Logs with severity ERROR when client security check for a SSLVPN session fails, otherwise logs with severity DEBUG	"%s:%s-ClientIP%s-Vserver%s:%d-Client_security_expression\"%s\"-"
SSLVPN	CLISEC_EXP_EVAL	ERROR	Logs with severity ERROR when client security expression evaluates to False, otherwise logs with severity DEBUG	"User%s:-ClientIP%s-Vserver%s:%d-""Clientsecuritycheck%s%s(%d)ontheclient machine"
SSLVPN	STA_VALIDATE_RESP	INFO	After a user logs into SSLVPN and the group for the user has been extracted	"Xdatalen%d-Xdata%s"
SSLVPN	REMOVE_SESSION_DEBUG	DEBUG	Gives debug information of session before	"Sessionid%u-""User%s-""Client_ip%s-

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			removing session intentionally	Nat_ip%s-""Vserver_ip%s-""Errmsg\"%s\""
EVENT	ALERTSTARTED	ALERT	When SNMP module starts an alarm (usually when the value of a monitored attribute crosses the threshold value	"%s"
EVENT	ALERTENDED	ALERT	When SNMP module stops an alarm (usually when the value of a monitored attribute returns to normal state)	"%s"
EVENT	STARTSYS	INFO	When NetScaler starts	"%s"
EVENT	STARTCPU	INFO	When a particular CPU starts	"%s"
EVENT	DEVICEDOWN	NOTICE	Whenever a device is down	"%s"
EVENT	DEVICEOFS	NOTICE	Whenever a device is out of service	"%s"
EVENT	DEVICEUP	NOTICE	Whenever a device is up	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	NICSTART	NOTICE	When the network interface is started	"%s"
EVENT	NICSTOP	NOTICE	When the network interface is stopped	"%s"
EVENT	NICHANG	NOTICE	When the network interface is in hung state	"%s"
EVENT	NICRESET	NOTICE	When the network interface is reset	"%s"
EVENT	NICMIGRATE	NOTICE	When an interface is bound or unbound from a channel	"%s"
EVENT	STOPSYS	INFO	When the NetScaler system is stopped	"%s"
EVENT	FREEBADMEM	EMERGENCY	When bad memory is freed (internal error)	"%s"
EVENT	FREEDUPMEM	EMERGENCY	When duplicate memory free occurs (internal error)	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	FREEEXTMEM	EMERGENCY	When memory is freed from a wrong pool (internal error)	"%s"
EVENT	PROPSUCCESS	INFO	When HA propagation is successful	"%s"
EVENT	PROPFAIL	ALERT	When HA propagation fails	"%s"
EVENT	STATECHANGE	0	HA State has changed.The string along with the message gives more information	"%s"
EVENT	CLSTATECHANGE	0	Cluster State has changed.The string along with the message gives more information	"%s"
EVENT	CACHESTARTFLUSH	INFO	When cache flush starts	"%s"
EVENT	CACHESTOPFLUSH	INFO	When cache flush is complete	"%s"
EVENT	MONITORTH	INFO	The monitor bound to the service has hit threshold limit	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	MONITORDOWN	INFO	The monitor bound to the service is down.	"%s"
EVENT	MONITORUP	INFO	The monitor bound to the service is up.	"%s"
EVENT	ROUTEDOWN	INFO	When the route is down	"%s"
EVENT	ROUTEUP	INFO	When the route is up	"%s"
EVENT	VRID6DOWN	INFO	When the vrid changes state to backup	"%s"
EVENT	VRIDDOWN	INFO	When the vrid changes state to backup	"%s"
EVENT	VRIDUP	INFO	When the vrid changes state to master	"%s"
EVENT	VRIDINIT	INFO	When the vrid changes state to init	"%s"
EVENT	VIPRHIUP	INFO	When the rhi state of vip changes to up	"%s"
EVENT	VIPRHIDOWN	INFO	When the rhi state of vip changes to down	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	STARTSAVECONFIG	INFO	When save configuration started	"%s"
EVENT	STOPSAVECONFIG	INFO	When save configuration has stopped	"%s"
EVENT	CONFIGSTART	INFO	When NetScaler starts to read the configuration from ns.conf file (during boot-up)	"%s"
EVENT	CONFIGEND	INFO	When NetScaler has completed reading the configuration from ns.conf file (during boot-up)	"%s"
EVENT	NICLACPSC	NOTICE		"%s"
EVENT	NICLOW_THROUGHPUT	NOTICE	When an interface's throughput is less than the min required	"%s"
EVENT	NICNORMAL_THROUGHPUT	NOTICE	When an interface's throughput is equal or greater than the min required	"%s"
EVENT	NICPOWERON	NOTICE	When an interface is powered on	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	NICPOWEROFF	NOTICE	When an interface is powered off	"%s"
EVENT	DHCPSVRERR	INFO	When the DHCP server sends an invalid setting	"%s"
EVENT	DHCPCAQUIRE	INFO	When the DHCP client aquires a lease	"%s"
EVENT	DHCPCRELEASE	INFO	When the DHCP client releases a lease	"%s"
EVENT	DHCPCDEPENDPBR	INFO	When the DHCP lease is released and a PBR is dependent on the lease ip	"%s"
EVENT	ROUTE6DOWN	INFO	When the route6 is down	"%s"
EVENT	ROUTE6UP	INFO	When the route6 is up	"%s"
EVENT	MEPDOWN	NOTICE	Mep is down.	"%s"
EVENT	MEPUP	NOTICE	Mep is up.	"%s"
EVENT	BACKUPMEPDOWN	NOTICE	Backup Mep is down.	"%s"
EVENT	BACKUPMEPUP	NOTICE	Backup Mep is up.	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
EVENT	NWMEPDOWN	NOTICE	Network metric Mep is down.	"%s"
EVENT	NWMEPUP	NOTICE	Network metric Mep is up.	"%s"
EVENT	BACKUPMEP6 DOWN	NOTICE	Backup ipv6 Mep is down.	"%s"
EVENT	BACKUPMEP6 UP	NOTICE	Backup ipv6 Mep is up.	"%s"
EVENT	UNKNOWN	DEBUG		"%s"
SSLLOG	SSL_HANDSH AKE_FAILURE	DEBUG	SSL HandShake Failure	"BackendSPCB Id%d-ServerIP%s-ServerPort%d-"\"ProtocolVersion%s-CipherSuite\"%s\"-"\"Session%s"
SSLLOG	SSL_HANDSH AKE_SUCCES S	DEBUG	SSL HandShake Success	"BackendSPCB Id%d-ServerIP%s-ServerPort%d-"\"ProtocolVersion%s-CipherSuite\"%s\"-"\"Session%s"
SSLLOG	SSL_CERT_EX PIRY_IMMINE NT	NOTICE	SSL Certificate Expiry Imminent	"CertificateKey Pair%s-DaysToExpire%u"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
SSLLOG	SSL_HANDSHAKE_ISSUERNAME	DEBUG	SSL Client Certificate IssueName	"SPCBId%d-IssuerName\"%s\""
SSLLOG	SSL_HANDSHAKE_SUBJECTNAME	DEBUG	SSL Client Certificate SubjectName	"SPCBId%d-SubjectName\"%s\""
SSLLOG	SSL_CRL_UPDATE_SUCCESS	NOTICE	SSL CRL Update Success	"crl_name%s-server_ip%s-server_port%d-"\"methodLDAP-ldapscope%s-"
SSLLOG	SSL_CRL_UPDATE_FAILURE	NOTICE	SSL CRL Update Failure	"crl_name%s-server_ip%s-server_port%d-"\"methodLDAP-ldapscope%s-"
SSLLOG	SSL_OCSPURL_RESOLVE_SUCCESS	DEBUG	SSL OCSPURL Resolve Success	"Domainname%sIpaddress%s"
SSLLOG	SSL_OCSPURL_RESOLVE_FAILURE	DEBUG	SSL OCSPURL Resolve Failure	"Domainname%sIpaddress%s"
SSLLOG	SSL_OCSPRESPONSE_SUCCESS	DEBUG	SSL OCSPResponse Success	"%02x"
SSLLOG	SSL_OCSPRESPONSE_FAILURE	DEBUG	SSL OCSPResponse Failure	"%02x"
APPFW	APPFW_STARTURL	INFO	AppFw StartURL violation	"DisallowIllegalURL.");}else{

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_MULTIPLE_HEADER	INFO	AppFw Multiple Header violation	"Multipleheadersinrequest");}
APPFW	APPFW_XMLPAYLOAD_CONTENT_TYPE_MISMATCH	INFO	AppFw Infer Content-Type Payload violation	"XMLMismatchedcontent-typeinHTTPheaderdetected=\"%s\"."
APPFW	APPFW_LOGEXPRESSION	INFO	AppFw Log Expression details	"%.*s"
APPFW	APPFW_DENYURL	INFO	AppFw DenyURL violation	"DisallowDenyURLforrulepattern=\"%s\"."
APPFW	APPFW_CONTENT_TYPE	INFO	AppFw Content-type violation	"Unknowncontent-typeheadervalue=\"%s\"."
APPFW	APPFW_REFERER_HEADER	INFO	AppFw Referer header violation	"parsingrefererheader'%s'failed"
APPFW	APPFW_CSRF_TAG	INFO	AppFw CSRF tag violation	"CSRFTagvalidationfailed");}
APPFW	APPFW_XSS	INFO	AppFw XSS violation	"%s"
APPFW	APPFW_XML_XSS	WARNING	AppFw XSS violation in XML	"%s"
APPFW	APPFW_SQL	INFO	AppFw SQL Injection violation	"%s"
APPFW	APPFW_SQL_GRAM	INFO	AppFw SQL Injection violation	"%sGrammar-basedSQLidete

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			reported by SQL Grammar	ctedfor%s%s=\" %s\""
APPFW	APPFW_XML_SQL	WARNING	AppFw SQL Injection violation in XML	"%s"
APPFW	APPFW_CMD	INFO	AppFw CMD Injection violation	"%s"
APPFW	APPFW_COOKIE	INFO	AppFw Cookie Consistency violation	"%s"
APPFW	APPFW_FIELDCONSISTENCY	INFO	AppFw Field Consistency violation	"%s"
APPFW	APPFW_FILE_UPLOAD_TYPE	INFO	AppFw File Upload Type violation	"%s"
APPFW	APPFW_BUFFEROVERFLOW_URL	INFO	AppFw Buffer Overflow violation in URL	"URLlength(%d)isgreaterthanmaximumallowed(%d)."
APPFW	APPFW_BUFFEROVERFLOW_COOKIE	INFO	AppFw Buffer Overflow violation in Cookie	"Cookieheaderlength(%d)isgreaterthanmaximumallowed(%d)."
APPFW	APPFW_BUFFEROVERFLOW_HDR	INFO	AppFw Buffer Overflow violation in HTTP Headers	"Header(%s)length(%d)isgreaterthanmaximumallowed(%d)."
APPFW	APPFW_BUFFEROVERFLOW_QUERY	INFO	AppFw Buffer Overflow	"Querystringlength(%d)isgreate

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			violation in Query string	rthanmaximum allowed(%d)."
APPFW	APPFW_BUFFEROVERFLOW_TOTAL_HDR	INFO	AppFw Buffer Overflow violation in total HTTP header length	"TotalHTTPheaderlength(%d)isgreaterthanmaximumallowed(%d)."
APPFW	APPFW_FIELDFORMAT	INFO	AppFw Field Format violation	"%s"
APPFW	APPFW_SAFECOMMERCE	INFO	AppFw Safe Commerce violation	"%s"
APPFW	APPFW_SAFECOMMERCE_XFORM	INFO	AppFw Safe Commerce violation detected and transformed	"%s"
APPFW	APPFW_SAFEOBJECT	INFO	AppFw Safe Object violation	"%s"
APPFW	APPFW_POLICY_HIT	INFO	AppFw profile invoked	"%s%u-PPE%u%s%s%s<%s>"
APPFW	APPFW_POLICY_HIT_BUILTIN	INFO	AppFw built-in profile invoked	"%s"
APPFW	APPFW_MAX_UPLOADS	INFO	File uploads exceed the allowed number	"%s"
APPFW	APPFW_SIGNATURE_MATCH	INFO	AppFw signature violation	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	AF_BIND_TO_PROFILE	INFO	AppFw rule bound to HTML profile	"Profile:%s
APPFW	AF_BIND_XML_TO_PROFILE	INFO	AppFw rule bound to XML profile	"Profile:%s
APPFW	AF_ADD_FIELDTYPE	INFO	Add an AppFw Field Type	"FieldType:%s
APPFW	AF_ADD_PROFILE	INFO	Add an AppFw profile	"Profile:%s\n"
APPFW	AF_RM_FIELDTYPE	INFO	Remove an Appfw Field Type	"FieldType:%s
APPFW	AF_RM_PROFILE	INFO	Remove an AppFw profile	"Profile:%s\n"
APPFW	AF_ADD_CFFIELD	INFO	Add a confidential field	"FieldName:%s
APPFW	AF_RM_CFFIELD	INFO	Remove a confidential field	"FieldName:%s
APPFW	AF_400_RESP	INFO	AppFw Request error. Generated 400 Response	"%s"
APPFW	AF_5XX_RESP	INFO	Server Error. Generated 5XX Response	"%s"
APPFW	AF_RESPONSE_PARSE_ERR	INFO	Response parse error	"Badresponsecacheheader"');

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	AF_MEMORY_ERR	WARNING	Memory allocation request for %lu bytes failed	"Contentlengthistoolarge(%lluBytes).MemoryAllocationfailed."
APPFW	AF_ORIGIN_SERVER_RESP_MISMATCH_ERR	WARNING	Origin server sent a response but AppFw needed something different	"Partial(range)requestsenttobackendserverincorrectly");
APPFW	AF_MALFORMED_REQ_ERR	INFO	Malformed request	"Malformedmulti-partrequest-connectionreset");break;
APPFW	AF_UTHREAD_STACK_ERR	ERROR	Appsecure uthread at 0x%x had a stack error	"Uthreadstackpointeroverflowed:");
APPFW	AF_SIGNATURE_ERR	INFO	Signature error	"Signatureid%ucontainsnofastmatchpattern"
APPFW	AF_STREAM_MSG_ERR	WARNING	Stream message error	"Lookupofprofilename'");
APPFW	AF_GENERIC_ERR_WITH_URL	WARNING	Generic error with URL	"Internalerror:additionaldatageneratedafterpartialresponsefor'");
APPFW	APPFW_XML_ATTACHMENT_FOUND	WARNING	Attachment Found in the XML Message.	"%s"
APPFW	APPFW_XML_ATTACHMENT	WARNING	XML Attachment	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	_ERR_CALLBACK_NULL		CallBack is NULL but HTTP message is MIME Attachment message.	
APPFW	APPFW_XML_ATTACHMENT_ERR_INVALID HEADER	WARNING	String %s is supposed to be MIME Header. But it is not according to the format of Mime Header HeaderName:HeaderValue	"%s"
APPFW	APPFW_XML_ATTACHMENT_ERR_INVALID_HEADER	WARNING	HTTP Content type should be 'application/xop+xml' or '\^(text	application)/([a-zA-Z]*\+xml xml)' but we got %s. "%s"
APPFW	APPFW_XML_ATTACHMENT_ERR_BOUNDARY_MISMATCH	WARNING	Boundary mismatch in mime message.	"%s"
APPFW	APPFW_XML_ERR_NO_ATTACHMENT_BOUNDARY	WARNING	The message having content-type as 'Multipart/Related' and not having a boundary is invalid.	"%s"
APPFW	APPFW_XML_ATTACHMENT	WARNING	XML Message has an Attachment with size greater	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	_ERR_MAX_SIZE		than the Configured Max Attachment Size.	
APPFW	APPFW_XML_ATTACHMENT_ERR_CONTENT_TYPE	WARNING	XML Message has an Attachment with Illegal Content-Type	"%s"
APPFW	APPFW_XML_DDOS_ERR_MSG_SEND_FAIL	WARNING	AppFw XML DDoS Send Fail Error.	"%s"
APPFW	APPFW_XML_DOS_ERR_CHAR_DATA_LENGTH	WARNING	Exceeds max character data length.	"%s"
APPFW	APPFW_XML_DOS_ERR_DTD	WARNING	DTD present in the XML message.	"%s"
APPFW	APPFW_XML_DOS_ERR_EXT_ENTITY	WARNING	External entities present in the XML message.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX	WARNING	AppFw XML DoS Maximum Error	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTES	WARNING	Element '%s' exceeds maximum attributes per element.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE	WARNING	In element '%s' an attribute exceeds	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	_NAME_LENGTH		maximum name length.	
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_VALUE_LENGTH	WARNING	In element '%s' attribute '%s' exceeds maximum attribute value length.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENTS	WARNING	Element '%s' exceeds maximum elements per message.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_CHILDREN	WARNING	Parent of element '%s' exceeds maximum children at element '%s'.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_DEPTH	WARNING	Element '%s' exceeds maximum element depth.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_NAME_LENGTH	WARNING	Element '%s' exceeds maximum element name length.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_FILE_SIZE	WARNING	Message size exceeds max size.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_NODES	WARNING	Node '%s' exceeds maximum	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			nodes per message.	
APPFW	APPFW_XML_DOS_ERR_MIN_FILE_SIZE	WARNING	Message size less than min size.	"%s"
APPFW	APPFW_XML_ERR_NOT_WELLFORMED	WARNING	Message is not a well-formed XML.	"%s"
APPFW	APPFW_XML_DOS_ERR_PI	WARNING	Processing instructions present in the XML message.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_NAMESPACES	WARNING	Element '%s' exceeds maximum active namespaces.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_NAMESPACEURI_LENGTH	WARNING	In element '%s' a namespace exceeds maximum uri length.	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSION_DEPTH	WARNING	Exceeds max entity expansion depth	"%s"
APPFW	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSIONS	WARNING	Exceeds max number of entity expansions	"%s"
APPFW	APPFW_XML_DOS_ERR_MA	WARNING	Exceeds max total SOAP array size	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	X_SOAPARRAY_SIZE			
APPFW	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_RANK	WARNING	Exceeds max SOAP array rank	"%s"
APPFW	APPFW_XML_ERR_CUSTOM	WARNING	AppFw XML internal error	"%s"
APPFW	APPFW_XML_ERR_DDOS_CONNECT_TO_SERVER_FAILED	WARNING	AppFw XML DDoS Connect to Server Failed.	"%s"
APPFW	APPFW_XML_ERR_DDOS_INTERATION_SOCKET_OPEN_FAIL	WARNING	AppFw XML DDoS Interaction socket open Failed.	"%s"
APPFW	APPFW_XML_ERR_DDOS_INVALID_CONFIG_FILE	WARNING	AppFw XML DDoS Invalid Config File.	"%s"
APPFW	APPFW_XML_ERR_DDOS_NO_FOLDER_INSTALLATION_PATH	WARNING	AppFw XML DDoS No Folder Installation Path.	"%s"
APPFW	APPFW_XML_ERR_DDOS_OPEN_CONFIG_FILE_FAIL	WARNING	AppFw XML DDoS Failure to Open Config File.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_ERR_DOS_TRIGGERED	WARNING	Denial of Service Error.	"%s"
APPFW	APPFW_XML_ERR_ENV_NOT_SET	WARNING	Environment variable QTHOME not set.	"%s"
APPFW	APPFW_XML_ERR_HASH_INSERT	WARNING	Problems inserting a namespace into the hash table.	"%s"
APPFW	APPFW_XML_ERR_HASH_LOOKUP	WARNING	Problems getting the key of a namespace from the hash table.	"%s"
APPFW	APPFW_XML_ERR_INITIALIZING_TOKENIZER	WARNING	Unable to initialize XML tokenizer.	"%s"
APPFW	APPFW_XML_ERR_INVALID_FILE	WARNING	Unable to open the file.	"%s"
APPFW	APPFW_XML_ERR_INVALID_STATE	WARNING	AppFw XML Internal State Invalid.	"%s"
APPFW	APPFW_XML_ERR_INVALID_XPATH	WARNING	Invalid XPath.	"%s"
APPFW	APPFW_XML_ERR_LOW_MEMORY	WARNING	AppFw XML Low memory.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_ERR_CHARDATA_LIMIT_EXCEEDED	WARNING	AppFw XML character data size exceeds the limit of 30MB	"%s"
APPFW	APPFW_XML_ERR_MALFORMED_ADDRESS	WARNING	Malformed address	"%s"
APPFW	APPFW_XML_ERR_NO_DIME	WARNING	NS-XML APPFW supports SwA and MTOM SOAP attachments, but attachment with this message is DIME.	"%s"
APPFW	APPFW_XML_ERR_OPERATION_CALLBACK	WARNING	Problems registering callbacks for operations.	"%s"
APPFW	APPFW_XML_ERR_PREFIX_LENGTH_EXCEEDED	WARNING	Prefix length %d exceeded, encountered length is %d.	"%s"
APPFW	APPFW_XML_ERR_READ_FAILED	WARNING	AppFw XML Read Failure	"%s"
APPFW	APPFW_XML_ERR_STREAM_POP	WARNING	Problems during pop of the node out of the XML stream.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_ERR_STREAM_PUSH	WARNING	Problems during push of the node into the XML stream.	"%s"
APPFW	APPFW_XML_ERR_UNSUPPORTED_PORT	WARNING	Port in address %s is greater than 65535.	"%s"
APPFW	APPFW_XML_ERR_UNSUPPORTED_PROTOCOL	WARNING	Unsupported protocol	"%s"
APPFW	APPFW_XML_ERR_VALIDATION_FAILED	WARNING	AppFw XML Validation Failed	"%s"
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_NULL	WARNING	AppFw XML Context is NULL.	"%s"
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_STATE_NULL	WARNING	Context user state is NULL; internal error.	"%s"
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_MESSAGE_CONFIG_NULL	WARNING	Message config struct is NULL.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_ABSTRACT_ELEMENT	WARNING	Cannot instantiate abstract element	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_VALIDATION_ERR_ABSTRACT_TYPE	WARNING	Cannot instantiate abstract type '%s', for element '%s'.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_ADDHEADERS	WARNING	Additional soap header %s present in soap message.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MAX_OCCURS	WARNING	Attribute '%s' appears more than once in element '%s'.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MIN_OCCURS	WARNING	Required attribute missing in element	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_CONTENT_MODEL_VIOLATED	WARNING	Content model of element '%s' not satisfied.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_CORRUPT_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_VALIDATION_ERR_CORRUPT_SCHEMA	WARNING	Error compiling the schema	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_DATATYPE_ENGINE_INIT	WARNING	Initialization of the datatype engine failed.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INTERNAL	WARNING	Internal corruption of WSDL in-memory structure.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_ATTRIBUTE	WARNING	Attribute '%s' is invalid.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_COMBINATION	WARNING	Invalid configuration for soap validation.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_COMPILED_WSDL	WARNING	Not able to open compiled WSDL.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_CONTENT_MODEL	WARNING	Element '%s' has invalid content model.	"%s"
APPFW	APPFW_XML_VALIDATION_E	WARNING	Data type is invalid.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	RR_INVALID_DATATYPE			
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_ELEMENT	WARNING	Invalid element.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_FILE	WARNING	Not able to open the file.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_TYPE_SUBSTITUTION	WARNING	Did not get expected type for element '%s', got '%s'.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_LOADING	WARNING	Unable to load validation engine.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_MAX	WARNING	AppFw XML Validation Max Error.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_NOSERVICEURL	WARNING	Service Url is not present or NULL.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_NOT_SUPPORTED	WARNING	Feature not supported.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_BODY	WARNING	Soap Body structure check failed.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_ENVELOPE	WARNING	Soap Envelope structure check failed.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_HEADER	WARNING	Soap Header structure check failed.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_UNBOUNDED_PREFIX	WARNING	Prefix '%s' is unbounded.	"%s"
APPFW	APPFW_XML_VALIDATION_LOAD_ERR_CONTENTS_CANNOT_BE_NIL	WARNING	Element '%s' cannot be nil.	"%s"
APPFW	APPFW_XML_VALIDATION_LOAD_ERR_NIL_WITH_CONTENTS	WARNING	Element '%s' is nil, cannot have contents.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_REX_STACK_OVERFLOW	WARNING	Level of recursion more than maximum allowed depth.	"%s"
APPFW	APPFW_XML_VALIDATION_ERR_REX_STACK_EMPTY	WARNING	Trying to pop from an empty stack.	"%s"
APPFW	APPFW_XML_VALIDATION_E	WARNING	Both SOAP Body and SOAP Header	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	RR_SOAPBODY_EMPTY		are empty in the SOAP request.	
APPFW	APPFW_XML_GENERIC_ERR_EMPTYBODY_REQ	WARNING	Request body is empty in the XML request.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_DATATYPE_VALUE	WARNING	Value should be of type '%s'.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_LOCATION	WARNING	Element '%s' cannot appears at this location.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_FACET_MISMATCH	WARNING	Facet mismatch.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_FAILED	WARNING	AppFw XML Validator Load Failed.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_ATTRIBUTE_VALUE	WARNING	Attribute '%s' has invalid value '%s'.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INV	WARNING	Invalid schema datatype.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	ALID_DATATYPE			
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_SCHEMA_NODE_TYPE	WARNING	Invalid schema node type.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_VALUE_FOR_FIXED	WARNING	Value '%s' does not match FIXED constraint '%s'.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_GT_MAX	WARNING	List length is greater than max allowed.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_INVALID	WARNING	List length is invalid.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_LT_MIN	WARNING	List length is lesser than min allowed.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_MAX	WARNING	AppFw XML Validation Maximum Load Error.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_RE	WARNING	Missing require attribute '%s' in element '%s'.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	QUIRED_ATTRIBUTE			
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_SCHEMA_COMPILATION	WARNING	Error code in the compiled Schema is being ignored.	"%s"
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_WSDL_COMPILATION	WARNING	Error code in the compiled WSDL is being ignored.	"%s"
APPFW	APPFW_XML_WSI_ERR_ACCELEMENTNAMESPACED	WARNING	R2735: A MESSAGE described with an rpc-literal binding MUST place the part accessor elements for parameters and return value in no namespace. Element '%s' must be unqualified.	"%s"
APPFW	APPFW_XML_WSI_ERR_ARRAYTYPE	WARNING	R2113: A MESSAGE containing serialized arrays MUST NOT include the soapenc:arrayType attribute. Element '%s' must not	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			include the soapenc:arrayType attribute.	
APPFW	APPFW_XML_WSI_ERR_BAD_ENV_NAMESPACE	WARNING	R1015: A RECEIVER MUST generate a fault if they encounter a message whose document element has a local name of "Envelope" but a namespace name that is not "http://schemas.xmlsoap.org/soap/envelope/" or "http://www.w3.org/2003/05/soap-envelope". We got namespace '%s' in SOAP Request.	"%s"
APPFW	APPFW_XML_WSI_ERR_BINDINGFAULTRESP	WARNING	R2740: The response envelope contained soap:Fault element(s), but they were not defined in the WSDL description. Element '%s' should be	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			defined as soap:fault in WSDL description.	
APPFW	APPFW_XML_WSI_ERR_BODY_CHILD_NAMESPACE	WARNING	R1014: The children of the soap:Body element in a MESSAGE MUST be namespace qualified. Unqualified children of soap:Body is '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_BODY_ENV_NAMESPACE	WARNING	BP1201: The envelope does not use SOAP 1.1 or SOAP 1.2, i.e. does not have a document element named "Envelope" or a namespace value of http://schemas.xmlsoap.org/soap/envelope/ or http://www.w3.org/2003/05/soap-envelope. We got namespace '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_CHI	WARNING	R1011: A MESSAGE	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	LDAFTERBODY		MUST NOT have any element children of soap:Envelope following the soap:Body element. Element '%s' should not appear after 'soap:Body' element.	
APPFW	APPFW_XML_WSI_ERR_CLAIM_MUSTUNDERSTAND	WARNING	R0007: A SENDER MUST NOT use the soap:mustUnderstand attribute when sending a SOAP header block containing a conformance claim. soap:mustUnderstand attribute is present on element '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_CTXT_NULL	WARNING	AppFw XML WSI Internal Context NULL	"%s"
APPFW	APPFW_XML_WSI_ERR_DOCTYPEALLOWED	WARNING	R1008: A MESSAGE MUST NOT contain a Document Type Declaration.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			DOCTYPE name is '%s'.	
APPFW	APPFW_XML_WSI_ERR_DOT_NOTATION	WARNING	R1031: When a MESSAGE contains a faultcode element the content of that element SHOULD NOT use of the SOAP 1.1 "dot" notation to refine the meaning of the Fault. Data '%s' should not contain 'DOT'(.) in it.	"%s"
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLE	WARNING	R1005: A MESSAGE MUST NOT contain soap:encoding Style attribute on any of the elements whose namespace is the same as the namespace of the qualified document element 'Envelope'. 'soap:encoding Style' attribute should not be	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			present on element '%s'.	
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLECHILD	WARNING	R1006: A MESSAGE MUST NOT contain soap:encodingStyle attributes on any element that is a child of soap:Body. 'soap:encodingStyle' attribute should not be present on immidiate child '%s' of soap:Body.	"%s"
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLEGRANDCHILD	WARNING	R1007: A MESSAGE described in an rpc-literal binding MUST NOT contain soap:encodingStyle attribute on any elements are grandchildren of soap:Body. 'soap:encodingStyle' attribute should not be present on grandchild '%s' of soap:Body.	"%s"
APPFW	APPFW_XML_WSI_ERR_EN	WARNING	R1032: The soap:Envelope,	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	VELEMENTSNOATTRIBUTES		soap:Header, and soap:Body elements in an ENVELOPE MUST NOT have attributes in the same namespace as that of the qualified document element 'Envelope'. Attribute '%s' should not be in the same namespace as that of the qualified document element 'Envelope'.	
APPFW	APPFW_XML_WSI_ERR_ENVNONAMESPACE	WARNING	R1033: An ENVELOPE SHOULD NOT contain the namespace declaration xmlns:xml="http://www.w3.org/XML/1998/namespace".	"%s"
APPFW	APPFW_XML_WSI_ERR_GOODRESPONSE200	WARNING	R1111: An INSTANCE SHOULD use a "200 OK" HTTP status code for responses that contain a SOAP	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			message that is not a SOAP fault. We should not get 'soap:Fault' element when HTTP response code is '200 OK'.	
APPFW	APPFW_XML_WSI_ERR_HEADER_HAS_WSICLAIM	WARNING	R0005: A MESSAGE's conformance claims MUST be carried as SOAP header blocks. Element '%s' should be immidiate children of soap:Header.	"%s"
APPFW	APPFW_XML_WSI_ERR_HTTP	WARNING	AppFw XML WSI HTTP Error	"%s"
APPFW	APPFW_XML_WSI_ERR_ISHTTPPOST	WARNING	R1132: A HTTP request MESSAGE MUST use the HTTP POST method. We got '%s' HTTP method.	"%s"
APPFW	APPFW_XML_WSI_ERR_ISUTF8OR16	WARNING	R1012: A MESSAGE MUST be serialized as either UTF-8 or	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			UTF-16. We got encoding '%s'.	
APPFW	APPFW_XML_WSI_ERR_MSGHASALLHEADERS	WARNING	R2738: A MESSAGE MUST include all soapbind:headers specified on a wsdl:input or wsdl:output of a wsdl:operation of a wsdl:binding that describes it.Wsdl header %s is not present in soap message.	"%s"
APPFW	APPFW_XML_WSI_ERR_MUSTUNDERSTAND	WARNING	R1013: A MESSAGE containing a soap:mustUnderstand attribute MUST only use the lexical forms "0" and "1". Value of 'soap:mustUnderstand' attribute is '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_NODEPLOYED	WARNING	Resource id of deployment is NULL.	"%s"
APPFW	APPFW_XML_WSI_ERR_NOENVELOPEWSDLMATCH	WARNING	BP1701: The envelope does not conform to the SOAP	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			schema located at 'http://schemas.xmlsoap.org/soap/envelope/' or 'http://www.w3.org/2003/05/soap-envelope'.	
APPFW	APPFW_XML_WSI_ERR_NONPOSTREQUEST	WARNING	R1114: An INSTANCE SHOULD use a "405 Method not Allowed" HTTP status code if the request method was not "POST". We got '%d' HTTP status code.	"%s"
APPFW	APPFW_XML_WSI_ERR_NONXMLREQUEST	WARNING	R1115: An INSTANCE SHOULD use a "415 Unsupported Media Type" HTTP status code if a HTTP request message's Content-Type header field-value is not permitted by its WSDL description. we got '%d' HTTP status code.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_WSI_ERR_NO PORTURL	WARNING	Port URL is NULL.	"%s"
APPFW	APPFW_XML_WSI_ERR_NO REQWSDLMAT CH	WARNING	BP1011: The content of the request envelope does not match the wsdl:message definition.	"%s"
APPFW	APPFW_XML_WSI_ERR_NO RESPWSDLMA TCH	WARNING	BP1013 The content of the response envelope does not match the wsdl:message definition.	"%s"
APPFW	APPFW_XML_WSI_ERR_NO WSDLDEPLOY ED	WARNING	Deployed resource is not WSDL.	"%s"
APPFW	APPFW_XML_WSI_ERR_ON EWAYRESPON SE	WARNING	R2714: For one-way operations, an INSTANCE MUST NOT return a HTTP response that contains a SOAP envelope. Specifically, the HTTP response entity-body must be empty. we got the	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			element soap:Envelope.	
APPFW	APPFW_XML_WSI_ERR_RESPONSESTATUS200OR202	WARNING	R1112: An INSTANCE SHOULD use either a "200 OK" or "202 Accepted" HTTP status code for a response that does do not contain a SOAP message but indicates successful HTTP outcome of a request. We got '%d' HTTP response code.	"%s"
APPFW	APPFW_XML_WSI_ERR_RESPONSEWRAPPED	WARNING	R2729: A MESSAGE described with an rpc-literal binding that is a response message MUST have a wrapper element whose name is the corresponding wsdl:operation name suffixed with the string "Response". Element name should be	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			'%sResponse' but got '%s'.	
APPFW	APPFW_XML_WSI_ERR_SOAPACTIONHEADERMATCH	WARNING	R2744: A HTTP request MESSAGE MUST contain a SOAPAction HTTP header field with a quoted value equal to the value of the soapAction attribute of soapbind:operation, if present in the corresponding WSDL description. Expected '%s' soapAction but got '%s' soapAction in HTTP header.	"%s"
APPFW	APPFW_XML_WSI_ERR_SOAPACTIONQUOTED	WARNING	R1109: The value of the SOAPAction HTTP header field in a HTTP request MESSAGE MUST be a quoted string. We got '%s' SOAPAction HTTP header.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTALLOWEDCHILD	WARNING	R1000: When a MESSAGE contains a soap:Fault element, that element MUST NOT have element children other than faultcode, faultstring, faultactor and detail. Element '%s' is not a allowed child of 'soap:Fault'.	"%s"
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTCHILDQ	WARNING	R1001: When a MESSAGE contains a soap:Fault element its element children MUST be unqualified. 'soap:Fault' child '%s' should be unqualified.	"%s"
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTINHTTP	WARNING	R1126: An INSTANCE MUST use a "500 Internal Server Error" HTTP status code if the response message is a SOAP Fault. We got '%s'	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			HTTP response code.	
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTNONENV	WARNING	R1003: A RECEIVER MUST accept fault messages that have any number of qualified or unqualified attributes, including zero, appearing on the detail element. The namespace of qualified attributes can be anything other than the namespace of the qualified document element 'Envelope'. Namespace of attribute '%s' should not be the same as that of the qualified document element 'Envelope'.	"%s"
APPFW	APPFW_XML_WSI_ERR_SOAPGOODXML10	WARNING	BP1601: The soap:Envelope or soap:Body does not conform to XML	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			1.0. Error is '%s'.	
APPFW	APPFW_XML_WSI_ERR_STDFAULTCODE	WARNING	R1004: When a MESSAGE contains a faultcode element the content of that element SHOULD be one of the fault codes defined in SOAP 1.1 or a namespace qualified fault code. 'faultcode' '%s' is not defined in SOAP 1.1 or it is not namespace qualified.	"%s"
APPFW	APPFW_XML_WSI_ERR_USEHTTP10OR11	WARNING	R1141: A MESSAGE MUST be sent using either HTTP/1.1 or HTTP/1.0. We got HTTP version '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_USEHTTP11	WARNING	R1140: A MESSAGE SHOULD be sent using HTTP/1.1. We got HTTP version '%s'.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_XML_WSI_ERR_WSICLAIMSWELLFORMED	WARNING	R0004: A MESSAGE MAY contain conformance claims, as specified in the conformance claim schema. Either 'conformsTo' attribute is absent or 'soap:mustUnderstand' attribute is present on element '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_WSI_LIST_NULL	WARNING	AppFw XML WSI List Null.	"%s"
APPFW	APPFW_XML_WSI_ERR_XMLPI	WARNING	R1009: A MESSAGE MUST NOT contain Processing Instructions. Name of Processing Instruction is '%s'.	"%s"
APPFW	APPFW_XML_WSI_ERR_XSINIL	WARNING	R2211: A MESSAGE described with an rpc-literal binding MUST NOT have the xsi:nil attribute with a value of	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			"1" or "true" on the part accessors. Element '%s' must not have the xsi:nil attribute.	
APPFW	APPFW_XML_XSD_COMPILE_INIT_ERR	WARNING	Error during initialization	"%s"
APPFW	APPFW_XML_XSD_COMPILE_LOADXSD_ERR	WARNING	AppFw XML XSDLOAD Failed during Compile	"%s"
APPFW	APPFW_XML_XSD_COMPILE_NOMODEL_ERR	WARNING	No XSModel to print	"%s"
APPFW	APPFW_XML_XSD_COMPILE_PARSE_ERR	INFO	Error during parsing	"%s"
APPFW	APPFW_XML_XSD_COMPILE_UNEXPECTED_ERR	WARNING	Unexpected exception during parsing	"%s"
APPFW	APPFW_XML_ERR_SOAP_FAULT	WARNING	Message contains SOAP Fault.	"%s"
APPFW	APPFW_XML_SOAP_FAULT_CONTENTS	WARNING	Dumps the SOAP Fault contents to Audit log.	"%s"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	AF_INVALID_HTTP_HEADER	WARNING	Error while parsing HTTP headers.	"ErrorwhileparsingHTTPheaders.");
APPFW	APPFW_CCARD_MATCH_IN_SIGNATURES	INFO	Credit card violation in signatures	"%s"
APPFW	APPFW_SESSIONLIMIT	INFO	AppFw Session Limit reached	"AppfwmaximumsessionLimitreachedforPEID%d"
APPFW	AF_ADD_RFCPROFILE	INFO	Add an AppFw rfc profile	"APPFWRFCProfile:%s\n"
APPFW	AF_RM_RFCPROFILE	INFO	Remove an AppFw rfc profile	"APPFWRFCProfile:%s\n"
APPFW	APPFW_INV_RFC	INFO	RFC syntax violation. Generated 302 Response	"%s"
APPFW	APPFW_NEW_SIGNATURE_ADDED	INFO	AppFw New Signature Added	"Newsignatureavailable:RuleID=%d
APPFW	APPFW_JSON_DOS_MAX_DOCUMENT_LENGTH	INFO	AppFw JSON document length exceeded	"%s"
APPFW	APPFW_JSON_DOS_MAX_CONTAINER_DEPTH	INFO	AppFw JSON document exceeds maximum container depth	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW	APPFW_JSON_DOS_MAX_OBJECT_KEY_COUNT	INFO	AppFw JSON document has object that exceeds maximum key count	"%s"
APPFW	APPFW_JSON_DOS_MAX_OBJECT_KEY_LENGTH	INFO	AppFw JSON document has key in object that exceeds maximum key length	"%s"
APPFW	APPFW_JSON_DOS_MAX_ARRAY_LENGTH	INFO	AppFw JSON document has array exceeds maximum array length	"%s"
APPFW	APPFW_JSON_DOS_MAX_STRING_LENGTH	INFO	AppFw JSON document has string that exceeds maximum string length	"%s"
APPFW	APPFW_JSON_SQL	INFO	AppFw JSON document has sql violation	"%s"
APPFW	APPFW_JSON_XSS	INFO	AppFw JSON document has Cross-site script violation	"%s"
APPFW	APPFW_DEPLOY_RELAXATION_DP	INFO	AppFw relaxation about to be deployed through	"Learnedrulewill beauto-deployedafter%dmins.ViolType:%s.Profile:%s

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			Dynamic Learning	
APPFW	APPFW_COOKIE_HIJACK	INFO	AppFw Cookie Hijacking violation	"%s"
APPFW	APPFW_POSTBODYLIMIT	INFO	AppFw Post Body Limit violation	"%s"
APPFW	APPFW_JSON_CMD	INFO	AppFw JSON document has command injection violation	"%s"
APPFW	APPFW_JSON_SQL_GRAM	INFO	AppFw JSON document has SQL Injection violation reported by SQL Grammar	"%s"
ROUTING	ZEBOS_CMD_EXECUTED	INFO	The ZebOS command executed.	"%s"
SNMP	TRAP_SENT	INFO	Trap Sent Information	"%s"
SNMP	TRAP_DROPPED	INFO	Trap Dropped information. Traps are dropped due to rate-limiting	"%s"
TRANSFORM	FILE_REQUEST	DEBUG	URL Transformation profile invoked	"Client%s-Profile%s-%sinto%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
TRANSFORM	REQ_PARSE_ERROR	WARNING	URL Transformation parsing error	"Client%s-Profile%s-Failedtoparserequ estURL%stransformation-URL%s"
TRANSFORM	REQ_HEADER	DEBUG	URL Transformation in a request header	"Client%s-Profile%s-Header%s-%sinto%s"
TRANSFORM	RESP_HEADER	DEBUG	URL Transformation in a response header	"Client%s-Profile%s-Header%s-%sinto%s"
TRANSFORM	BODY_FRAG	DEBUG	URL Transformation in a response body	"Client%s-Profile%s-Type%s-%sinto%s"
TRANSFORM	ACTION_MATCH	DEBUG	URL Transformation action matched URL	"Client%s-Profile%s-Action%s-%sinto%s"
TRANSFORM	ACTION_MISMATCH	DEBUG	URL Transformation action didn't match URL	"Client%s-Profile%s-Action%s-Value%s"
TRANSFORM	PCRE_ERROR	WARNING	URL Transformation regex error	"Client%s-Profile%s-Action%s-PCREerrorcode%d"
TRANSFORM	REQ_WRITE_ERROR	WARNING	URL Transformation	"Client%s-Profile%s-

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			error in a request header	Failedtowrite%s requestheader"
APPFW_RESP	APPFW_XML_XSS	WARNING	AppFw XSS violation in XML	"%s"
APPFW_RESP	APPFW_XML_SQL	WARNING	AppFw SQL Injection violation in XML	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_FOUND	WARNING	Attachment Found in the XML Message.	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_CALLBACK_NULL	WARNING	XML Attachment CallBack is NULL but HTTP message is MIME Attachment message.	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_INVALID HEADER	WARNING	String %s is supposed to be MIME Header. But it is not according to the format of Mime Header HeaderName:HeaderValue	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_INVALID_HEADER	WARNING	HTTP Content type should be 'application/xop+xml' or '\^(text	application)/([a-zA-Z]*\+xml xml)' but we got %s. "%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_BOUND	WARNING	Boundary mismatch in mime message.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	ARY_MISMATCH			
APPFW_RESP	APPFW_XML_ERR_NO_ATTACHMENT_BOUNDARY	WARNING	The message having content-type as 'Multipart/ Related' and not having a boundary is invalid.	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_MAX_SIZE	WARNING	XML Message has an Attachment with size greater than the Configured Max Attachment Size.	"%s"
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_CONTENT_TYPE	WARNING	XML Message has an Attachment with Illegal Content-Type	"%s"
APPFW_RESP	APPFW_XML_DDOS_ERR_MSG_SEND_FAIL	WARNING	AppFw XML DDoS Send Fail Error.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_CHAR_DATA_LENGTH	WARNING	Exceeds max character data length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_DTD	WARNING	DTD present in the XML message.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_DOS_ERR_EXT_ENTITY	WARNING	External entities present in the XML message.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX	WARNING	AppFw XML DoS Maximum Error	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTES	WARNING	Element '%s' exceeds maximum attributes per element.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_NAME_LENGTH	WARNING	In element '%s' an attribute exceeds maximum name length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_VALUE_LENGTH	WARNING	In element '%s' attribute '%s' exceeds maximum attribute value length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENTS	WARNING	Element '%s' exceeds maximum elements per message.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_CHILDREN	WARNING	Parent of element '%s' exceeds maximum children at element '%s'.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_DEPTH	WARNING	Element '%s' exceeds maximum element depth.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_NAME_LENGTH	WARNING	Element '%s' exceeds maximum element name length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_FILE_SIZE	WARNING	Message size exceeds max size.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NODES	WARNING	Node '%s' exceeds maximum nodes per message.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MIN_FILE_SIZE	WARNING	Message size less than min size.	"%s"
APPFW_RESP	APPFW_XML_ERR_NOT_WELLFORMED	WARNING	Message is not a well-formed XML.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_PI	WARNING	Processing instructions present in the XML message.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NAMESPACES	WARNING	Element '%s' exceeds maximum active namespaces.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NAMESPACEURI_LENGTH	WARNING	In element '%s' a namespace exceeds maximum uri length.	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSION_DEPTH	WARNING	Exceeds max entity expansion depth	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSIONS	WARNING	Exceeds max number of entity expansions	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_SIZE	WARNING	Exceeds max total SOAP array size	"%s"
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_RANK	WARNING	Exceeds max SOAP array rank	"%s"
APPFW_RESP	APPFW_XML_ERR_CUSTOM	WARNING	AppFw XML internal error	"%s"
APPFW_RESP	APPFW_XML_ERR_DDOS_CONNECT_TO_SERVER_FAILED	WARNING	AppFw XML DDoS Connect to Server Failed.	"%s"
APPFW_RESP	APPFW_XML_ERR_DDOS_INTERATION_SOCKET_OPEN_FAIL	WARNING	AppFw XML DDoS Interaction socket open Failed.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_ERR_DDOS_INVALID_CONFIG_FILE	WARNING	AppFw XML DDoS Invalid Config File.	"%s"
APPFW_RESP	APPFW_XML_ERR_DDOS_NO_FOLDER_INSTALLATION_PATH	WARNING	AppFw XML DDoS No Folder Installation Path.	"%s"
APPFW_RESP	APPFW_XML_ERR_DDOS_OPEN_CONFIG_FILE_FAIL	WARNING	AppFw XML DDoS Failure to Open Config File.	"%s"
APPFW_RESP	APPFW_XML_ERR_DOS_TRIGGERED	WARNING	Denial of Service Error.	"%s"
APPFW_RESP	APPFW_XML_ERR_ENV_NOT_SET	WARNING	Environment variable QTHOME not set.	"%s"
APPFW_RESP	APPFW_XML_ERR_HASH_INSERT	WARNING	Problems inserting a namespace into the hash table.	"%s"
APPFW_RESP	APPFW_XML_ERR_HASH_LOOKUP	WARNING	Problems getting the key of a namespace from the hash table.	"%s"
APPFW_RESP	APPFW_XML_ERR_INITIALIZING_TOKENIZER	WARNING	Unable to initialize XML tokenizer.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_ERR_INVALID_FILE	WARNING	Unable to open the file.	"%s"
APPFW_RESP	APPFW_XML_ERR_INVALID_STATE	WARNING	AppFw XML Internal State Invalid.	"%s"
APPFW_RESP	APPFW_XML_ERR_INVALID_XPATH	WARNING	Invalid XPath.	"%s"
APPFW_RESP	APPFW_XML_ERR_LOW_MEMORY	WARNING	AppFw XML Low memory.	"%s"
APPFW_RESP	APPFW_XML_ERR_CHARDATA_LIMIT_EXCEEDED	WARNING	AppFw XML character data size exceeds the limit of 30MB	"%s"
APPFW_RESP	APPFW_XML_ERR_MALFORMED_ADDRESS	WARNING	Malformed address	"%s"
APPFW_RESP	APPFW_XML_ERR_NO_DIME	WARNING	NS-XML APPFW supports SwA and MTOM SOAP attachments, but attachment with this message is DIME.	"%s"
APPFW_RESP	APPFW_XML_ERR_OPERATI	WARNING	Problems registering	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	ON_CALLBACK		callbacks for operations.	
APPFW_RESP	APPFW_XML_ERR_PREFIX_LENGTH_EXCEEDED	WARNING	Prefix length %d exceeded, encountered length is %d.	"%s"
APPFW_RESP	APPFW_XML_ERR_READ_FAILED	WARNING	AppFw XML Read Failure	"%s"
APPFW_RESP	APPFW_XML_ERR_STREAM_POP	WARNING	Problems during pop of the node out of the XML stream.	"%s"
APPFW_RESP	APPFW_XML_ERR_STREAM_PUSH	WARNING	Problems during push of the node into the XML stream.	"%s"
APPFW_RESP	APPFW_XML_ERR_UNSUPPORTED_PORT	WARNING	Port in address %s is greater than 65535.	"%s"
APPFW_RESP	APPFW_XML_ERR_UNSUPPORTED_PROTOCOL	WARNING	Unsupported protocol	"%s"
APPFW_RESP	APPFW_XML_ERR_VALIDATION_FAILED	WARNING	AppFw XML Validation Failed	"%s"
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ER	WARNING	AppFw XML Context is NULL.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	R_CONTEXT_NULL			
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_STATE_NULL	WARNING	Context user state is NULL; internal error.	"%s"
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ERR_MESSAGE_CONFIG_NULL	WARNING	Message config struct is NULL.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ABSTRACT_ELEMENT	WARNING	Cannot instantiate abstract element	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ABSTRACT_TYPE	WARNING	Cannot instantiate abstract type '%s', for element '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ADDHEADERS	WARNING	Additional soap header %s present in soap message.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MAX_OCCURS	WARNING	Attribute '%s' appears more than once in element '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ATTRIBUT	WARNING	Required attribute missing in element	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	E_MIN_OCCURS			
APPFW_RESP	APPFW_XML_VALIDATION_ERR_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CONTENT_MODEL_VIOLATED	WARNING	Content model of element '%s' not satisfied.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CORRUPT_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CORRUPT_SCHEMA	WARNING	Error compiling the schema	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_DATATYPE_ENGINE_INIT	WARNING	Initialization of the datatype engine failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INTERNAL	WARNING	Internal corruption of WSDL in-memory structure.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_ATTRIBUTE	WARNING	Attribute '%s' is invalid.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_COMBINATION	WARNING	Invalid configuration for soap validation.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_COMPILED_WSDL	WARNING	Not able to open compiled WSDL.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_CONTENT_MODEL	WARNING	Element '%s' has invalid content model.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_DATATYPE	WARNING	Data type is invalid.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_ELEMENT	WARNING	Invalid element.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_FILE	WARNING	Not able to open the file.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_TYPE_SUBSTITUTION	WARNING	Did not get expected type for element '%s', got '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_LOADING	WARNING	Unable to load validation engine.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATION_ERR_MAX	WARNING	AppFw XML Validation Max Error.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_NOSERVICEURL	WARNING	Service Url is not present or NULL.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_NOT_SUPPORTED	WARNING	Feature not supported.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_BODY	WARNING	Soap Body structure check failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_ENVELOPE	WARNING	Soap Envelope structure check failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_HEADER	WARNING	Soap Header structure check failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_UNBOUNDED_PREFIX	WARNING	Prefix '%s' is unbounded.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_LOAD_ERR_CONTENTS_CANNOT_BE_NIL	WARNING	Element '%s' cannot be nil.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATION_LOAD_ERR_NIL_WITH_CONTENTS	WARNING	Element '%s' is nil, cannot have contents.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_REX_STACK_OVERFLOW	WARNING	Level of recursion more than maximum allowed depth.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_REX_STACK_EMPTY	WARNING	Trying to pop from an empty stack.	"%s"
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAPBODY_EMPTY	WARNING	Both SOAP Body and SOAP Header are empty in the SOAP request.	"%s"
APPFW_RESP	APPFW_XML_GENERIC_ERR_EMPTYBODY_REQ	WARNING	Request body is empty in the XML request.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_DATATYPE_VALUE	WARNING	Value should be of type '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_LOCATION	WARNING	Element '%s' cannot appears at this location.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_FACET_MISMATCH	WARNING	Facet mismatch.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_FAILED	WARNING	AppFw XML Validator Load Failed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_ATTRIBUTE_VALUE	WARNING	Attribute '%s' has invalid value '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_DATATYPE	WARNING	Invalid schema datatype.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_SCHEMA_NODE_TYPE	WARNING	Invalid schema node type.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_VALUE_FOR_FIXED	WARNING	Value '%s' does not match FIXED constraint '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_GT_MAX	WARNING	List length is greater than max allowed.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_INVALID	WARNING	List length is invalid.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_LT_MIN	WARNING	List length is lesser than min allowed.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_MAX	WARNING	AppFw XML Validation Maximum Load Error.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_REQUIRED_ATTRIBUTE	WARNING	Missing require attribute '%s' in element '%s'.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_SCHEMA_COMPILATION	WARNING	Error code in the compiled Schema is being ignored.	"%s"
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_WSDL_COMPILATION	WARNING	Error code in the compiled WSDL is being ignored.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ACCELEMENTNAMESPACED	WARNING	R2735: A MESSAGE described with an rpc-literal binding MUST place the part	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			accessor elements for parameters and return value in no namespace. Element '%s' must be unqualified.	
APPFW_RESP	APPFW_XML_WSI_ERR_ARRAYTYPE	WARNING	R2113: A MESSAGE containing serialized arrays MUST NOT include the soapenc:arrayType attribute. Element '%s' must not include the soapenc:arrayType attribute.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_BAD_ENV_NAMESPACE	WARNING	R1015: A RECEIVER MUST generate a fault if they encounter a message whose document element has a local name of "Envelope" but a namespace name that is not "http://schemas.xmlsoap.org/soap/envelope/" or	

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			"http://www.w3.org/2003/05/soap-envelope". We got namespace '%s' in SOAP Request.	
APPFW_RESP	APPFW_XML_WSI_ERR_BINDINGFAULTRESP	WARNING	R2740: The response envelope contained soap:Fault element(s), but they were not defined in the WSDL description. Element '%s' should be defined as soap:fault in WSDL description.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_BODY_CHILD_NAMESPACE	WARNING	R1014: The children of the soap:Body element in a MESSAGE MUST be namespace qualified. Unqualified children of soap:Body is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_BO	WARNING	BP1201: The envelope does not use SOAP	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
	DY_ENV_NAMESPACE		1.1 or SOAP 1.2, i.e. does not have a document element named "Envelope" or a namespace value of http://schemas.xmlsoap.org/soap/envelope/ or http://www.w3.org/2003/05/soap-envelope. We got namespace '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_CHILDAFTERBODY	WARNING	R1011: A MESSAGE MUST NOT have any element children of soap:Envelope following the soap:Body element. Element '%s' should not appear after 'soap:Body' element.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_CLAIM_MUSTUNDERSTAND	WARNING	R0007: A SENDER MUST NOT use the soap:mustUnderstand attribute when sending a	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			SOAP header block containing a conformance claim. soap:mustUnderstand attribute is present on element '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_CTXT_NULL	WARNING	AppFw XML WSI Internal Context NULL	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_DOCTYPEALLOWED	WARNING	R1008: A MESSAGE MUST NOT contain a Document Type Declaration. DOCTYPE name is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_DOT_NOTATION	WARNING	R1031: When a MESSAGE contains a faultcode element the content of that element SHOULD NOT use of the SOAP 1.1 "dot" notation to refine the meaning of the Fault. Data '%s' should not contain 'DOT'(.) in it.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLE	WARNING	R1005: A MESSAGE MUST NOT contain soap:encodingStyle attribute on any of the elements whose namespace is the same as the namespace of the qualified document element 'Envelope'. 'soap:encodingStyle' attribute should not be present on element '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLECHILD	WARNING	R1006: A MESSAGE MUST NOT contain soap:encodingStyle attributes on any element that is a child of soap:Body. 'soap:encodingStyle' attribute should not be present on immidiate child '%s' of soap:Body.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLEGRANDCHILD	WARNING	R1007: A MESSAGE described in an rpc-literal binding MUST NOT contain soap:encoding Style attribute on any elements are grandchildren of soap:Body. 'soap:encoding Style' attribute should not be present on grandchild '%s' of soap:Body.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ENVELEMENTSNOATTRIBUTES	WARNING	R1032: The soap:Envelope, soap:Header, and soap:Body elements in an ENVELOPE MUST NOT have attributes in the same namespace as that of the qualified document element 'Envelope'. Attribute '%s' should not be in the same namespace as that of the qualified document	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			element 'Envelope'.	
APPFW_RESP	APPFW_XML_WSI_ERR_ENVNONAMESPACE	WARNING	R1033: An ENVELOPE SHOULD NOT contain the namespace declaration xmlns:xml="http://www.w3.org/XML/1998/namespace".	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_GOODRESPONSE200	WARNING	R1111: An INSTANCE SHOULD use a "200 OK" HTTP status code for responses that contain a SOAP message that is not a SOAP fault. We should not get 'soap:Fault' element when HTTP response code is '200 OK'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_HEADER_HAS_WSICLAIM	WARNING	R0005: A MESSAGE's conformance claims MUST be carried as SOAP header blocks. Element '%s' should be immidiate	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			children of soap:Header.	
APPFW_RESP	APPFW_XML_WSI_ERR_HTTP	WARNING	AppFw XML WSI HTTP Error	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ISHTTPPOST	WARNING	R1132: A HTTP request MESSAGE MUST use the HTTP POST method. We got '%s' HTTP method.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ISUTF8OR16	WARNING	R1012: A MESSAGE MUST be serialized as either UTF-8 or UTF-16. We got encoding '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_MSGHASALLHEADERS	WARNING	R2738: A MESSAGE MUST include all soapbind:headers specified on a wsdl:input or wsdl:output of a wsdl:operation of a wsdl:binding that describes it.Wsdl header %s is not present in soap message.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_MUSTUNDERSTAND	WARNING	R1013: A MESSAGE containing a soap:mustUnderstand attribute MUST only use the lexical forms "0" and "1". Value of 'soap:mustUnderstand' attribute is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NODEPLOYED	WARNING	Resource id of deployment is NULL.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NOENVELOPEWSDLMATCH	WARNING	BP1701: The envelope does not conform to the SOAP schema located at 'http://schemas.xmlsoap.org/soap/envelope/' or 'http://www.w3.org/2003/05/soap-envelope'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NONPOSTREQUEST	WARNING	R1114: An INSTANCE SHOULD use a "405 Method not Allowed" HTTP status code if the request method was not "POST". We got	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			'%d' HTTP status code.	
APPFW_RESP	APPFW_XML_WSI_ERR_NONXMLREQUEST	WARNING	R1115: An INSTANCE SHOULD use a "415 Unsupported Media Type" HTTP status code if a HTTP request message's Content-Type header field-value is not permitted by its WSDL description. we got '%d' HTTP status code.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NOPORTURL	WARNING	Port URL is NULL.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NOREQWSDLMATCH	WARNING	BP1011: The content of the request envelope does not match the wsdl:message definition.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_NORESPWSDLMATCH	WARNING	BP1013 The content of the response envelope does not match the wsdl:message definition.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_NOWSDLDEPLOYED	WARNING	Deployed resource is not WSDL.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_ONEWAYRESPONSE	WARNING	R2714: For one-way operations, an INSTANCE MUST NOT return a HTTP response that contains a SOAP envelope. Specifically, the HTTP response entity-body must be empty. we got the element soap:Envelope.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_RESPONSESTATUS200OR202	WARNING	R1112: An INSTANCE SHOULD use either a "200 OK" or "202 Accepted" HTTP status code for a response that does do not contain a SOAP message but indicates successful HTTP outcome of a request. We got '%d'	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			HTTP response code.	
APPFW_RESP	APPFW_XML_WSI_ERR_RESPONSEWRAPPED	WARNING	R2729: A MESSAGE described with an rpc-literal binding that is a response message MUST have a wrapper element whose name is the corresponding wsdl:operation name suffixed with the string "Response". Element name should be '%sResponse' but got '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPACTIONHEADERMATCH	WARNING	R2744: A HTTP request MESSAGE MUST contain a SOAPAction HTTP header field with a quoted value equal to the value of the soapAction attribute of soapbind:operation, if present in the corresponding WSDL description.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			Expected '%s' soapAction but got '%s' soapAction in HTTP header.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPACTIONQUOTED	WARNING	R1109: The value of the SOAPAction HTTP header field in a HTTP request MESSAGE MUST be a quoted string. We got '%s' SOAPAction HTTP header.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTALLOWEDCHILD	WARNING	R1000: When a MESSAGE contains a soap:Fault element, that element MUST NOT have element children other than faultcode, faultstring, faultactor and detail. Element '%s' is not a allowed child of 'soap:Fault'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTCHILDQ	WARNING	R1001: When a MESSAGE contains a soap:Fault element its	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			element children MUST be unqualified. 'soap:Fault' child '%s' should be unqualified.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTINHTTP	WARNING	R1126: An INSTANCE MUST use a "500 Internal Server Error" HTTP status code if the response message is a SOAP Fault. We got '%s' HTTP response code.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTNONENV	WARNING	R1003: A RECEIVER MUST accept fault messages that have any number of qualified or unqualified attributes, including zero, appearing on the detail element. The namespace of qualified attributes can be anything other than the namespace of	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			the qualified document element 'Envelope'. Namespace of attribute '%s' should not be the same as that of the qualified document element 'Envelope'.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPGOODXML10	WARNING	BP1601: The soap:Envelope or soap:Body does not conform to XML 1.0. Error is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_STDFAULTCODE	WARNING	R1004: When a MESSAGE contains a faultcode element the content of that element SHOULD be one of the fault codes defined in SOAP 1.1 or a namespace qualified fault code. 'faultcode' '%s' is not defined in SOAP 1.1 or it is not	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			namespace qualified.	
APPFW_RESP	APPFW_XML_WSI_ERR_USEHTTP10OR11	WARNING	R1141: A MESSAGE MUST be sent using either HTTP/1.1 or HTTP/1.0. We got HTTP version '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_USEHTTP11	WARNING	R1140: A MESSAGE SHOULD be sent using HTTP/1.1. We got HTTP version '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_WSICLAIMSWELLFORMED	WARNING	R0004: A MESSAGE MAY contain conformance claims, as specified in the conformance claim schema. Either 'conformsTo' attribute is absent or 'soap:mustUnderstand' attribute is present on element '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_WSI_LIST_NULL	WARNING	AppFw XML WSI List Null.	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_XMLPI	WARNING	R1009: A MESSAGE MUST NOT contain Processing Instructions. Name of Processing Instruction is '%s'.	"%s"
APPFW_RESP	APPFW_XML_WSI_ERR_XSINIL	WARNING	R2211: A MESSAGE described with an rpc-literal binding MUST NOT have the xsi:nil attribute with a value of "1" or "true" on the part accessors. Element '%s' must not have the xsi:nil attribute.	"%s"
APPFW_RESP	APPFW_XML_XSD_COMPILE_INIT_ERR	WARNING	Error during initialization	"%s"
APPFW_RESP	APPFW_XML_XSD_COMPILE_LOADXSD_ERR	WARNING	AppFw XML XSDLOAD Failed during Compile	"%s"
APPFW_RESP	APPFW_XML_XSD_COMPILE_NOMODEL_ERR	WARNING	No XSModel to print	"%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
APPFW_RESP	APPFW_XML_XSD_COMPILE_PARSE_ERR	INFO	Error during parsing	"%s"
APPFW_RESP	APPFW_XML_XSD_COMPILE_UNEXPECTED_ERR	WARNING	Unexpected exception during parsing	"%s"
APPFW_RESP	APPFW_XML_ERR_SOAP_FAULT	WARNING	Message contains SOAP Fault.	"%s"
APPFW_RESP	APPFW_XML_SOAP_FAULT_CONTENTS	WARNING	Dumps the SOAP Fault contents to Audit log.	"%s"
APPFW_RESP	AF_INVALID_HTTP_HEADER	WARNING	Error while parsing HTTP headers.	"Errorwhileparsingheaders.");
APPFW_RESP	APPFW_CCARD_MATCH_IN_SIGNATURES	INFO	Credit card violation in signatures	"%s"
AAATM	LOGIN	INFO	Login to AAA TM vserver succeeds	"User%s-Client_ip%s-""Nat_ip%s-Vserver%s:%d-Browser_type\"%s\"-Group(s)\"%s\""
AAATM	LOGOUT	INFO	AAA TM session logged out	"User%s-""Client_ip%s-Nat_ip%s-""Vserver%s:%d-""Start_time\"%s\"-End_time\"%s\"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
				-Duration%s-"" Http_resources _accessed%s-" "Total_TCP_co nnections%d-"" Total_policies_a llowed%d- Total_policies_d enied%d-""Total _bytes_send%s - Total_bytes_rec v%s-""Total_co mpressedbytes _send%s- Total_compress edbytes_recv% s-""Compressio n_ratio_send% d.%02u% %-""Compressi on_ratio_recv% d.%02u% %-""LogoutMet hod\"%s\"- Group(s)\"%s\""
AAATM	HTTPREQUES T	DEBUG	A AAA TM session receives a HTTP request	"%sUser%s:Gr oup(s) %s:Vserver%s: %d- %s:SSOis%s: %s%s%s"
AAATM	HTTP_RESOU RCEACCESS_ DENIED	NOTICE	A http resource access is denied by policy engine. The denied policy name is	"- Denied_by_poli cy\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
			captured in the log message.	
NSIP6	IPV6_DUPLICATED	INFO	IPv6 address got duplicated.	"%s"
ICA	SESSION_SETUP	DEBUG	ICA session setup	"session_guid%s-device_serial_number%u-client_cookie:%s-""flags%llu-session_setup_time%s-client_ip%s-client_type%d-""client_launcher%d-client_version%s-client_hostname%s-""domain_name%s-server_name%s-connection_priority%u-""access_type%d-status%d"
ICA	CHANNEL_UPDATE	DEBUG	ICA channel update	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-channel_update_begin%s-channel_update_end%s-""channel_id_1%d-

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
				channel_id_1_val%d-channel_id_2%d-channel_id_2_val%d-""channel_id_3%d-channel_id_3_val%d-channel_id_4%d-channel_id_4_val%d-""channel_id_5%d-channel_id_5_val%d"
ICA	SESSION_UPDATE	DEBUG	ICA session update	"session_guid%s-device_serial_number%u-""client_cookie%s-flags%llu-""nsica_session_status%d-""nsica_session_client_ip%s-""nsica_session_client_port%d-""nsica_session_server_ip%s-""nsica_session_server_port%d-""nsica_session_reconnect_count%d-""nsica_session_acr_count%d-""connection_priority%u-""timestamp%s-"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ICA	L7_LATENCY_UPDATE	DEBUG	ICA L7 latency update	"session_guid%s-device_serial_number%u-""client_cookie%s-flags%llu-""nsica_status%d-""L7LatencyThresholdFactor%d-""L7LatencyWaittime%d-""L7LatencyNotifyInterval%d-""L7LatencyMaxNotifyCount%d-""L7ThresholdBreachAvgClientsideLatency%d-""L7ThresholdBreachMaxClientsideLatency%d-""L7ThresholdBreachAvgServersideLatency%d-""L7ThresholdBreachMaxServersideLatency%d-""MinL7Latency%d-"
ICA	SESSION_TERMINATE	DEBUG	ICA session terminate	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-session_end_time%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ICA	NETWORK_UPDATE	DEBUG	ICA network update	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-ica_rtt%u-clientside_rxbytes%u-""clientside_txbytes%u-clientside_packet_retransmits%u-""serverside_packet_retransmits%u-clientside_rtt%u-serverside_rtt%u-""clientside_jitter%u-serverside_jitter%u"
ICA	APPLICATION_LAUNCH	DEBUG	ICA application launch	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-startup_duration%u-launch_mechanism%u-""app_launch_time%s-app_process_id%u-""app_name%s-module_path%s"

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
ICA	APPLICATION_TERMINATE	DEBUG	ICA application terminate	"session_guid%s-device_serial_number%u-client_cookie%s-""flags%llu-app_termination_type%d-app_process_id%u-""app_termination_time%s"
RDP	RDP_EVENT	DEBUG	RDP event	"UserName:%s
RDP	RDP_CONNECTION_EVENT	DEBUG	RDP connection event	"UserName:%s
CLI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""
GUI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""
API	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""
CONSOLE	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in NetScaler	"User%s-Remote_ip%s-Command\"%s\"-""Status\"%s\""

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
BOT	BOT_WHITELIST	INFO	Bot whitelist	"Allowwhitelist.URL: %.*sLogMsg: %.*s"
BOT	BOT_BLACKLIST	INFO	Bot blacklist	"Disallowblacklist.URL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_IPREP	INFO	Bot iprep	"DisallowmaliciousIP.Category: %.*sURL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_DEVICE_FINGERPRINT	INFO	Bot Device FingerPrint	"DeviceFingerPrintvalidationfailed.URL: %.*s<%s>"
BOT	BOT_RATE_LIMIT	INFO	Bot Rate Limit	"ConnectionRateLimithit.URL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_STATIC_SIGNATURE	INFO	Bot static signature log.	"Botsignaturematched.User-Agent: %s(%u)Type: %sURL: %.*s<%s>"
BOT	BOT_SIG_AUTO_UPDATE	INFO	Bot signature auto update log.	"BotNewSignatureAvailable.NewlyaddedRules: %uDeletedRules:%u\n"

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
BOT	BOT_TRAP_URL	INFO	Bot Trap URL.	"TrapURLSession.URL: %.*s<%s>"
BOT	BOT_CAPTCHA	INFO	Bot Captcha	"Captchamaxattempts(%u)exceeded.URL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_TPS	INFO	Bot TPS.	"TPSIPlimithitforIP:%sURL: %.*sLogMsg: %.*s<%s>"
BOT	BOT_LOGEXPRESSION	INFO	Bot Log Expression.	"%s%u-PPE%u%s%s%.*s%.*s"
ROUTING	PAL	VARIABLE		
PITBOSS	PITBOSS	INFO	Pitboss watch is added on a process with the process id pid	Adding pitboss watch on (%d)
PITBOSS	PITBOSS	INFO	Pitboss watch is deleted on a process with the process id pid	Deleting watch on (%d)
PITBOSS	PB_SYSTEM_RESTART	ALERT	Process with pid has reached maximum number of restarts.Therefore the systemis being restarted	proc (%d) (%s) has had its maximum number of restarts (%d), rebooting the system

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	DESCRIPTION	CATEGORY	FORMAT
PITBOSS	PB_PROCESS_RESTART	ALERT	Process with pid is being restarted.The message indicates the number of times the process has been restarted	Restarting process old pid (%d) action (%s)
ROUTING	ROUTE_ADVERTISED	INFO	Route Advertised	ROUTE (%s %s %s) - ADVERTISED
ROUTING	ROUTE_WITHDRAWN	INFO	Route Withdrawn	ROUTE (%s %s %s) - WITHDRAWN
ROUTING	ROUTE_RELEARN		Route Relearnt	RELEARN (0x%x)
ROUTING	ROUTE_HASTATE	INFO	HA state change	HASTATE (0x%x)
CVPN	CVPN_INPUT_URL	DEBUG	The input URL before rewriting	HTML_URL %s
CVPN	CVPN_REWRITTEN_URL	DEBUG	The rewritten url	REWRITTEN_URL %.*s
CVPN	CVPN_PCRE_ERROR	DEBUG	PCRE Error	Regex %.*s : PCRE_ERROR %d
CVPN	CVPN_MATCHED_URL	DEBUG	The matched url	MATCHED_URL %.*s

ADC 12.1 Syslog Message Reference

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
TCP	CONN_DELINK	INFO	When a server side and a client side TCP connection is delinked.These are the connections which are being tracked by Citrix ADC like HTTP	
TCP	CONN_TERMINATE	INFO	When a TCP connection terminates.The logged data indicates the number of bytes transmitted and received over the connection and lso the connection start and end time	
TCP	OTHERCONN_DELINK	INFO	When a server side and a client side TCP connection is delinked.These are the connections which are not	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			being tracked by Citrix ADC like FTP,telnet etc	
TCP	NAT_CONN_DELINK	INFO	When a server side and a client side TCP connection for RNAT are delinked we need to log the connection information	
TCP	NAT_OTHERCONN_DELINK	INFO	When a server side and a client side TCP connection for RNAT are delinked we need to log the connection information	
ACL	ACL_PKT_LOG	INFO	ACL Packet Log	
ACL	ACL6_PKT_LOG	INFO	ACL6 Packet Log	
LSN	LSN_SESSION	INFO	Info of LSN session created	
LSN	LSN_EIM_MAPPING	INFO	Info of LSN Endpoint independent mapping created	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
LSN	LSN_ADDR_MAPPING	INFO	Info of LSN Address dependent mapping created	
LSN	LSN_ADDRPORT_MAPPING	INFO	Info of LSN Address and Port dependent mapping created	
LSN	PPTP_LOG	INFO	Info of PPTP connection	
LSN	LSN_PORTBLOCK	INFO	Info of LSN Portblock mappings	
LSN	LSN_DETERMINISTIC	INFO	Info of LSN Portblock mappings	
ALG	ALG_SIP_PARSE_PACKET_EVENT	ERROR	Error of SIP packet parsing	
ALG	ALG_SDP_PARSE_PACKET_EVENT	ERROR	Error of SDP packet parsing	
ALG	ALG_SIP_ERROR_PACKET_EVENT	ERROR	Error of SIP protocol	
ALG	ALG_DHT_ERROR_PACKET_EVENT	ERROR	Error of SIP ALG DHT	
ALG	ALG_SIP_GENERATE_ERRO	ERROR	Error of SIP generate	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	R_PACKET_EVENT			
ALG	ALG_SIP_INFO_PACKET_EVENT	INFO	Info of SIP packet	
ALG	ALG_SIP_INFO_DELETE_CALL_PACKET_EVENT	INFO	Info of SIP call deletion	
ALG	ALG_RTSP_INFO_PACKET_EVENT	INFO	Info of RTSP packet	
ALG	ALG_RTSP_INFO_DELETE_CALL_PACKET_EVENT	INFO	Info of RTSP call deletion	
ALG	ALG_RTSP_PARSE_PACKET_EVENT	ERROR	Error of RTSP packet parsing	
ALG	ALG_RTSP_ALG_PACKET_EVENT	ERROR	Error of RTSP ALG	
ALG	ALG_RTSP_DHT_PACKET_EVENT	ERROR	Error of RTSP DHT	
DNS	DNS_QUERY	INFO	Information of DNS queries recieved by the DNS endpoints on Citrix ADC	
DNS	DNS_RESPONSE	INFO	Information of DNS responses served by the	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			DNS endpoints on Citrix ADC to clients	
DNS	DNS_ERROR	INFO	Information of errors encountered during DNS packet processing on Citrix ADC	
SUBSCRIBER	SESSION_EVENT	INFO	Subscriber Session Event Info	
SUBSCRIBER	SESSION_FAILURE	ERROR	Subscriber Session Failure Info	
SSLI	INTERCEPT_LOG	INFO	SSL Interception Success Log	
SSLI	BYPASS_LOG	INFO	SSL Interception Bypass Log	
SSLI	DROPPED_LOG	INFO	SSL Interception Dropped Log	
URLFILT	URLFILT_LOG	INFO	URL filtering Log	
CI	ICAP_LOG	INFO	ICAP transaction Log.	
CI	ICAPC_LOG	INFO	ICAP custom log.	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
CI	INLINE_INSPECTION_LOG	INFO	Inline Inspection transaction Log.	
CI	TRAFFIC_MIRROR_LOG	INFO	Traffic Mirror transaction Log.	
AAA	LOGIN_FAILED	WARNING	When the aaa module failed to login the user.The reason for failure is indicated in the message	
AAA	EXTRACTED_GROUPS	INFO	After a user logs in the group for the user has been extracted	
UI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in Citrix ADC	
SSLVPN	LOGIN	INFO	SSLVPN login succeeds	
SSLVPN	LOGOUT	INFO	SSLVPN session logs out.Logout method is captured in the message	
SSLVPN	ICASTART	INFO	ICA application launch has started	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
SSLVPN	ICAEND_CONNSTAT	INFO	ICA application has terminated	
SSLVPN	TCPCONNSTAT	INFO	Logs the TCP connection related information for a connection belonging to a SSLVPN session	
SSLVPN	TCPCONN_TIMEDOUT	INFO	An SSLVPN connection timed out.The information about the connection start and end time the amount of data transferred and received are present in the message date	
SSLVPN	UDPFLOWSTAT	INFO	When a UDP flow , within a SSLVPN session, terminates	
SSLVPN	HTTPREQUEST	INFO	A SSLVPN session receives a HTTP request	
SSLVPN	NONHTTP_RESOURCEACCESS_DENIED	NOTICE	A non-http resource access is denied by	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			policy engine. The denied policy name is captured in the log message.	
SSLVPN	HTTP_RESOURCEACCESS_DENIED	NOTICE	A http resource access is denied by policy engine. The denied policy name is captured in the log message.	
SSLVPN	LICLMT_REACHED	INFO	SSLVPN license limit reached	
SSLVPN	CLISEC_CHECK	ERROR	Logs with severity ERROR when client security check for a SSLVPN session fails, otherwise logs with severity DEBUG	
SSLVPN	CLISEC_EXP_EVAL	ERROR	Logs with severity ERROR when client security expression evaluates to False, otherwise logs with severity DEBUG	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
SSLVPN	STA_VALIDATE_RESP	INFO	After a user logs into SSLVPN and the group for the user has been extracted	
SSLVPN	REMOVE_SESSION_DEBUG	DEBUG	Gives debug information of session before removing session intentionally	
EVENT	ALERTSTARTED	ALERT	When SNMP module starts an alarm (usually when the value of a monitored attribute crosses the threshold value	
EVENT	ALERTENDED	ALERT	When SNMP module stops an alarm (usually when the value of a monitored attribute returns to normal state)	
EVENT	STARTSYS	INFO	When Citrix ADC starts	
EVENT	STARTCPU	INFO	When a particular CPU starts	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
EVENT	DEVICEDOWN	NOTICE	Whenever a device is down	
EVENT	DEVICEOFS	NOTICE	Whenever a device is out of service	
EVENT	DEVICEUP	NOTICE	Whenever a device is up	
EVENT	NICSTART	NOTICE	When the network interface is started	
EVENT	NICSTOP	NOTICE	When the network interface is stopped	
EVENT	NICHANG	NOTICE	When the network interface is in hung state	
EVENT	NICRESET	NOTICE	When the network interface is reset	
EVENT	NICMIGRATE	NOTICE	When an interface is bound or unbound from a channel	
EVENT	STOPSYS	INFO	When the Citrix ADC system is stopped	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
EVENT	FREEBADMEM	EMERGENCY	When bad memory is freed (internal error)	
EVENT	FREEDUPMEM	EMERGENCY	When duplicate memory free occurs (internal error)	
EVENT	FREEEXTMEM	EMERGENCY	When memory is freed from a wrong pool (internal error)	
EVENT	PROPSUCCESS	INFO	When HA propagation is successful	
EVENT	PROPFAIL	ALERT	When HA propagation fails	
EVENT	STATECHANGE	0	HA State has changed.The string along with the message gives more information	
EVENT	CLSTATECHANGE	0	Cluster State has changed.The string along with the message gives more information	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
EVENT	CACHESTART FLUSH	INFO	When cache flush starts	
EVENT	CACHESTOPF LUSH	INFO	When cache flush is complete	
EVENT	MONITORTH	INFO	The monitor bound to the service has hit threshold limit	
EVENT	MONITORDOW N	INFO	The monitor bound to the service is down.	
EVENT	MONITORUP	INFO	The monitor bound to the service is up.	
EVENT	ROUTEDOWN	INFO	When the route is down	
EVENT	ROUTEUP	INFO	When the route is up	
EVENT	VRID6DOWN	INFO	When the vrid changes state to backup	
EVENT	VRIDDOWN	INFO	When the vrid changes state to backup	
EVENT	VRIDUP	INFO	When the vrid changes state to master	
EVENT	VRIDINIT	INFO	When the vrid changes state to init	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
EVENT	VIPRHIUP	INFO	When the rhi state of vip changes to up	
EVENT	VIPRHIDOWN	INFO	When the rhi state of vip changes to down	
EVENT	STARTSAVECONFIG	INFO	When save configuration started	
EVENT	STOPSAVECONFIG	INFO	When save configuration has stopped	
EVENT	CONFIGSTART	INFO	When Citrix ADC starts to read the configuration from ns.conf file (during boot-up)	
EVENT	CONFIGEND	INFO	When Citrix ADC has completed reading the configuration from ns.conf file (during boot-up)	
EVENT	NICLACPSC	NOTICE		
EVENT	NICLOW_THROUGHPUT	NOTICE	When an interface's throughput is less than the min required	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
EVENT	NICNORMAL_THROUGHPUT	NOTICE	When an interface's throughput is equal or greater than the min required	
EVENT	NICPOWERON	NOTICE	When an interface is powered on	
EVENT	NICPOWEROFF	NOTICE	When an interface is powered off	
EVENT	DHCPSVRERR	INFO	When the DHCP server sends an invalid setting	
EVENT	DHCPCAQUIRE	INFO	When the DHCP client aquires a lease	
EVENT	DHCPCRELEASE	INFO	When the DHCP client releases a lease	
EVENT	DHCPCDEPENDPBR	INFO	When the DHCP lease is released and a PBR is dependent on the lease ip	
EVENT	ROUTE6DOWN	INFO	When the route6 is down	
EVENT	ROUTE6UP	INFO	When the route6 is up	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
EVENT	UNKNOWN	DEBUG		
SSLLOG	SSL_HANDSHAKE_FAILURE	DEBUG	SSL HandShake Failure	
SSLLOG	SSL_HANDSHAKE_SUCCESS	DEBUG	SSL HandShake Success	
SSLLOG	SSL_CERT_EXPIRY_IMMINENT	NOTICE	SSL Certificate Expiry Imminent	
SSLLOG	SSL_HANDSHAKE_ISSUERNAME	DEBUG	SSL Client Certificate IssueName	
SSLLOG	SSL_HANDSHAKE_SUBJECTNAME	DEBUG	SSL Client Certificate SubjectName	
SSLLOG	SSL_CRL_UPDATE_SUCCESS	NOTICE	SSL CRL Update Success	
SSLLOG	SSL_CRL_UPDATE_FAILURE	NOTICE	SSL CRL Update Failure	
SSLLOG	SSL_OCSPURL_RESOLVE_SUCCESS	DEBUG	SSL OCSPURL Resolve Success	
SSLLOG	SSL_OCSPURL_RESOLVE_FAILURE	DEBUG	SSL OCSPURL Resolve Failure	
SSLLOG	SSL_OCSPRESPONSE_SUCCESS	DEBUG	SSL OCSPResponse Success	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
SSLLOG	SSL_OCSPRESPONSE_FAILURE	DEBUG	SSL OCSPResponse Failure	
APPFW	APPFW_STARTURL	INFO	AppFw StartURL violation	
APPFW	APPFW_MULTIPLE_HEADER	INFO	AppFw Multiple Header violation	
APPFW	APPFW_LOGEXPRESSION	INFO	AppFw Log Expression details	
APPFW	APPFW_DENYURL	INFO	AppFw DenyURL violation	
APPFW	APPFW_CONTENT_TYPE	INFO	AppFw Content-type violation	
APPFW	APPFW_REFERER_HEADER	INFO	AppFw Referer header violation	
APPFW	APPFW_CSRF_TAG	INFO	AppFw CSRF tag violation	
APPFW	APPFW_XSS	INFO	AppFw XSS violation	
APPFW	APPFW_XML_XSS	WARNING	AppFw XSS violation in XML	
APPFW	APPFW_SQL	INFO	AppFw SQL Injection violation	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_SQL	WARNING	AppFw SQL Injection violation in XML	
APPFW	APPFW_COOKIE	INFO	AppFw Cookie Consistency violation	
APPFW	APPFW_FIELDCONSISTENCY	INFO	AppFw Field Consistency violation	
APPFW	APPFW_BUFFEROVERFLOW_URL	INFO	AppFw Buffer Overflow violation in URL	
APPFW	APPFW_BUFFEROVERFLOW_COOKIE	INFO	AppFw Buffer Overflow violation in Cookie	
APPFW	APPFW_BUFFEROVERFLOW_HDR	INFO	AppFw Buffer Overflow violation in HTTP Headers	
APPFW	APPFW_FIELDFORMAT	INFO	AppFw Field Format violation	
APPFW	APPFW_SAFECOMMERCE	INFO	AppFw Safe Commerce violation	
APPFW	APPFW_SAFECOMMERCE_XFORM	INFO	AppFw Safe Commerce violation detected and transformed	
APPFW	APPFW_SAFEOBJECT	INFO	AppFw Safe Object violation	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_POLICY_HIT	INFO	AppFw profile invoked	
APPFW	APPFW_POLICY_HIT_BUILTIN	INFO	AppFw built-in profile invoked	
APPFW	APPFW_MAX_UPLOADS	INFO	File uploads exceed the allowed number	
APPFW	APPFW_SIGNATURE_MATCH	INFO	AppFw signature violation	
APPFW	AF_BIND_TO_PROFILE	INFO	AppFw rule bound to HTML profile	
APPFW	AF_BIND_XML_TO_PROFILE	INFO	AppFw rule bound to XML profile	
APPFW	AF_ADD_FIELDTYPE	INFO	Add an AppFw Field Type	
APPFW	AF_ADD_PROFILE	INFO	Add an AppFw profile	
APPFW	AF_RM_FIELDTYPE	INFO	Remove an Appfw Field Type	
APPFW	AF_RM_PROFILE	INFO	Remove an AppFw profile	
APPFW	AF_ADD_CFFIELD	INFO	Add a confidential field	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	AF_RM_CFFIELD	INFO	Remove a confidential field	
APPFW	AF_400_RESP	INFO	AppFw Request error. Generated 400 Response	
APPFW	AF_5XX_RESP	INFO	Server Error. Generated 5XX Response	
APPFW	AF_RESPONSE_PARSE_ERR	INFO	Response parse error	
APPFW	AF_MEMORY_ERR	WARNING	Memory allocation request for %lu bytes failed	
APPFW	AF_ORIGIN_SERVER_RESP_MISMATCH_ERR	WARNING	Origin server sent a response but AppFw needed something different	
APPFW	AF_MALFORMED_REQ_ERR	INFO	Malformed request	
APPFW	AF_UTHREAD_STACK_ERR	ERROR	Appsecure uthread at 0x%x had a stack error	
APPFW	AF_SIGNATURE_ERR	INFO	Signature error	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	AF_STREAM_MSG_ERR	WARNING	Stream message error	
APPFW	AF_GENERIC_ERR_WITH_URL	WARNING	Generic error with URL	
APPFW	APPFW_XML_ATTACHMENT_FOUND	WARNING	Attachment Found in the XML Message.	
APPFW	APPFW_XML_ATTACHMENT_ERR_CALLBACK_NULL	WARNING	XML Attachment CallBack is NULL but HTTP message is MIME Attachment message.	
APPFW	APPFW_XML_ATTACHMENT_ERR_INVALID HEADER	WARNING	String %s is supposed to be MIME Header. But it is not according to the format of Mime Header HeaderName:HeaderValue	
APPFW	APPFW_XML_ATTACHMENT_ERR_INVALID_HEADER	WARNING	HTTP Content type should be 'application/xop+xml' or '\^(text|application)/([a-zA-Z]*\+xml|xml)' but we got %s.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_ATTACHMENT_ERR_BOUNDARY_MISMATCH	WARNING	Boundary mismatch in mime message.	
APPFW	APPFW_XML_ERR_NO_ATTACHMENT_BOUNDARY	WARNING	The message having content-type as 'Multipart/ Related' and not having a boundary is invalid.	
APPFW	APPFW_XML_ATTACHMENT_ERR_MAX_SIZE	WARNING	XML Message has an Attachment with size greater than the Configured Max Attachment Size.	
APPFW	APPFW_XML_ATTACHMENT_ERR_CONTENT_TYPE	WARNING	XML Message has an Attachment with Illegal Content-Type	
APPFW	APPFW_XML_DDOS_ERR_MSG_SEND_FAIL	WARNING	AppFw XML DDoS Send Fail Error.	
APPFW	APPFW_XML_DOS_ERR_CHAR_DATA_LENGTH	WARNING	Exceeds max character data length.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_DOS_ERR_DTD	WARNING	DTD present in the XML message.	
APPFW	APPFW_XML_DOS_ERR_EXT_ENTITY	WARNING	External entities present in the XML message.	
APPFW	APPFW_XML_DOS_ERR_MAX	WARNING	AppFw XML DoS Maximum Error	
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTES	WARNING	Element '%s' exceeds maximum attributes per element.	
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_NAME_LENGTH	WARNING	In element '%s' an attribute exceeds maximum name length.	
APPFW	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_VALUE_LENGTH	WARNING	In element '%s' attribute '%s' exceeds maximum attribute value length.	
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENTS	WARNING	Element '%s' exceeds maximum elements per message.	
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_CHILDREN	WARNING	Parent of element '%s' exceeds maximum	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			children at element '%s'.	
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_DEPTH	WARNING	Element '%s' exceeds maximum element depth.	
APPFW	APPFW_XML_DOS_ERR_MAX_ELEMENT_NAME_LENGTH	WARNING	Element '%s' exceeds maximum element name length.	
APPFW	APPFW_XML_DOS_ERR_MAX_FILE_SIZE	WARNING	Message size exceeds max size.	
APPFW	APPFW_XML_DOS_ERR_MAX_NODES	WARNING	Node '%s' exceeds maximum nodes per message.	
APPFW	APPFW_XML_DOS_ERR_MIN_FILE_SIZE	WARNING	Message size less than min size.	
APPFW	APPFW_XML_ERR_NOT_WELLFORMED	WARNING	Message is not a well-formed XML.	
APPFW	APPFW_XML_DOS_ERR_PI	WARNING	Processing instructions present in the XML message.	
APPFW	APPFW_XML_DOS_ERR_MAX_NAMESPACES	WARNING	Element '%s' exceeds maximum	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			active namespaces.	
APPFW	APPFW_XML_DOS_ERR_MAX_NAMESPACEURI_LENGTH	WARNING	In element '%s' a namespace exceeds maximum uri length.	
APPFW	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSION_DEPTH	WARNING	Exceeds max entity expansion depth	
APPFW	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSIONS	WARNING	Exceeds max number of entity expansions	
APPFW	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_SIZE	WARNING	Exceeds max total SOAP array size	
APPFW	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_RANK	WARNING	Exceeds max SOAP array rank	
APPFW	APPFW_XML_ERR_CUSTOM	WARNING	AppFw XML internal error	
APPFW	APPFW_XML_ERR_DDOS_CONNECT_TO_SERVER_FAILED	WARNING	AppFw XML DDoS Connect to Server Failed.	
APPFW	APPFW_XML_ERR_DDOS_INTERATION_SO	WARNING	AppFw XML DDoS Interaction	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	CKET_OPEN_FAIL		socket open Failed.	
APPFW	APPFW_XML_ERR_DDOS_INVALID_CONFIG_FILE	WARNING	AppFw XML DDoS Invalid Config File.	
APPFW	APPFW_XML_ERR_DDOS_NO_FOLDER_INSTALLATION_PATH	WARNING	AppFw XML DDoS No Folder Installation Path.	
APPFW	APPFW_XML_ERR_DDOS_OPEN_CONFIG_FILE_FAIL	WARNING	AppFw XML DDoS Failure to Open Config File.	
APPFW	APPFW_XML_ERR_DOS_TRIGGERED	WARNING	Denial of Service Error.	
APPFW	APPFW_XML_ERR_ENV_NOT_SET	WARNING	Environment variable QTHOME not set.	
APPFW	APPFW_XML_ERR_HASH_INSERT	WARNING	Problems inserting a namespace into the hash table.	
APPFW	APPFW_XML_ERR_HASH_LOOKUP	WARNING	Problems getting the key of a namespace from the hash table.	
APPFW	APPFW_XML_ERR_INITIALIZ	WARNING	Unable to initialize XML tokenizer.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	ING_TOKENIZER			
APPFW	APPFW_XML_ERR_INVALID_FILE	WARNING	Unable to open the file.	
APPFW	APPFW_XML_ERR_INVALID_STATE	WARNING	AppFw XML Internal State Invalid.	
APPFW	APPFW_XML_ERR_INVALID_XPATH	WARNING	Invalid XPath.	
APPFW	APPFW_XML_ERR_LOW_MEMORY	WARNING	AppFw XML Low memory.	
APPFW	APPFW_XML_ERR_CHARDATA_LIMIT_EXCEEDED	WARNING	AppFw XML character data size exceeds the limit of 30MB	
APPFW	APPFW_XML_ERR_MALFORMED_ADDRESS	WARNING	Malformed address	
APPFW	APPFW_XML_ERR_NO_DIME	WARNING	NS-XML APPFW supports SwA and MTOM SOAP attachments, but attachment with this message is DIME.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_ERR_OPERATION_CALLBACK	WARNING	Problems registering callbacks for operations.	
APPFW	APPFW_XML_ERR_PREFIX_LENGTH_EXCEEDED	WARNING	Prefix length %d exceeded, encountered length is %d.	
APPFW	APPFW_XML_ERR_READ_FAILED	WARNING	AppFw XML Read Failure	
APPFW	APPFW_XML_ERR_STREAM_POP	WARNING	Problems during pop of the node out of the XML stream.	
APPFW	APPFW_XML_ERR_STREAM_PUSH	WARNING	Problems during push of the node into the XML stream.	
APPFW	APPFW_XML_ERR_UNSUPPORTED_PORT	WARNING	Port in address %s is greater than 65535.	
APPFW	APPFW_XML_ERR_UNSUPPORTED_PROTOCOL	WARNING	Unsupported protocol	
APPFW	APPFW_XML_ERR_VALIDATION_FAILED	WARNING	AppFw XML Validation Failed	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_NULL	WARNING	AppFw XML Context is NULL.	
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_STATE_NULL	WARNING	Context user state is NULL; internal error.	
APPFW	APPFW_XML_PACKET_PROCESSING_ERR_MESSAGE_CONFIG_NULL	WARNING	Message config struct is NULL.	
APPFW	APPFW_XML_VALIDATION_ERR_ABSTRACT_ELEMENT	WARNING	Cannot instantiate abstract element	
APPFW	APPFW_XML_VALIDATION_ERR_ABSTRACT_TYPE	WARNING	Cannot instantiate abstract type '%s', for element '%s'.	
APPFW	APPFW_XML_VALIDATION_ERR_ADDHEADERS	WARNING	Additional soap header %s present in soap message.	
APPFW	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MAX_OCCURS	WARNING	Attribute '%s' appears more than once in element '%s'.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MIN_OCCURS	WARNING	Required attribute missing in element	
APPFW	APPFW_XML_VALIDATION_ERR_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	
APPFW	APPFW_XML_VALIDATION_ERR_CONTENT_MODEL_VIOLATED	WARNING	Content model of element '%s' not satisfied.	
APPFW	APPFW_XML_VALIDATION_ERR_CORRUPT_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	
APPFW	APPFW_XML_VALIDATION_ERR_CORRUPT_SCHEMA	WARNING	Error compiling the schema	
APPFW	APPFW_XML_VALIDATION_ERR_DATATYPE_ENGINE_INIT	WARNING	Initialization of the datatype engine failed.	
APPFW	APPFW_XML_VALIDATION_ERR_INTERNAL	WARNING	Internal corruption of WSDL in-memory structure.	
APPFW	APPFW_XML_VALIDATION_E	WARNING	Attribute '%s' is invalid.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	RR_INVALID_ATTRIBUTE			
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_COMBINATION	WARNING	Invalid configuration for soap validation.	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_COMPILED_WSDL	WARNING	Not able to open compiled WSDL.	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_CONTENT_MODEL	WARNING	Element '%s' has invalid content model.	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_DATATYPE	WARNING	Data type is invalid.	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_ELEMENT	WARNING	Invalid element.	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_FILE	WARNING	Not able to open the file.	
APPFW	APPFW_XML_VALIDATION_ERR_INVALID_TYPE_SUBSTITUTION	WARNING	Did not get expected type for element '%s', got '%s'.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_VALIDATION_ERR_LOADING	WARNING	Unable to load validation engine.	
APPFW	APPFW_XML_VALIDATION_ERR_MAX	WARNING	AppFw XML Validation Max Error.	
APPFW	APPFW_XML_VALIDATION_ERR_NOSERVICEURL	WARNING	Service Url is not present or NULL.	
APPFW	APPFW_XML_VALIDATION_ERR_NOT_SUPPORTED	WARNING	Feature not supported.	
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_BODY	WARNING	Soap Body structure check failed.	
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_ENVELOPE	WARNING	Soap Envelope structure check failed.	
APPFW	APPFW_XML_VALIDATION_ERR_SOAP_HEADER	WARNING	Soap Header structure check failed.	
APPFW	APPFW_XML_VALIDATION_ERR_UNBOUNDED_PREFIX	WARNING	Prefix '%s' is unbounded.	
APPFW	APPFW_XML_VALIDATION_LOAD_ERR_CO	WARNING	Element '%s' cannot be nil.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	NTENTS_CANNOT_BE_NIL			
APPFW	APPFW_XML_VALIDATION_LOAD_ERR_NIL_WITH_CONTENTS	WARNING	Element '%s' is nil, cannot have contents.	
APPFW	APPFW_XML_VALIDATION_ERR_REX_STACK_OVERFLOW	WARNING	Level of recursion more than maximum allowed depth.	
APPFW	APPFW_XML_VALIDATION_ERR_REX_STACK_EMPTY	WARNING	Trying to pop from an empty stack.	
APPFW	APPFW_XML_VALIDATION_ERR_SOAPBODY_EMPTY	WARNING	Both SOAP Body and SOAP Header are empty in the SOAP request.	
APPFW	APPFW_XML_GENERIC_ERR_EMPTYBODY_REQ	WARNING	Request body is empty in the XML request.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_DATATYPE_VALUE	WARNING	Value should be of type '%s'.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_EL	WARNING	Element '%s' cannot appears at this location.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	EMENT_INVALID_LOCATION			
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_FACET_MISMATCH	WARNING	Facet mismatch.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_FAILED	WARNING	AppFw XML Validator Load Failed.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_ATTRIBUTE_VALUE	WARNING	Attribute '%s' has invalid value '%s'.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_DATATYPE	WARNING	Invalid schema datatype.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_SCHEMA_NODE_TYPE	WARNING	Invalid schema node type.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_VALUE_FOR_FIXED	WARNING	Value '%s' does not match FIXED constraint '%s'.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIS	WARNING	List length is greater than max allowed.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	T_LENGTH_GT_MAX			
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_INVALID	WARNING	List length is invalid.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_LT_MIN	WARNING	List length is lesser than min allowed.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_MAX	WARNING	AppFw XML Validation Maximum Load Error.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_REQUIRED_ATTRIBUTE	WARNING	Missing require attribute '%s' in element '%s'.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_SCHEMA_COMPILATION	WARNING	Error code in the compiled Schema is being ignored.	
APPFW	APPFW_XML_VALIDATOR_LOAD_ERR_WSDL_COMPILATION	WARNING	Error code in the compiled WSDL is being ignored.	
APPFW	APPFW_XML_WSI_ERR_AC	WARNING	R2735: A MESSAGE described with an rpc-literal	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	CELEMENTNAMESPACED		binding MUST place the part accessor elements for parameters and return value in no namespace. Element '%s' must be unqualified.	
APPFW	APPFW_XML_WSI_ERR_ARRAYTYPE	WARNING	R2113: A MESSAGE containing serialized arrays MUST NOT include the soapenc:arrayType attribute. Element '%s' must not include the soapenc:arrayType attribute.	
APPFW	APPFW_XML_WSI_ERR_BAD_ENV_NAMESPACE	WARNING	R1015: A RECEIVER MUST generate a fault if they encounter a message whose document element has a local name of "Envelope" but a namespace name that is not "http://schemas.xmlso	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			ap.org/soap/envelope/" or "http://www.w3.org/2003/05/soap-envelope". We got namespace '%s' in SOAP Request.	
APPFW	APPFW_XML_WSI_ERR_BINDINGFAULTRESP	WARNING	R2740: The response envelope contained soap:Fault element(s), but they were not defined in the WSDL description. Element '%s' should be defined as soap:fault in WSDL description.	
APPFW	APPFW_XML_WSI_ERR_BODY_CHILD_NAMESPACE	WARNING	R1014: The children of the soap:Body element in a MESSAGE MUST be namespace qualified. Unqualified children of soap:Body is '%s'.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_WSI_ERR_BODY_ENV_NAMESPACE	WARNING	BP1201: The envelope does not use SOAP 1.1 or SOAP 1.2, i.e. does not have a document element named "Envelope" or a namespace value of http://schemas.xmlsoap.org/soap/envelope/ or http://www.w3.org/2003/05/soap-envelope. We got namespace '%s'.	
APPFW	APPFW_XML_WSI_ERR_CHILDAFTERBODY	WARNING	R1011: A MESSAGE MUST NOT have any element children of soap:Envelope following the soap:Body element. Element '%s' should not appear after 'soap:Body' element.	
APPFW	APPFW_XML_WSI_ERR_CLA	WARNING	R0007: A SENDER MUST NOT use the	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	IM_MUSTUNDERSTAND		soap:mustUnderstand attribute when sending a SOAP header block containing a conformance claim. soap:mustUnderstand attribute is present on element '%s'.	
APPFW	APPFW_XML_WSI_ERR_CTXT_NULL	WARNING	AppFw XML WSI Internal Context NULL	
APPFW	APPFW_XML_WSI_ERR_DOCTYPEALLOWED	WARNING	R1008: A MESSAGE MUST NOT contain a Document Type Declaration. DOCTYPE name is '%s'.	
APPFW	APPFW_XML_WSI_ERR_DOT_NOTATION	WARNING	R1031: When a MESSAGE contains a faultcode element the content of that element SHOULD NOT use of the SOAP 1.1 "dot" notation to refine the meaning of the Fault. Data '%s' should not	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			contain 'DOT'(.) in it.	
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLE	WARNING	R1005: A MESSAGE MUST NOT contain soap:encodingStyle attribute on any of the elements whose namespace is the same as the namespace of the qualified document element 'Envelope'. 'soap:encodingStyle' attribute should not be present on element '%s'.	
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLECHILD	WARNING	R1006: A MESSAGE MUST NOT contain soap:encodingStyle attributes on any element that is a child of soap:Body. 'soap:encodingStyle' attribute should not be present on immidiate child '%s' of soap:Body.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_WSI_ERR_ENCODINGSTYLEGRANDCHILD	WARNING	R1007: A MESSAGE described in an rpc-literal binding MUST NOT contain soap:encodingStyle attribute on any elements are grandchildren of soap:Body. 'soap:encodingStyle' attribute should not be present on grandchild '%s' of soap:Body.	
APPFW	APPFW_XML_WSI_ERR_ENVELEMENTSNOATTRIBUTES	WARNING	R1032: The soap:Envelope, soap:Header, and soap:Body elements in an ENVELOPE MUST NOT have attributes in the same namespace as that of the qualified document element 'Envelope'. Attribute '%s' should not be in the same namespace as that of the qualified document	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			element 'Envelope'.	
APPFW	APPFW_XML_WSI_ERR_ENVNONAMESPACE	WARNING	R1033: An ENVELOPE SHOULD NOT contain the namespace declaration xmlns:xml="http://www.w3.org/XML/1998/namespace".	
APPFW	APPFW_XML_WSI_ERR_GOODRESPONSE200	WARNING	R1111: An INSTANCE SHOULD use a "200 OK" HTTP status code for responses that contain a SOAP message that is not a SOAP fault. We should not get 'soap:Fault' element when HTTP response code is '200 OK'.	
APPFW	APPFW_XML_WSI_ERR_HEADER_HAS_WSICLAIM	WARNING	R0005: A MESSAGE's conformance claims MUST be carried as SOAP header blocks. Element '%s' should be immidiate	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			children of soap:Header.	
APPFW	APPFW_XML_WSI_ERR_HTTP	WARNING	AppFw XML WSI HTTP Error	
APPFW	APPFW_XML_WSI_ERR_ISHTTPPOST	WARNING	R1132: A HTTP request MESSAGE MUST use the HTTP POST method. We got '%s' HTTP method.	
APPFW	APPFW_XML_WSI_ERR_ISUTF8OR16	WARNING	R1012: A MESSAGE MUST be serialized as either UTF-8 or UTF-16. We got encoding '%s'.	
APPFW	APPFW_XML_WSI_ERR_MSGHASALLHEADERS	WARNING	R2738: A MESSAGE MUST include all soapbind:headers specified on a wsdl:input or wsdl:output of a wsdl:operation of a wsdl:binding that describes it.Wsdl header %s is not present in soap message.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_WSI_ERR_MUSTUNDERSTAND	WARNING	R1013: A MESSAGE containing a soap:mustUnderstand attribute MUST only use the lexical forms "0" and "1". Value of 'soap:mustUnderstand' attribute is '%s'.	
APPFW	APPFW_XML_WSI_ERR_NODEPLOYED	WARNING	Resource id of deployment is NULL.	
APPFW	APPFW_XML_WSI_ERR_NOENVELOPEWSDLMATCH	WARNING	BP1701: The envelope does not conform to the SOAP schema located at 'http://schemas.xmlsoap.org/soap/envelope/' or 'http://www.w3.org/2003/05/soap-envelope'.	
APPFW	APPFW_XML_WSI_ERR_NONPOSTREQUEST	WARNING	R1114: An INSTANCE SHOULD use a "405 Method not Allowed" HTTP status code if the request method was not "POST". We got	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			'%d' HTTP status code.	
APPFW	APPFW_XML_WSI_ERR_NONXMLREQUEST	WARNING	R1115: An INSTANCE SHOULD use a "415 Unsupported Media Type" HTTP status code if a HTTP request message's Content-Type header field-value is not permitted by its WSDL description. we got '%d' HTTP status code.	
APPFW	APPFW_XML_WSI_ERR_NOPORTURL	WARNING	Port URL is NULL.	
APPFW	APPFW_XML_WSI_ERR_NOREQWSDLMATCH	WARNING	BP1011: The content of the request envelope does not match the wsdl:message definition.	
APPFW	APPFW_XML_WSI_ERR_NORESPWSDLMATCH	WARNING	BP1013 The content of the response envelope does not match the wsdl:message definition.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_WSI_ERR_NOWSDLDEPLOYED	WARNING	Deployed resource is not WSDL.	
APPFW	APPFW_XML_WSI_ERR_ONEWAYRESPONSE	WARNING	R2714: For one-way operations, an INSTANCE MUST NOT return a HTTP response that contains a SOAP envelope. Specifically, the HTTP response entity-body must be empty. we got the element soap:Envelope.	
APPFW	APPFW_XML_WSI_ERR_RESPONSESTATUS200OR202	WARNING	R1112: An INSTANCE SHOULD use either a "200 OK" or "202 Accepted" HTTP status code for a response that does do not contain a SOAP message but indicates successful HTTP outcome of a request. We got '%d'	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			HTTP response code.	
APPFW	APPFW_XML_WSI_ERR_RESPONSEWRAPPED	WARNING	R2729: A MESSAGE described with an rpc-literal binding that is a response message MUST have a wrapper element whose name is the corresponding wsdl:operation name suffixed with the string "Response". Element name should be '%sResponse' but got '%s'.	
APPFW	APPFW_XML_WSI_ERR_SOAPACTIONHEADERMATCH	WARNING	R2744: A HTTP request MESSAGE MUST contain a SOAPAction HTTP header field with a quoted value equal to the value of the soapAction attribute of soapbind:operation, if present in the corresponding WSDL description.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			Expected '%s' soapAction but got '%s' soapAction in HTTP header.	
APPFW	APPFW_XML_WSI_ERR_SOAPACTIONQUOTED	WARNING	R1109: The value of the SOAPAction HTTP header field in a HTTP request MESSAGE MUST be a quoted string. We got '%s' SOAPAction HTTP header.	
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTALLOWEDCHILD	WARNING	R1000: When a MESSAGE contains a soap:Fault element, that element MUST NOT have element children other than faultcode, faultstring, faultactor and detail. Element '%s' is not a allowed child of 'soap:Fault'.	
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTCHILDQ	WARNING	R1001: When a MESSAGE contains a soap:Fault element its	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			element children MUST be unqualified. 'soap:Fault' child '%s' should be unqualified.	
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTINHTTP	WARNING	R1126: An INSTANCE MUST use a "500 Internal Server Error" HTTP status code if the response message is a SOAP Fault. We got '%s' HTTP response code.	
APPFW	APPFW_XML_WSI_ERR_SOAPFAULTNONENV	WARNING	R1003: A RECEIVER MUST accept fault messages that have any number of qualified or unqualified attributes, including zero, appearing on the detail element. The namespace of qualified attributes can be anything other than the namespace of	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			the qualified document element 'Envelope'. Namespace of attribute '%s' should not be the same as that of the qualified document element 'Envelope'.	
APPFW	APPFW_XML_WSI_ERR_SOAPGOODXML10	WARNING	BP1601: The soap:Envelope or soap:Body does not conform to XML 1.0. Error is '%s'.	
APPFW	APPFW_XML_WSI_ERR_STDFAULTCODE	WARNING	R1004: When a MESSAGE contains a faultcode element the content of that element SHOULD be one of the fault codes defined in SOAP 1.1 or a namespace qualified fault code. 'faultcode' '%s' is not defined in SOAP 1.1 or it is not	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			namespace qualified.	
APPFW	APPFW_XML_WSI_ERR_USEHTTP10OR11	WARNING	R1141: A MESSAGE MUST be sent using either HTTP/1.1 or HTTP/1.0. We got HTTP version '%s'.	
APPFW	APPFW_XML_WSI_ERR_USEHTTP11	WARNING	R1140: A MESSAGE SHOULD be sent using HTTP/1.1. We got HTTP version '%s'.	
APPFW	APPFW_XML_WSI_ERR_WSICLAIMSWELLFORMED	WARNING	R0004: A MESSAGE MAY contain conformance claims, as specified in the conformance claim schema. Either 'conformsTo' attribute is absent or 'soap:mustUnderstand' attribute is present on element '%s'.	
APPFW	APPFW_XML_WSI_ERR_WSI_LIST_NULL	WARNING	AppFw XML WSI List Null.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_WSI_ERR_XMLPI	WARNING	R1009: A MESSAGE MUST NOT contain Processing Instructions. Name of Processing Instruction is '%s'.	
APPFW	APPFW_XML_WSI_ERR_XSINIL	WARNING	R2211: A MESSAGE described with an rpc-literal binding MUST NOT have the xsi:nil attribute with a value of "1" or "true" on the part accessors. Element '%s' must not have the xsi:nil attribute.	
APPFW	APPFW_XML_XSD_COMPILE_INIT_ERR	WARNING	Error during initialization	
APPFW	APPFW_XML_XSD_COMPILE_LOADXSD_ERR	WARNING	AppFw XML XSDLOAD Failed during Compile	
APPFW	APPFW_XML_XSD_COMPILE_NOMODEL_ERR	WARNING	No XSModel to print	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_XML_XSD_COMPILE_PARSE_ERR	INFO	Error during parsing	
APPFW	APPFW_XML_XSD_COMPILE_UNEXPECTED_ERR	WARNING	Unexpected exception during parsing	
APPFW	APPFW_XML_ERR_SOAP_FAULT	WARNING	Message contains SOAP Fault.	
APPFW	APPFW_XML_SOAP_FAULT_CONTENTS	WARNING	Dumps the SOAP Fault contents to Audit log.	
APPFW	AF_INVALID_HTTP_HEADER	WARNING	Error while parsing HTTP headers.	
APPFW	APPFW_CCARD_MATCH_IN_SIGNATURES	INFO	Credit card violation in signatures	
APPFW	APPFW_SESSIONLIMIT	INFO	AppFw Session Limit reached	
APPFW	AF_ADD_RFC PROFILE	INFO	Add an AppFw rfc profile	
APPFW	AF_RM_RFCPROFILE	INFO	Remove an AppFw rfc profile	
APPFW	APPFW_INV_RFC	INFO	RFC syntax violation. Generated 302 Response	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW	APPFW_NEW_SIGNATURE_ADDED	INFO	AppFw New Signature Added	
ROUTING	ZEBOS_CMD_EXECUTED	INFO	The ZebOS command executed.	
SNMP	TRAP_SENT	INFO	Trap Sent Information	
SNMP	TRAP_DROPPED	INFO	Trap Dropped information. Traps are dropped due to rate-limiting	
TRANSFORM	FILE_REQUEST	DEBUG	URL Transformation profile invoked	
TRANSFORM	REQ_PARSE_ERROR	WARNING	URL Transformation parsing error	
TRANSFORM	REQ_HEADER	DEBUG	URL Transformation in a request header	
TRANSFORM	RESP_HEADER	DEBUG	URL Transformation in a response header	
TRANSFORM	BODY_FRAG	DEBUG	URL Transformation in a response body	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
TRANSFORM	ACTION_MATCH	DEBUG	URL Transformation action matched URL	
TRANSFORM	ACTION_MISMATCH	DEBUG	URL Transformation action didn't match URL	
TRANSFORM	PCRE_ERROR	WARNING	URL Transformation regex error	
TRANSFORM	REQ_WRITE_ERROR	WARNING	URL Transformation error in a request header	
APPFW_RESP	APPFW_XML_XSS	WARNING	AppFw XSS violation in XML	
APPFW_RESP	APPFW_XML_SQL	WARNING	AppFw SQL Injection violation in XML	
APPFW_RESP	APPFW_XML_ATTACHMENT_FOUND	WARNING	Attachment Found in the XML Message.	
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_CALLBACK_NULL	WARNING	XML Attachment CallBack is NULL but HTTP message is MIME Attachment message.	
APPFW_RESP	APPFW_XML_ATTACHMENT	WARNING	String %s is supposed to be	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	_ERR_INVALID HEADER		MIME Header. But it is not according to the format of Mime Header HeaderName:HeaderValue	
APPFW_RESP	APPFW_XML_ ATTACHMENT _ERR_INVALID _HEADER	WARNING	HTTP Content type should be 'application/ xop+xml' or '\^(text| application)/([a-zA-Z]*\+xml| xml)' but we got %s.	
APPFW_RESP	APPFW_XML_ ATTACHMENT _ERR_BOUND ARY_MISMATC H	WARNING	Boundary mismatch in mime message.	
APPFW_RESP	APPFW_XML_ ERR_NO_ATTA CHMENT_BOU NDARY	WARNING	The message having content-type as 'Multipart/ Related' and not having a boundary is invalid.	
APPFW_RESP	APPFW_XML_ ATTACHMENT _ERR_MAX_SI ZE	WARNING	XML Message has an Attachment with size greater than the Configured Max Attachment Size.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_ATTACHMENT_ERR_CONTENT_TYPE	WARNING	XML Message has an Attachment with Illegal Content-Type	
APPFW_RESP	APPFW_XML_DDOS_ERR_MSG_SEND_FAIL	WARNING	AppFw XML DDoS Send Fail Error.	
APPFW_RESP	APPFW_XML_DOS_ERR_CHAR_DATA_LENGTH	WARNING	Exceeds max character data length.	
APPFW_RESP	APPFW_XML_DOS_ERR_DTD	WARNING	DTD present in the XML message.	
APPFW_RESP	APPFW_XML_DOS_ERR_EXT_ENTITY	WARNING	External entities present in the XML message.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX	WARNING	AppFw XML DoS Maximum Error	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTES	WARNING	Element '%s' exceeds maximum attributes per element.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_NAME_LENGTH	WARNING	In element '%s' an attribute exceeds maximum name length.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ATTRIBUTE_VALUE_LENGTH	WARNING	In element '%s' attribute '%s' exceeds maximum attribute value length.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENTS	WARNING	Element '%s' exceeds maximum elements per message.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_CHILDREN	WARNING	Parent of element '%s' exceeds maximum children at element '%s'.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_DEPTH	WARNING	Element '%s' exceeds maximum element depth.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ELEMENT_NAME_LENGTH	WARNING	Element '%s' exceeds maximum element name length.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_FILE_SIZE	WARNING	Message size exceeds max size.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NODES	WARNING	Node '%s' exceeds maximum nodes per message.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_DOS_ERR_MIN_FILE_SIZE	WARNING	Message size less than min size.	
APPFW_RESP	APPFW_XML_ERR_NOT_WELLFORMED	WARNING	Message is not a well-formed XML.	
APPFW_RESP	APPFW_XML_DOS_ERR_PI	WARNING	Processing instructions present in the XML message.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NAMESPACES	WARNING	Element '%s' exceeds maximum active namespaces.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_NAMESPACEURI_LENGTH	WARNING	In element '%s' a namespace exceeds maximum uri length.	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSION_DEPTH	WARNING	Exceeds max entity expansion depth	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_ENTITY_EXPANSIONS	WARNING	Exceeds max number of entity expansions	
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_SIZE	WARNING	Exceeds max total SOAP array size	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_DOS_ERR_MAX_SOAPARRAY_RANK	WARNING	Exceeds max SOAP array rank	
APPFW_RESP	APPFW_XML_ERR_CUSTOM	WARNING	AppFw XML internal error	
APPFW_RESP	APPFW_XML_ERR_DDOS_CONNECT_TO_SERVER_FAILED	WARNING	AppFw XML DDoS Connect to Server Failed.	
APPFW_RESP	APPFW_XML_ERR_DDOS_INTERATION_SOCKET_OPEN_FAIL	WARNING	AppFw XML DDoS Interaction socket open Failed.	
APPFW_RESP	APPFW_XML_ERR_DDOS_INVALID_CONFIG_FILE	WARNING	AppFw XML DDoS Invalid Config File.	
APPFW_RESP	APPFW_XML_ERR_DDOS_NO_FOLDER_INSTALLATION_PATH	WARNING	AppFw XML DDoS No Folder Installation Path.	
APPFW_RESP	APPFW_XML_ERR_DDOS_OPEN_CONFIG_FILE_FAIL	WARNING	AppFw XML DDoS Failure to Open Config File.	
APPFW_RESP	APPFW_XML_ERR_DOS_TRIGGERED	WARNING	Denial of Service Error.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_ERR_ENV_NOT_SET	WARNING	Environment variable QTHOME not set.	
APPFW_RESP	APPFW_XML_ERR_HASH_INSERT	WARNING	Problems inserting a namespace into the hash table.	
APPFW_RESP	APPFW_XML_ERR_HASH_LOOKUP	WARNING	Problems getting the key of a namespace from the hash table.	
APPFW_RESP	APPFW_XML_ERR_INITIALIZING_TOKENIZER	WARNING	Unable to initialize XML tokenizer.	
APPFW_RESP	APPFW_XML_ERR_INVALID_FILE	WARNING	Unable to open the file.	
APPFW_RESP	APPFW_XML_ERR_INVALID_STATE	WARNING	AppFw XML Internal State Invalid.	
APPFW_RESP	APPFW_XML_ERR_INVALID_XPATH	WARNING	Invalid XPath.	
APPFW_RESP	APPFW_XML_ERR_LOW_MEMORY	WARNING	AppFw XML Low memory.	
APPFW_RESP	APPFW_XML_ERR_CHARDATA_LIMIT_EXCEEDED	WARNING	AppFw XML character data size exceeds	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			the limit of 30MB	
APPFW_RESP	APPFW_XML_ERR_MALFORMED_ADDRESS	WARNING	Malformed address	
APPFW_RESP	APPFW_XML_ERR_NO_DIME	WARNING	NS-XML APPFW supports SwA and MTOM SOAP attachments, but attachment with this message is DIME.	
APPFW_RESP	APPFW_XML_ERR_OPERATION_CALLBACK	WARNING	Problems registering callbacks for operations.	
APPFW_RESP	APPFW_XML_ERR_PREFIX_LENGTH_EXCEEDED	WARNING	Prefix length %d exceeded, encountered length is %d.	
APPFW_RESP	APPFW_XML_ERR_READ_FAILED	WARNING	AppFw XML Read Failure	
APPFW_RESP	APPFW_XML_ERR_STREAM_POP	WARNING	Problems during pop of the node out of the XML stream.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_ERR_STREAM_PUSH	WARNING	Problems during push of the node into the XML stream.	
APPFW_RESP	APPFW_XML_ERR_UNSUPPORTED_PORT	WARNING	Port in address %s is greater than 65535.	
APPFW_RESP	APPFW_XML_ERR_UNSUPPORTED_PROTOCOL	WARNING	Unsupported protocol	
APPFW_RESP	APPFW_XML_ERR_VALIDATION_FAILED	WARNING	AppFw XML Validation Failed	
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_NULL	WARNING	AppFw XML Context is NULL.	
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ERR_CONTEXT_STATE_NULL	WARNING	Context user state is NULL; internal error.	
APPFW_RESP	APPFW_XML_PACKET_PROCESSING_ERR_MESSAGE_CONFIG_NULL	WARNING	Message config struct is NULL.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ABSTRACT_ELEMENT	WARNING	Cannot instantiate abstract element	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ABSTRACT_TYPE	WARNING	Cannot instantiate abstract type '%s', for element '%s'.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ADDHEADERS	WARNING	Additional soap header %s present in soap message.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MAX_OCCURS	WARNING	Attribute '%s' appears more than once in element '%s'.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_ATTRIBUTE_MIN_OCCURS	WARNING	Required attribute missing in element	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CONTENT_MODEL_VIOLATED	WARNING	Content model of element '%s' not satisfied.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CORRUPT_COMPILED_WSDL	WARNING	Compiled WSDL file is corrupt.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_VALIDATION_ERR_CORRUPT_SCHEMA	WARNING	Error compiling the schema	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_DATATYPE_ENGINE_INIT	WARNING	Initialization of the datatype engine failed.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INTERNAL	WARNING	Internal corruption of WSDL in-memory structure.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_ATTRIBUTE	WARNING	Attribute '%s' is invalid.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_COMBINATION	WARNING	Invalid configuration for soap validation.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_COMPILED_WSDL	WARNING	Not able to open compiled WSDL.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_CONTENT_MODEL	WARNING	Element '%s' has invalid content model.	
APPFW_RESP	APPFW_XML_VALIDATION_E	WARNING	Data type is invalid.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	RR_INVALID_DATATYPE			
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_ELEMENT	WARNING	Invalid element.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_FILE	WARNING	Not able to open the file.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_INVALID_TYPE_SUBSTITUTION	WARNING	Did not get expected type for element '%s', got '%s'.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_LOADING	WARNING	Unable to load validation engine.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_MAX	WARNING	AppFw XML Validation Max Error.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_NOSERVICEURL	WARNING	Service Url is not present or NULL.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_NOT_SUPPORTED	WARNING	Feature not supported.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_BODY	WARNING	Soap Body structure check failed.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_ENVELOPE	WARNING	Soap Envelope structure check failed.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_SOAP_HEADER	WARNING	Soap Header structure check failed.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_UNBOUNDED_PREFIX	WARNING	Prefix '%s' is unbounded.	
APPFW_RESP	APPFW_XML_VALIDATION_LOAD_ERR_CONTENTS_CANNOT_BE_NIL	WARNING	Element '%s' cannot be nil.	
APPFW_RESP	APPFW_XML_VALIDATION_LOAD_ERR_NIL_WITH_CONTENTS	WARNING	Element '%s' is nil, cannot have contents.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_REX_STACK_OVERFLOW	WARNING	Level of recursion more than maximum allowed depth.	
APPFW_RESP	APPFW_XML_VALIDATION_ERR_REX_STACK_EMPTY	WARNING	Trying to pop from an empty stack.	
APPFW_RESP	APPFW_XML_VALIDATION_E	WARNING	Both SOAP Body and SOAP Header	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	RR_SOAPBODY_EMPTY		are empty in the SOAP request.	
APPFW_RESP	APPFW_XML_GENERIC_ERR_EMPTYBODY_REQ	WARNING	Request body is empty in the XML request.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_DATATYPE_VALUE	WARNING	Value should be of type '%s'.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_ELEMENT_INVALID_LOCATION	WARNING	Element '%s' cannot appears at this location.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_FACET_MISMATCH	WARNING	Facet mismatch.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_FAILED	WARNING	AppFw XML Validator Load Failed.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_ATTRIBUTE_VALUE	WARNING	Attribute '%s' has invalid value '%s'.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INV	WARNING	Invalid schema datatype.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	ALID_DATATYPE			
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_SCHEMA_NODE_TYPE	WARNING	Invalid schema node type.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_INVALID_VALUE_FOR_FIXED	WARNING	Value '%s' does not match FIXED constraint '%s'.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_GT_MAX	WARNING	List length is greater than max allowed.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_INVALID	WARNING	List length is invalid.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_LIST_LENGTH_LT_MIN	WARNING	List length is lesser than min allowed.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_MAX	WARNING	AppFw XML Validation Maximum Load Error.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_RE	WARNING	Missing require attribute '%s' in element '%s'.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	QUIRED_ATTRIBUTE			
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_SCHEMA_COMPILATION	WARNING	Error code in the compiled Schema is being ignored.	
APPFW_RESP	APPFW_XML_VALIDATOR_LOAD_ERR_WSDL_COMPILATION	WARNING	Error code in the compiled WSDL is being ignored.	
APPFW_RESP	APPFW_XML_WSI_ERR_ACCELEMENTNAMESPACED	WARNING	R2735: A MESSAGE described with an rpc-literal binding MUST place the part accessor elements for parameters and return value in no namespace. Element '%s' must be unqualified.	
APPFW_RESP	APPFW_XML_WSI_ERR_ARRAYTYPE	WARNING	R2113: A MESSAGE containing serialized arrays MUST NOT include the soapenc:arrayType attribute. Element '%s' must not	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			include the soapenc:arrayType attribute.	
APPFW_RESP	APPFW_XML_WSI_ERR_BAD_ENV_NAMESPACE	WARNING	R1015: A RECEIVER MUST generate a fault if they encounter a message whose document element has a local name of "Envelope" but a namespace name that is not "http://schemas.xmlsoap.org/soap/envelope/" or "http://www.w3.org/2003/05/soap-envelope". We got namespace '%s' in SOAP Request.	
APPFW_RESP	APPFW_XML_WSI_ERR_BINDINGFAULTRESP	WARNING	R2740: The response envelope contained soap:Fault element(s), but they were not defined in the WSDL description. Element '%s' should be	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			defined as soap:fault in WSDL description.	
APPFW_RESP	APPFW_XML_WSI_ERR_BODY_CHILD_NAMESPACE	WARNING	R1014: The children of the soap:Body element in a MESSAGE MUST be namespace qualified. Unqualified children of soap:Body is '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_BODY_ENV_NAMESPACE	WARNING	BP1201: The envelope does not use SOAP 1.1 or SOAP 1.2, i.e. does not have a document element named "Envelope" or a namespace value of http://schemas.xmlsoap.org/soap/envelope/ or http://www.w3.org/2003/05/soap-envelope. We got namespace '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_CHI	WARNING	R1011: A MESSAGE	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	LDAFTERBODY		MUST NOT have any element children of soap:Envelope following the soap:Body element. Element '%s' should not appear after 'soap:Body' element.	
APPFW_RESP	APPFW_XML_WSI_ERR_CLAIM_MUSTUNDERSTAND	WARNING	R0007: A SENDER MUST NOT use the soap:mustUnderstand attribute when sending a SOAP header block containing a conformance claim. soap:mustUnderstand attribute is present on element '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_CTXT_NULL	WARNING	AppFw XML WSI Internal Context NULL	
APPFW_RESP	APPFW_XML_WSI_ERR_DOCTYPEALLOWED	WARNING	R1008: A MESSAGE MUST NOT contain a Document Type Declaration.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			DOCTYPE name is '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_DOT_NOTATION	WARNING	R1031: When a MESSAGE contains a faultcode element the content of that element SHOULD NOT use of the SOAP 1.1 "dot" notation to refine the meaning of the Fault. Data '%s' should not contain 'DOT'(.) in it.	
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLE	WARNING	R1005: A MESSAGE MUST NOT contain soap:encodingStyle attribute on any of the elements whose namespace is the same as the namespace of the qualified document element 'Envelope'. 'soap:encodingStyle' attribute should not be	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			present on element '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLECHILD	WARNING	R1006: A MESSAGE MUST NOT contain soap:encodingStyle attributes on any element that is a child of soap:Body. 'soap:encodingStyle' attribute should not be present on immidiate child '%s' of soap:Body.	
APPFW_RESP	APPFW_XML_WSI_ERR_ENCODINGSTYLEGRANDCHILD	WARNING	R1007: A MESSAGE described in an rpc-literal binding MUST NOT contain soap:encodingStyle attribute on any elements are grandchildren of soap:Body. 'soap:encodingStyle' attribute should not be present on grandchild '%s' of soap:Body.	
APPFW_RESP	APPFW_XML_WSI_ERR_EN	WARNING	R1032: The soap:Envelope,	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
	VELEMENTSNOATTRIBUTES		soap:Header, and soap:Body elements in an ENVELOPE MUST NOT have attributes in the same namespace as that of the qualified document element 'Envelope'. Attribute '%s' should not be in the same namespace as that of the qualified document element 'Envelope'.	
APPFW_RESP	APPFW_XML_WSI_ERR_ENVNONAMESPACE	WARNING	R1033: An ENVELOPE SHOULD NOT contain the namespace declaration xmlns:xml="http://www.w3.org/XML/1998/namespace".	
APPFW_RESP	APPFW_XML_WSI_ERR_GOODRESPONSE200	WARNING	R1111: An INSTANCE SHOULD use a "200 OK" HTTP status code for responses that contain a SOAP	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			message that is not a SOAP fault. We should not get 'soap:Fault' element when HTTP response code is '200 OK'.	
APPFW_RESP	APPFW_XML_WSI_ERR_HEADER_HAS_WSICLAIM	WARNING	R0005: A MESSAGE's conformance claims MUST be carried as SOAP header blocks. Element '%s' should be immidiate children of soap:Header.	
APPFW_RESP	APPFW_XML_WSI_ERR_HTTP	WARNING	AppFw XML WSI HTTP Error	
APPFW_RESP	APPFW_XML_WSI_ERR_ISHTTPPOST	WARNING	R1132: A HTTP request MESSAGE MUST use the HTTP POST method. We got '%s' HTTP method.	
APPFW_RESP	APPFW_XML_WSI_ERR_ISUTF8OR16	WARNING	R1012: A MESSAGE MUST be serialized as either UTF-8 or	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			UTF-16. We got encoding '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_MSGHASALLHEADERS	WARNING	R2738: A MESSAGE MUST include all soapbind:headers specified on a wsdl:input or wsdl:output of a wsdl:operation of a wsdl:binding that describes it.Wsdl header %s is not present in soap message.	
APPFW_RESP	APPFW_XML_WSI_ERR_MUSTUNDERSTAND	WARNING	R1013: A MESSAGE containing a soap:mustUnderstand attribute MUST only use the lexical forms "0" and "1". Value of 'soap:mustUnderstand' attribute is '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_NODEPLOYED	WARNING	Resource id of deployment is NULL.	
APPFW_RESP	APPFW_XML_WSI_ERR_NOENVELOPEWSDLMATCH	WARNING	BP1701: The envelope does not conform to the SOAP	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			schema located at 'http://schemas.xmlsoap.org/soap/envelope/' or 'http://www.w3.org/2003/05/soap-envelope'.	
APPFW_RESP	APPFW_XML_WSI_ERR_NONPOSTREQUEST	WARNING	R1114: An INSTANCE SHOULD use a "405 Method not Allowed" HTTP status code if the request method was not "POST". We got '%d' HTTP status code.	
APPFW_RESP	APPFW_XML_WSI_ERR_NONXMLREQUEST	WARNING	R1115: An INSTANCE SHOULD use a "415 Unsupported Media Type" HTTP status code if a HTTP request message's Content-Type header field-value is not permitted by its WSDL description. we got '%d' HTTP status code.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_NO PORTURL	WARNING	Port URL is NULL.	
APPFW_RESP	APPFW_XML_WSI_ERR_NO REQWSDLMAT CH	WARNING	BP1011: The content of the request envelope does not match the wsdl:message definition.	
APPFW_RESP	APPFW_XML_WSI_ERR_NO RESPWSDLMA TCH	WARNING	BP1013 The content of the response envelope does not match the wsdl:message definition.	
APPFW_RESP	APPFW_XML_WSI_ERR_NO WSDLDEPLOY ED	WARNING	Deployed resource is not WSDL.	
APPFW_RESP	APPFW_XML_WSI_ERR_ON EWAYRESPON SE	WARNING	R2714: For one-way operations, an INSTANCE MUST NOT return a HTTP response that contains a SOAP envelope. Specifically, the HTTP response entity-body must be empty. we got the	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			element soap:Envelope.	
APPFW_RESP	APPFW_XML_WSI_ERR_RESPONSESTATUS200OR202	WARNING	R1112: An INSTANCE SHOULD use either a "200 OK" or "202 Accepted" HTTP status code for a response that does do not contain a SOAP message but indicates successful HTTP outcome of a request. We got '%d' HTTP response code.	
APPFW_RESP	APPFW_XML_WSI_ERR_RESPONSEWRAPPED	WARNING	R2729: A MESSAGE described with an rpc-literal binding that is a response message MUST have a wrapper element whose name is the corresponding wsdl:operation name suffixed with the string "Response". Element name should be	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			'%sResponse' but got '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPACTIONHEADERMATCH	WARNING	R2744: A HTTP request MESSAGE MUST contain a SOAPAction HTTP header field with a quoted value equal to the value of the soapAction attribute of soapbind:operation, if present in the corresponding WSDL description. Expected '%s' soapAction but got '%s' soapAction in HTTP header.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPACTIONQUOTED	WARNING	R1109: The value of the SOAPAction HTTP header field in a HTTP request MESSAGE MUST be a quoted string. We got '%s' SOAPAction HTTP header.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTALLOWEDCHILD	WARNING	R1000: When a MESSAGE contains a soap:Fault element, that element MUST NOT have element children other than faultcode, faultstring, faultactor and detail. Element '%s' is not a allowed child of 'soap:Fault'.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTCHILDQ	WARNING	R1001: When a MESSAGE contains a soap:Fault element its element children MUST be unqualified. 'soap:Fault' child '%s' should be unqualified.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTINHTTP	WARNING	R1126: An INSTANCE MUST use a "500 Internal Server Error" HTTP status code if the response message is a SOAP Fault. We got '%s'	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			HTTP response code.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPFAULTNONENV	WARNING	R1003: A RECEIVER MUST accept fault messages that have any number of qualified or unqualified attributes, including zero, appearing on the detail element. The namespace of qualified attributes can be anything other than the namespace of the qualified document element 'Envelope'. Namespace of attribute '%s' should not be the same as that of the qualified document element 'Envelope'.	
APPFW_RESP	APPFW_XML_WSI_ERR_SOAPGOODXML10	WARNING	BP1601: The soap:Envelope or soap:Body does not conform to XML	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			1.0. Error is '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_STDFAULTCODE	WARNING	R1004: When a MESSAGE contains a faultcode element the content of that element SHOULD be one of the fault codes defined in SOAP 1.1 or a namespace qualified fault code. 'faultcode' '%s' is not defined in SOAP 1.1 or it is not namespace qualified.	
APPFW_RESP	APPFW_XML_WSI_ERR_USEHTTP10OR11	WARNING	R1141: A MESSAGE MUST be sent using either HTTP/1.1 or HTTP/1.0. We got HTTP version '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_USEHTTP11	WARNING	R1140: A MESSAGE SHOULD be sent using HTTP/1.1. We got HTTP version '%s'.	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	APPFW_XML_WSI_ERR_WSICLAIMSWELLFORMED	WARNING	R0004: A MESSAGE MAY contain conformance claims, as specified in the conformance claim schema. Either 'conformsTo' attribute is absent or 'soap:mustUnderstand' attribute is present on element '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_WSI_LIST_NULL	WARNING	AppFw XML WSI List Null.	
APPFW_RESP	APPFW_XML_WSI_ERR_XMLPI	WARNING	R1009: A MESSAGE MUST NOT contain Processing Instructions. Name of Processing Instruction is '%s'.	
APPFW_RESP	APPFW_XML_WSI_ERR_XSINIL	WARNING	R2211: A MESSAGE described with an rpc-literal binding MUST NOT have the xsi:nil attribute with a value of	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			"1" or "true" on the part accessors. Element '%s' must not have the xsi:nil attribute.	
APPFW_RESP	APPFW_XML_XSD_COMPILE_INIT_ERR	WARNING	Error during initialization	
APPFW_RESP	APPFW_XML_XSD_COMPILE_LOADXSD_ERR	WARNING	AppFw XML XSDLOAD Failed during Compile	
APPFW_RESP	APPFW_XML_XSD_COMPILE_NOMODEL_ERR	WARNING	No XSModel to print	
APPFW_RESP	APPFW_XML_XSD_COMPILE_PARSE_ERR	INFO	Error during parsing	
APPFW_RESP	APPFW_XML_XSD_COMPILE_UNEXPECTED_ERR	WARNING	Unexpected exception during parsing	
APPFW_RESP	APPFW_XML_ERR_SOAP_FAULT	WARNING	Message contains SOAP Fault.	
APPFW_RESP	APPFW_XML_SOAP_FAULT_CONTENTS	WARNING	Dumps the SOAP Fault contents to Audit log.	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
APPFW_RESP	AF_INVALID_HTTP_HEADER	WARNING	Error while parsing HTTP headers.	
APPFW_RESP	APPFW_CCARD_MATCH_IN_SIGNATURES	INFO	Credit card violation in signatures	
AAATM	LOGIN	INFO	Login to AAA TM vserver succeeds	
AAATM	LOGOUT	INFO	AAA TM session logged out	
AAATM	HTTPREQUEST	DEBUG	A AAA TM session receives a HTTP request	
AAATM	HTTP_RESOURCEACCESS_DENIED	NOTICE	A http resource access is denied by policy engine. The denied policy name is captured in the log message.	
NSIP6	IPV6_DUPLICATED	INFO	IPv6 address got duplicated.	
ICA	SESSION_SETUP	DEBUG	ICA session setup	
ICA	CHANNEL_UPDATE	DEBUG	ICA channel update	
ICA	SESSION_UPDATE	DEBUG	ICA session update	

ADC SYSLOG MESSAGES

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
ICA	L7_LATENCY_UPDATE	DEBUG	ICA L7 latency update	
ICA	SESSION_TERMINATE	DEBUG	ICA session terminate	
ICA	NETWORK_UPDATE	DEBUG	ICA network update	
ICA	APPLICATION_LAUNCH	DEBUG	ICA application launch	
ICA	APPLICATION_TERMINATE	DEBUG	ICA application terminate	
RDP	RDP_EVENT	DEBUG	RDP event	
RDP	RDP_CONNECTION_EVENT	DEBUG	RDP connection event	
CLI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in Citrix ADC	
GUI	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in Citrix ADC	
API	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command executed in Citrix ADC	
CONSOLE	CMD_EXECUTED	INFO	Logs the NSCLI/GUI command	

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
			executed in Citrix ADC	
ROUTING	PAL	VARIABLE		
PITBOSS	PITBOSS	INFO	Pitboss watch is added on a process with the process id pid	Adding pitboss watch on (%d)
PITBOSS	PITBOSS	INFO	Pitboss watch is deleted on a process with the process id pid	Deleting watch on (%d)
PITBOSS	PB_SYSTEM_RESTART	ALERT	Process with pid has reached maximum number of restarts.Therefore the systemis being restarted	proc (%d) (%s) has had its maximum number of restarts (%d), rebooting the system
PITBOSS	PB_PROCESS_RESTART	ALERT	Process with pid is being restarted.The message indicates the number of times the process has been restarted	Restarting process old pid (%d) action (%s)
ROUTING	ROUTE_ADVERTISED	INFO	Route Advertised	ROUTE (%s %s %s) - ADVERTISED

FEATURE	MESSAGE	CATEGORY	DESCRIPTION	FORMAT
ROUTING	ROUTE_WITHDRAWN	INFO	Route Withdrawn	ROUTE (%s %s %s) - WITHDRAWN
ROUTING	ROUTE_RELEARN		Route Relearnt	RELEARN (0x%x)
ROUTING	ROUTE_HASTATE	INFO	HA state change	HASTATE (0x%x)
CVPN	CVPN_INPUT_URL	DEBUG	The input URL before rewriting	HTML_URL %s
CVPN	CVPN_REWRITTEN_URL	DEBUG	The rewritten url	REWRITTEN_URL %.*s
CVPN	CVPN_PCRE_ERROR	DEBUG	PCRE Error	Regex %.*s : PCRE_ERROR %d
CVPN	CVPN_MATCHED_URL	DEBUG	The matched url	MATCHED_URL %.*s

Copyright and Trademark Notice

CITRIX SYSTEMS, INC., 2019. ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS OR USED TO MAKE DERIVATIVE WORK (SUCH AS TRANSLATION, TRANSFORMATION, OR ADAPTATION) WITHOUT THE EXPRESS WRITTEN PERMISSION OF CITRIX SYSTEMS, INC. ALTHOUGH THE MATERIAL PRESENTED IN THIS DOCUMENT IS BELIEVED TO BE ACCURATE, IT IS PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE ALL RESPONSIBILITY FOR THE USE OR APPLICATION OF THE PRODUCT(S) DESCRIBED IN THIS MANUAL.

CITRIX SYSTEMS, INC. OR ITS SUPPLIERS DO NOT ASSUME ANY LIABILITY THAT MAY OCCUR DUE TO THE USE OR APPLICATION OF THE PRODUCT(S) DESCRIBED IN THIS DOCUMENT. INFORMATION IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. COMPANIES, NAMES, AND DATA USED IN EXAMPLES ARE FICTITIOUS UNLESS OTHERWISE NOTED.